## **NMOCD**

HUBBS OCD DE	PARTMENT OF THE I	NTERIOR	The state of the s	OMB NO. 1004-0135 Expires: July 31, 2010	
HOBBS OCD DE	NOTICES AND DEDO	DTS ON WELLS	NMN	Serial No.	
AUG 2 2 po not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.		6. If Ind	6. If Indian, Allottee or Tribe Name		
RECE SUBMIT IN TRI	PLICATE - Other instruc	tions on reverse side.	7. If Un	t or CA/Agreement, Name and/or No	
1. Type of Well  Oil Well Gas Well Other  2. Name of Operator RIDGEWAY ARIZONA OIL CORP  Contact: JAMIE HOGUE E-Mail: jhogue@enhancedoilres.com				8. Well Name and No. FEDERAL 23 3  9. API Well No. 30-041-10529-00-S1	
		3b. Phone No. (include area Ph: 832.485.8522		de) 10. Field and Pool, or Exploratory CHAVEROO-SAN ANDRES	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish, and State		
Sec 23 T7S R33E SWSE 660FSL 1980FEL			ROOSEVELT COUN		
12. CHECK APPE	ROPRIATE BOX(ES) TO	INDICATE NATURE	OF NOTICE, REPORT,	OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Star	INT TO PA	
	☐ Alter Casing	☐ Fracture Treat	□ Reclamation	P&A NR	
Subsequent Report	☐ Casing Repair	☐ New Construction	n Recomplete	P&AR RX	
☐ Final Abandonment Notice	☐ Change Plans	☑ Plug and Abando	on		
	☐ Convert to Injection	☐ Plug Back	■ Water Disposal		
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi	ally or recomplete horizontally, rk will be performed or provide I operations. If the operation respondent Notices shall be file	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion	measured and true vertical depti M/BIA. Required subsequent re or recompletion in a new interva	ns of all pertinent markers and zones. ports shall be filed within 30 days I, a Form 3160-4 shall be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final 8.04/16 MIRU plugging equip 1/2" csg w/ 45 bbls of hot wate fluid. Pressure tested csg, held csg @ 2270'. Sqz'd 45 sx class Perf'd csg @ 1875'. Sqz'd 45 sx backhoe. Dug out cellar. Cut of	ally or recomplete horizontally, rk will be performed or provide a loperations. If the operation responded horizontal be file in the performent of the performent of the performent. POH w/ rods & purer. Set 4 1/2" CIBP @ 406 d 500 psi. Spot'd 25 sx class C cmt w/ 2% CACL & disx class C cmt & displace class C cmt & circulated toff wellhead. Welded on "Use of the performance	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion and only after all requirements, mp. Changed out wellhes of the control of the c	measured and true vertical depti M/BIA. Required subsequent re or recompletion in a new interva- including reclamation, have bee ad, NU BOP. Circulated 4 5 bbls mud laden 1. 08/05/16 Perf'd Tagged plug @ 2134'. 16 Tag'd plug @ 1768'. red in welder and	ns of all pertinent markers and zones. ports shall be filed within 30 days l, a Form 3160-4 shall be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for fi 08/04/16 MIRU plugging equip 1/2" csg w/ 45 bbls of hot wate fluid. Pressure tested csg @ 2270'. Sqz'd 45 sx clas Perf'd csg @ 1875'. Sqz'd 45 sx Perf'd csg @ 60'. Sqz'd 25 sx	ally or recomplete horizontally, rk will be performed or provide a loperations. If the operation responded horizontal be file in the performent of the performent of the performent. POH w/ rods & purer. Set 4 1/2" CIBP @ 406 d 500 psi. Spot'd 25 sx class C cmt w/ 2% CACL & disx class C cmt & displace class C cmt & circulated toff wellhead. Welded on "Use of the performance	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion and only after all requirements, mp. Changed out wellhes of the control of the c	measured and true vertical depti M/BIA. Required subsequent re or recompletion in a new interva- including reclamation, have bee ad, NU BOP. Circulated 4 5 bbls mud laden '. 08/05/16 Perf'd Tagged plug @ 2134'. 16 Tag'd plug @ 1768'. red in welder and larker". Backfilled	ns of all pertinent markers and zones. ports shall be filed within 30 days l, a Form 3160-4 shall be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final complete that the site is ready for final com	ally or recomplete horizontally, rk will be performed or provide to operations. If the operation respondence in the operation is pandoment Notices shall be file inal inspection.)  Dement. POH w/ rods & purer. Set 4 1/2" CIBP @ 406 d 500 psi. Spot'd 25 sx class C cmt w/ 2% CACL & disx class C cmt & displace class C cmt & circulated to file wellhead. Welded on "the paned location, and move the complete in true and correct.  Electronic Submission #3 For RIDGEWAY	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion of donly after all requirements, mp. Changed out wellhes of the control of the c	measured and true vertical deptim/BIA. Required subsequent re or recompletion in a new intervaluation in a new intervaluation of the properties of the prope	is of all pertinent markers and zones. ports shall be filed within 30 days il, a Form 3160-4 shall be filed once in completed, and the operator has	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final 2004/16 MIRU plugging equip 1/2" csg w/ 45 bbls of hot water fluid. Pressure tested csg, held csg @ 2270'. Sqz'd 45 sx class Perf'd csg @ 1875'. Sqz'd 45 sx backhoe. Dug out cellar. Cut of cellar. Removed deadmen, clear.	ally or recomplete horizontally, rk will be performed or provide to operations. If the operation resondoment Notices shall be file inal inspection.)  Dement. POH w/ rods & purer. Set 4 1/2" CIBP @ 406 d 500 psi. Spot'd 25 sx class C cmt w/ 2% CACL & d sx class C cmt & displace class C cmt & circulated to fif wellhead. Welded on "to eaned location, and mover true and correct.  Electronic Submission #3 For RIDGEWAY committed to AFMSS for pro	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion and only after all requirements, and only after all requirements, and consider the subset of	measured and true vertical deptim/BIA. Required subsequent re or recompletion in a new interval including reclamation, have been add, NU BOP. Circulated 4 bibls mud laden 1.08/05/16 Perfd 1.08/05/16 Perfd 2.134'. 16 Tagged plug @ 2134'. 16 Tag'd plug @ 1768'. Ted in welder and larker". Backfilled	is of all pertinent markers and zones. ports shall be filed within 30 days il, a Form 3160-4 shall be filed once in completed, and the operator has	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final content of the street of the st	ally or recomplete horizontally, rk will be performed or provide to operations. If the operation respondence in the operation is provided to operation. If the operation respondence in the operation is provided to operation.)  The operation of t	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion of donly after all requirements, and only after all requirements, mp. Changed out wellhes of the control of th	measured and true vertical depti M/BIA. Required subsequent re or recompletion in a new interval including reclamation, have been ad, NU BOP. Circulated 4 is bbls mud laden 1. 08/05/16 Perf'd. Tagged plug @ 2134'. 16 Tag'd plug @ 1768'. Ted in welder and larker". Backfilled  FOR R  Well Information System nt to the Roswell 5 on 08/15/2016 (16MMS028)	is of all pertinent markers and zones. ports shall be filed within 30 days li, a Form 3160-4 shall be filed once in completed, and the operator has	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final Os/04/16 MIRU plugging equip 1/2" csg w/ 45 bbls of hot water fluid. Pressure tested csg, held csg @ 2270'. Sqz'd 45 sx class Perf'd csg @ 1875'. Sqz'd 45 sx class Perf'd csg @ 60'. Sqz'd 25 sx backhoe. Dug out cellar. Cut of cellar. Removed deadmen, cless and the state of	ally or recomplete horizontally, rk will be performed or provide to operations. If the operation respandoment Notices shall be file inal inspection.)  Doment. POH w/ rods & purer. Set 4 1/2" CIBP @ 406 dt 500 psi. Spot'd 25 sx class C cmt w/ 2% CACL & disx class C cmt & displace class C cmt & circulated to file will be completed and correct.  Electronic Submission #3 For RIDGEWAY committed to AFMSS for propical control of the committed of the committed of the committed to AFMSS for propical control of the committed of the committed of the committed to AFMSS for propical control of the committed	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion of donly after all requirements, and only after all requirements, mp. Changed out wellhes of the control of th	measured and true vertical deptim/BIA. Required subsequent reor recompletion in a new interval including reclamation, have been add, NU BOP. Circulated 4 bibls mud laden 1.08/05/16 Perfd 1.08/0	ports shall be filed within 30 days il, a Form 3160-4 shall be filed once in completed, and the operator has	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final Abdeter	ally or recomplete horizontally, rk will be performed or provide to operations. If the operation respandoment Notices shall be file inal inspection.)  Doment. POH w/ rods & purer. Set 4 1/2" CIBP @ 406 dt 500 psi. Spot'd 25 sx class C cmt w/ 2% CACL & disx class C cmt & displace class C cmt & circulated to file will be completed and correct.  Electronic Submission #3 For RIDGEWAY committed to AFMSS for propical control of the committed of the committed of the committed to AFMSS for propical control of the committed of the committed of the committed to AFMSS for propical control of the committed	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion and only after all requirements, mp. Changed out wellhes of the control of the c	measured and true vertical deptim/BIA. Required subsequent reor recompletion in a new interval including reclamation, have been add, NU BOP. Circulated 4 bibls mud laden 1.08/05/16 Perfd 1.08/0	as of all pertinent markers and zones. ports shall be filed within 30 days il, a Form 3160-4 shall be filed once in completed, and the operator has	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final Os/04/16 MIRU plugging equip 1/2" csg w/ 45 bbls of hot water fluid. Pressure tested csg, held csg @ 2270'. Sqz'd 45 sx class Perf'd csg @ 1875'. Sqz'd 45 sx class Perf'd csg @ 60'. Sqz'd 25 sx backhoe. Dug out cellar. Cut of cellar. Removed deadmen, cless and the state of	ally or recomplete horizontally, rk will be performed or provide to operations. If the operation respondence in the operation is provided to operation. If the operation respondence in the operation is provided to operation.)  The provided the operation of the o	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion and only after all requirements, mp. Changed out wellher it. Circulated hole w/ 65 ass C cmt @ 4067-3710 isplaced to 2145'. WOC. d to 1750'. WOC. 08/08/o surface. 08/09/16 Mov. Underground Dry Hole M d off.  847754 verified by the BLI ARIZONA OIL CORP, secessing by DAVID GLASS Title GEDATE OR STA	measured and true vertical deptim/BIA. Required subsequent reor recompletion in a new interval including reclamation, have been add, NU BOP. Circulated 4 bibls mud laden 1.08/05/16 Perfd 1.08/0	as of all pertinent markers and zones. ports shall be filed within 30 days il, a Form 3160-4 shall be filed once in completed, and the operator has	

\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*

Approved as to plugging of the well bore. Liability under bond

**RECLAMATION DUE:** FEB 09 2017

Form 3160-5

is retained until surface restoration is completed.