Form 3 60-5 (April 2004)

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

UNITED STATES

SEP 0 6 2016 DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT CARISDAD FIELDS DECEMPENDICES AND REPORTS ON WELLOCD THE

SUBMIT IN TRIPLICATE- Other instructions on reverse side. 1. Type of Well Oil Well Oil Well Other				7. If Unit or CA/Agreement, Name and/or No.	
2. Name of Operator Matador Production Company				9. API Well No.	
		3b. Phone No. (include 575/623/6601			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Lea; Bone Spring	
Unit O, 330' FSL & 1,980' FEL, Sec 27: T19S, R34E				11. County or Parish, State Lea, New Mexico	
TYPE OF SUBMISSION		TY	PE OF ACTION		
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (State Reclamation Recomplete Temporarily Ab		Water Shut-Off Well Integrity Other Float Csg to Bottom -
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond NO. RLB0015172	operations. If the operationandonment Notices shall inspection.)	on results in a multiple com be filed only after all require	pletion or recompletion i ements, including reclam	n a new interv nation, have be	en completed, and the operator has
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond NO. RLB0015172 "Matador would like to plan on running. Matador requests appr	operations. If the operation and onment Notices shall had inspection.) having the option to froval to utilize casing of lateral production evacuation and a colla	on results in a multiple com be filed only after all require loat our casing to botton flotation tool on produc casing to TD. Current of pse force equal to 9.00 p	n. To do this we wou tion casing while run asing design (5-1/2" 2 pg mud gradient. At	n a new intervention, have be	al, a Form 3160-4 shall be filed once en completed, and the operator has lateral section filled with air whi e. Will place tool near base of leets minimum required collapse
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond NO. RLB0015172 "Matador would like to plan on running. Matador requests appicarve and plan to float ~7000 ft design factor with full internal of	operations. If the operation and onment Notices shall had inspection.) having the option to froval to utilize casing of lateral production evacuation and a colla	on results in a multiple com be filed only after all require loat our casing to botton flotation tool on produc casing to TD. Current of pse force equal to 9.00 p	n. To do this we wou tion casing while run asing design (5-1/2" 2 pg mud gradient. At	n a new intervention, have be	al, a Form 3160-4 shall be filed once en completed, and the operator has lateral section filled with air while. Will place tool near base of leets minimum required collapse
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond No. RLB0015172 "Matador would like to plan on running. Matador requests approurve and plan to float ~7000 ft design factor with full internal cout air through surface pressured." 4. I hereby certify that the foregoing	operations. If the operational and inspection.) having the option to froval to utilize casing of lateral production and a collage control equipment p	on results in a multiple com be filed only after all require loat our casing to botton flotation tool on produc casing to TD. Current of pse force equal to 9.00 p	n. To do this we wou tion casing while run asing design (5-1/2" 2 pg mud gradient. At	n a new intervention, have be	al, a Form 3160-4 shall be filed once en completed, and the operator has lateral section filled with air while. Will place tool near base of leets minimum required collapse
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond NO. RLB0015172 "Matador would like to plan on running. Matador requests approximate and plan to float ~7000 ft design factor with full internal cout air through surface pressured."	operations. If the operational and inspection.) having the option to froval to utilize casing of lateral production and a collage control equipment p	on results in a multiple combe filed only after all require filed only after all require float our casing to bottom flotation tool on product casing to TD. Current opse force equal to 9.00 prior to start of cementing	n. To do this we wou tion casing while run asing design (5-1/2" 2 pg mud gradient. At	n a new intervention, have be	al, a Form 3160-4 shall be filed once en completed, and the operator has lateral section filled with air while. Will place tool near base of leets minimum required collapse
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond No. RLB0015172 "Matador would like to plan on running. Matador requests approximate and plan to float ~7000 ft design factor with full internal cout air through surface pressured at the country of t	operations. If the operational and inspection.) having the option to froval to utilize casing of lateral production and a collage control equipment p	on results in a multiple combe filed only after all require filed only after all require float our casing to botton flotation tool on productasing to TD. Current casing to Toce equal to 9.00 prior to start of cementing	m. To do this we wou tion casing while run asing design (5-1/2" 2 pg mud gradient. At g."	n a new intervention, have be	al, a Form 3160-4 shall be filed once en completed, and the operator has lateral section filled with air while. Will place tool near base of leets minimum required collapse
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond No. RLB0015172 "Matador would like to plan on running. Matador requests approurve and plan to float ~7000 ft design factor with full internal cout air through surface pressured through surface pressured. 4. I hereby certify that the foregoing Name (Printed/Typed) Tammy R. Link Signature	operations. If the operational and onment Notices shall had inspection.) having the option to a royal to utilize casing of lateral production evacuation and a collar e control equipment p	on results in a multiple combe filed only after all require filed only after all require float our casing to bottom flotation tool on product casing to TD. Current opse force equal to 9.00 prior to start of cementing	n. To do this we wou tion casing while run asing design (5-1/2" 2 pg mud gradient. At g."	n a new intervation, have be alid have the lang into hol 20# P-110) m TD will rup	al, a Form 3160-4 shall be filed once en completed, and the operator has lateral section filled with air whi e. Will place tool near base of leets minimum required collapse
following completion of the involved testing has been completed. Final Abd determined that the site is ready for fir BLM Bond No. NMB001079 Surety Bond No. RLB0015172 "Matador would like to plan on running. Matador requests app curve and plan to float ~7000 ft design factor with full internal cout air through surface pressured through surface pressured. 14. I hereby certify that the foregoing Name (Printed/Typed) Tammy R. Link Signature	operations. If the operational and onment Notices shall had inspection.) having the option to a royal to utilize casing of lateral production evacuation and a collar e control equipment p	on results in a multiple combe filed only after all require filed only after all require float our casing to bottom flotation tool on productasing to TD. Current of the force equal to 9.00 prior to start of cementing to To start of cementing floating for the file force force equal to 9.00 prior to start of cementing floating	n. To do this we wou tion casing while run asing design (5-1/2" 2 pg mud gradient. At g."	n a new intervation, have be alid have the lang into hol 20# P-110) m TD will rup	al, a Form 3160-4 shall be filed once en completed, and the operator has lateral section filled with air whi e. Will place tool near base of leets minimum required collapse