Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103		
District I - (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013		
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	OIL CONSERVATION DIVISION	WELL API NO. 30-025-31366		
811 S. First St., Artesia, NM 8820 BBS District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	5. Indicate Type of Lease STATE X FEE			
District IV – (505) 476-3460 NOV 0 2 1220 S. St. Francis Dr., Santa Fe, NM 0 2 87505	6. State Oil & Gas Lease No.			
SUNDRY NOTIO (DO NOT USE THIS FORM FOR PROPOSA DIFFERENT RESERVOIR. USE "APPLICA	7. Lease Name or Unit Agreement Name			
PROPOSALS.) 1. Type of Well: Oil Well X	8. Well Number 72			
2. Name of Operator CHEVRON U.S.A.INC.	/	9. OGRID Number		
3. Address of Operator DEAUVILLEE BLVD. RM #n3002	MIDLAND, TX. 79706	10. Pool name or Wildcat LOVINGTON SAN ANDRES G/B		
	T 32.87163 X-LONG -103.30247 feet from the SOUTH line and 113	0feet from theEASTline		
Section 36	Township 16-S Range 36-E	NMPM County LEA		
	11. Elevation (Show whether DR, RKB, RT, GR, etc. 3,828' GR			

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF		SUBSEQUENT REPOR	
PERFORM REMEDIAL WORK	INT TO PA	REMEDIAL WORK	ERING CASING
TEMPORARILY ABANDON	P&ANR PMX	COMMENCE DRILLING OPNS.	NDA X
PULL OR ALTER CASING		CASING/CEMENT JOB	
DOWNHOLE COMMINGLE	P&A R		
CLOSED-LOOP SYSTEM		And the second second	
OTHER:		OTHER:	and the second sec

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.
8 5/8" 24 # @ 408', TOC SURF. 5 ½" 15.5# @ 5,070' TOC SURF, PERFS 4,620'- 5,016', TD 5,070'.

10/25-26/16 MIRU, NDWH, NU BOP & TEST. POOH TBG. & ESP.

10/27/16 RIH SET CIBP @ 4,560', RIH TAG CIBP @ 4,560' TEST CSG. 500# GOOD, MARK WHITAKER W/ NMOCD WITNESS MIX & SPOT 180 SX CL "C" CMT FROM 4,550'- 2,772', MIX & SPOT 30 SX CL "C" CMT FROM 2,112'- 1,816'.

10/28/16 MIX & SPOT 55 SX CL "C" CMT FROM 465' BACK TO SURFACE . CUT ALL CASING & ANCHORS & REMOVED 3' BELOW GRADE. WELD ON DRY HOLE MARKER AS PER RULE 19.15.7.14. OF NMAC, CLEAN LOCATION.

ALL CEMENT PLUGS CLASS "C", W/ CLOSED LOOP SYSTEM.

CA	B	0	N	D	: (03	29
~	-	~.		-	•		

Spud Date:	Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.				
hereby certify that the information above is true and	complete to the best of my knowledge	and belief.			
SIGNATURE	TITLE_Agent for Chevron	DATE10 / 31 / 16			
Type or print name Monty L. McCarver E-main	il address: _ monty.mccarver@cjes.com	PHONE: _713-325-6288			
For State Use Only APPROVED BY: Wah Whiteh	TITLE P.E.S.	DATE 11/2/2016			
Conditions of Approval (if any):					