

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010SUNDRY NOTICES AND REPORTS **Carlsbad Field Office**
OCD Hobbs

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

Case Serial No.
16047

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.
SMALLS FEDERAL 8H9. API Well No.
30-025-4306910. Field and Pool, or Exploratory
WC-025 G-06 S223421L;BS11. County or Parish, and State
LEA COUNTY, NM

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

COG OPERATING LLC

Contact: MAYTE X REYES

E-Mail: mreyes1@concho.com

3a. Address

2208 WEST MAIN STREET
ARTESIA, NM 88210

3b. Phone No. (include area code)

Ph: 575-748-6945

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 28 T22S R34E SWSW 190FSL 410FWL

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original APD
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

COG Operating LLC, respectfully requests approval for the following changes to the original approved APD.

~~BHL Change~~
~~From: 330' FNL & 380' FWL Section 28, T22S, R34E~~
~~To: 50' FNL 380' FWL Section 28, T22S, R34E~~
~~C102 Attached~~

Drilling Changes
Attached:
Drilling Plan
Directional Plan

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #354068 verified by the BLM Well Information System
For COG OPERATING LLC, sent to the Hobbs
Committed to AFMSS for processing by DEBORAH MCKINNEY on 10/11/2016 ()

Name (Printed/Typed) MAYTE X REYES

Title REGULATORY ANALYST

Signature (Electronic Submission)

Date 10/10/2016

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

Mustafa Haguel

Title

Engineer

Date 10-13-2016

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Hobbs

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED *****MSS/OCB 11/16/2016*

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	COG Operating, LLC.
LEASE NO.:	NMNM-116047
WELL NAME & NO.:	Smalls Federal 8H
SURFACE HOLE FOOTAGE:	0190' FSL & 0410' FWL
BOTTOM HOLE FOOTAGE	0330' FNL & 0380' FWL
LOCATION:	Section 28, T. 22 S., R 34 E., NMPM
COUNTY:	Lea County, New Mexico

All previous COAs still apply, except for the following:

A. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) for Water Basin:

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Capitan Reef

Possible water flows in the Artesia Group, Salado, and Capitan Reef.

Possible lost circulation in the Red Beds, Rustler, Artesia Group, Capitan Reef, and Delaware.

1. The **16 inch** surface casing shall be set at approximately **2160 feet** (**in a competent bed below the Magenta Dolomite, which is a Member of the Rustler, and if salt is encountered, set casing at least 25 feet above the salt**) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Special Capitan Reef requirements:

If lost circulation (50% or greater) occurs below the Base of the Salt, the operator shall do the following:

- **Switch to fresh water mud to protect the Capitan Reef and use fresh water mud until setting the intermediate casing. The appropriate BLM office is to be notified for a PET to witness the switch to fresh water.**
- **Daily drilling reports from the Base of the Salt to the setting of the intermediate casing are to be submitted to the BLM CFO engineering staff via e-mail by 0800 hours each morning. Any lost circulation encountered is to be recorded on these drilling reports. The daily drilling report should show mud volume per shift/tour. Failure to submit these reports will result in an Incidence of Non-Compliance being issued for failure to comply with the Conditions of Approval. If not already planned, the operator shall run a caliper survey for the intermediate well bore and submit to the appropriate BLM office.**

Intermediate casing shall be kept fluid filled to meet the minimum collapse requirement.

2. The minimum required fill of cement behind the **11-3/4 inch** intermediate casing is:

☒ Cement to surface. If cement does not circulate see A.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to Capitan Reef.**

3. The minimum required fill of cement behind the 8-5/8 inch 2nd intermediate casing, which shall be set at approximately 5180 feet, is:

Operator has proposed DV tool at depth of 3910', but will adjust cement proportionately if moved. DV tool shall be set a minimum of 50' below previous shoe and a minimum of 200' above current shoe. Operator shall submit sundry if DV tool depth cannot be set in this range. If an ECP is used, it is to be set a minimum of 50' below the shoe to provide cement across the shoe. If it cannot be set below the shoe, a CBL shall be run to verify cement coverage.

- a. First stage to DV tool:

☒ Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job. Operator should have plans as to how they will achieve circulation on the next stage.

- b. Second stage above DV tool:

☒ Cement to surface. If cement does not circulate see A.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to Capitan Reef.**

Centralizers required on horizontal leg, must be type for horizontal service and a minimum of one every other joint.

4. The minimum required fill of cement behind the 5-1/2 inch production casing is:

☒ Cement should tie in 50 feet above Capitan Reef at approximately 3925 feet.

MHH 10132016

COG Operating LLC, Smalls Federal 8

H

1. Geologic Formations

TVD of target	10,345'	Pilot hole depth	N/A
MD at TD:	15,152'	Deepest expected fresh water:	605'

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Quaternary Fill	Surface	Water	
Rustler	1868'	Water	
Top of Salt	2148'	Salt	
Tansill	3600'	Barren	
Yates	3671'	Oil/Gas	
Capitan Reef	3975'	Water	Possible lost circ
Delaware Group	5172'	Oil/Gas	Possible lost circ
Bone Spring	8468'	Oil/Gas	
2 nd Bone Spring Sand	9997'	Target Zone	
Wolfcamp	11169'	Oil/Gas	

2. Casing Program → SEE COA

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
20"	0	2010 2160	16"	65 84	H40 J55	STC LTC	1.15	1.57	3.36
14.75"	0	3750	11.75	47	J55	STC	1.17	1.3	2.69
10.625"	0	5225 5180'	8.625	32	K55	STC	1.04	1.55	2.86
7.875"	0	15152	5.5	17	P110	LTC	1.42	2.03	1.83
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
- BLM standard formulas were used on all SF calculations.
- Intermediate casings will be kept $\geq 1/3$ full; to avoid approaching collapse pressures.
- Will set DV tool within 100' of the top of the Capitan Reef. Estimated setting depth is 3900'.

COG Operating LLC, Smalls Federal 8

H

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	Y
If yes, does production casing cement tie back a minimum of 50' above the Reef?	Y
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

2. Cementing Program - PSEE COA

3.

Casing	# Sks	Wt. lb/ gal	Yld ft3/ sack	H ₂ O gal/s k	500# Comp. Strength (hours)	Slurry Description
Surf.	1450	13.5	1.75	9	12	Lead: Class C + 4% Gel
	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl ₂
1 st Inter.	1450	13.5	1.75	9	12	Lead: Econocem HLC 65:35:6 + 5% Salt
	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl
2 nd Int 1 st Stage	400	12.7	1.98	10.6	16	1 st stage Lead: Econocem HLC 65:35:6 + 5% Salt
	250	14.8	1.34	6.34	8	1 st stage Tail: Class C + 2% CaCl
2 nd Int 2 nd Stage	600	13.5	1.75	9.11	12	2 nd stage Lead: Class C + 4% Gel (DV @ ~1800')
	100	14.8	1.34	6.34	8	2 nd stage Tail: Class C + 2% CaCl
5.5 Prod 1 Stage	650	10.4	3.38	19	72	Lead: Halliburton Tune Lite Blend
	1000	14.4	1.24	5.7	19	Tail: Versacem 50:50:2 Class H + 1% Salt

Low
Cement.
- SEE COA

COG Operating LLC, Smalls Federal 8

H

Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Casing String	TOC	% Excess
Surface	0'	95%
1 st Intermediate	0'	110%
2 nd Intermediate 1 st Stage	DVT	150%
2 nd Intermediate 2 nd Stage	0	100% OH 20% CH Stage Tool at ~3910'
Production	3948' 3925'	40% OH to Tie In to 50' above capitan reef

Pilot hole depth: NA'

KOP: 9840'

4. Pressure Control Equipment

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
14-3/4"	20"	2M	Annular	x	2000 psi
			Blind Ram		2M
			Pipe Ram		
			Double Ram		
			Other*		
10-5/8"	13-5/8"	2M	Annular	x	2000 psi
			Blind Ram		2M
			Pipe Ram		
			Double Ram		
			Other*		
7-7/8"	11"	3M	Annular	x	50% testing pressure
			Blind Ram	x	5M
			Pipe Ram	x	
			Double Ram		
			Other*		

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a

COG Operating LLC, Smalls Federal 8

H

higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
	Are anchors required by manufacturer? No.
N	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. See attached schematic.

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. Shoe	FW Gel	8.6-8.8	28-34	N/C
Surf shoe	11-3/4" Int shoe (3450')	Saturated Brine	10.0-10.2	28-34	N/C
11-3/4" Int shoe	8-5/8" Int. Shoe (5,550')	Fresh Water	8.4-8.6	28-34	N/C
8-5/8" Int shoe	Lateral TD	Cut Brine	8.6 – 9.2	28-34	N/C

*If lost circulation is encountered, will switch to fresh water.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	Pason PVT
---	-----------

6. Logging and Testing Procedures

COG Operating LLC, Smalls Federal 8

H

Logging, Coring and Testing.	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned		Interval
X	Mud log	Production
	Triple Combo	Pilot Hole TD – Intermediate Casing
	GR-Neutron	Intermediate Casing - Surface

COG Operating LLC, Smalls Federal 8

H

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	5052 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions.

- Lost circulation material/sweeps/mud scavengers.
- Maintain stock of LCM and weighting materials onsite.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

	H ₂ S is present
	H ₂ S Plan attached

8. Other facets of operation

Is this a walking operation? No.

Will be pre-setting casing? No.

Will well be hydraulically fractured? Yes.

Attachments

- BOP & Choke Schematics
- Directional Plan
- Rig plat