

HOBBS OCD

JAN 13 2017

Submit 1 Copy To Appropriate District
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM

87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

October 13, 2009

WELL API NO.

30-025-43490

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Columbus Fee

8. Well Number

24H

9. OGRID Number

229137

10. Pool name or Wildcat

WC-025 G-09 S253336D, Upper Wolfcamp

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

COG Operating LLC

3. Address of Operator

2208 W. Main Street, Artesia, NM 88210

4. Well Location

Unit Letter B : 210 feet from the North line and 2210 feet from the East line
Section 34 Township 25S Range 33E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3327'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☒PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

COG Operating LLC respectfully requests approval for the following drilling changes to the above referenced APD.

- Operator will drill 17.5" surface hole to 1200'. Run 13-3/8" 68# L80 BTC casing to TD and cement to surface with 800 sx of cement.
- Operator will drill 12.25" intermediate hole to 11,700'. Run 9-5/8" 47# L80 BTC to TD and cement to surface with 1500 sx of cement.
- Operator will drill 8.5" production hole to TD= 22,384'. Run 5.5" 23# P110 BTC to TD and tie back 500' into intermediate casing with 2500 sx of cement.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE: Regulatory Analyst

DATE: 1/13/2017

Type or print name: Mayte Reyes

E-mail address: mreyes1@conchoresources.com

PHONE: (575) 748-6945

For State Use Only

APPROVED BY:

TITLE

Petroleum Engineer

DATE

01/13/17

Conditions of Approval (if any):