

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-03533

5. Indicate Type of Lease
STATE x FEE

6. State Oil & Gas Lease No.
ES 892

7. Lease Name or Unit Agreement Name

GULF STATE

8. Well Number 1

9. OGRID Number

10. Pool name or Wildcat
SAN SIMON YATES NORTH

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well X Gas Well Other

2. Name of Operator
ESTATE OF G.P. SIMS

3. Address of Operator
PO BOX 1046, EUNICE NM 88231

4. Well Location

Unit Letter K : 1980 feet from the SOUTH line and 1980 feet from the WEST line
Section 33 Township 21S Range 35E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON X

TEMPORARILY ABANDON CHANGE PLANS

PULL OR ALTER CASING MULTIPLE COMPL

DOWNHOLE COMMINGLE

CLOSED-LOOP SYSTEM

OTHER:

SUBSEQUENT

REMEDIAL WORK

COMPL

JOB

OTHER:

RT OF:

ALTERING CASING

PANDA

INT TO PA PMX

P&A NR

P&A R

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1) PICK UP AND RUN TUBING TO ^{TAG} 3445'. CIRCULATE CSG W/ REGULATION MLF. Pressure test csg.
2) PERFORATE CASING AT 1840'. 1800'
3) SQUEEZE PERF W/ 40 SX CEMENT. LEAVE TOC AT 1740'. WOC AND TAG. 1700'
4) PERFORATE CASING AT 370' (50' BELOW 8 5/8" SHOE).
5) SQUEEZE PERF W/ 50 SX CEMENT. WOC AND TAG. CIRC CMT TO SURFACE INSIDE/OUTSIDE 4 1/2
6) PLACE 15 SX SURFACE PLUG.
7) CUT OFF WELLHEAD AND WELD ON REGULATION P&A MARKER.

Verify cmt to surface all strings

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Marvin Burrows TITLE AGENT FOR DATE 1/23/17

Type or print name MARVIN BURROWS E-mail address: BURROWSMARVIN@GMAIL.COM PHONE: 575-631-8067

For State Use Only

APPROVED BY: Marvin Burrows TITLE Petroleum Engr. Specialist DATE 1/24/2017

Conditions of Approval (if any):

MAVERICK WELL PLUGGERS

COMPANY: Estate of G.P. Sims

WELL NAME: Gulf State

WELL #: # 1

COUNTY: Lea County, N. M.

LEASE ID: ES - 892

SURFACE CASING				
OD	WT/FT	GRADE	SET AT	TOC
8-5/8"	36#	J 55	320'	Surface
INTERMEDIATE CASING				
OD	WT/FT	GRADE	SET AT	TOC
PRODUCTION CASING				
OD	WT/FT	GRADE	SET AT	TOC
4-1/2"	9.5	J 55	3,972'	3,392 Cal.
TUBING				
OD	WT/FT	GRADE	SET AT	TAC

