# State of New Mexico Energy, Minerals and Natural Resources Department

Susana Martinez Governor

David Martin Cabinet Secretary

Brett F. Woods, Ph.D. Deputy Cabinet Secretary David R. Catanach, Division Director Oil Conservation Division



Administrative Order SWD-1601 November 23, 2015

## ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Pursuant to the provisions of Division Rule 19.15.26.8(B) NMAC, BC & D Operating Incorporated (the "operator") seeks an administrative order to re-enter and re-complete the West Jal B No. 1 with a location 1980 feet from the South line and 1980 feet from the East line, Unit letter J of Section 17, Township 25 South, Range 36 East, NMPM, Lea County, New Mexico, for the commercial disposal of produced water.

### THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rules 19.15.26.8(B) NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objection was received within the required suspense period. The applicant has presented satisfactory evidence that all requirements prescribed in rule 19.15.26.8 NMAC have been met and the operator is in compliance with rule 19.15.5.9 NMAC.

#### IT IS THEREFORE ORDERED THAT:

The applicant, BC & D Operating Inc. (OGRID 25670), is hereby authorized to utilize its the West Jal B No. 1 (API No. 30-025-20857) with a location 1980 feet from the South line and 1980 feet from the East line, Unit letter J of Section 17, Township 25 South, Range 36 East, NMPM, Lea County, New Mexico, for commercial disposal of oil field produced water (UIC Class II only) through a perforated interval within the Cherry Canyon formation from <u>5340 feet</u> to 6000 feet. Injection shall occur through <u>4½-inch</u> or smaller, internally-coated tubing and a packer set a maximum of 100 feet above the top perforation.

### IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the well construction proposed and described in the application (as modified by applicant on September 28, 2015), any modifications included in this order and, if necessary, as modified by the District Supervisor.

The operator shall install 7-inch casing over the approved injection interval to the proposed depth of 6750 feet with the cement for the casing circulated to surface. The operator shall install a cast-iron bridge plug with cement cap at 6200 feet.

Administrative Order SWD-1601 BC & D Operating Inc. November 23, 2015 Page 2 of 3

.

Prior to commencing injection, the operator shall provide to Division's District I office cement bond log (or equivalent) showing placement of cement for the 7-inch casing.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division rule 19.15.26.11(A) NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to **no more than 1068 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well. At the discretion of the supervisor of the Division's District I office, the operator shall install and maintain a chart recorder showing casing and tubing pressures during disposal operations.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District I office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District I office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division rules 19.15.26.13 and 19.15.7.24 NMAC.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection order after notice and hearing if the operator is in violation of rule 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate two (2) years after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause. Administrative Order SWD-1601 BC & D Operating Inc. November 23, 2015 Page 3 of 3

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.

DAVID R. CATANACH Director

DRC/prg

cc: Oil Conservation Division - Hobbs District Office