BUR SUNDRY N Do not use this is abandoned well. SUBMI 1. Type of Well Oil Well Gas W 2. Name of Operator Burk Royal 3a. Address	ty Co., Ltd	T WELLS to re-enter an uch proposes	5) Lease Serial No. 5) Lease Serial No. 6 If Indian, Allottee or 017 Collection CA/Agreent	ment, Name and/or No. 9en Double L Queen #1 🖌 005-20320
4. Location of Well (Footage, Sec., T., 1980'FSL&66	chita Falls, TX 76308 940-397 R.,M., or Survey Description CFWL(10+6) NWSV CK THE APPROPRIATE BOX(ES) TO INIT	V 6, 15S, 30E	11. Country or Parish, S	Chaves
	Casing Repair New Change Plans	ture Treat Recla v Construction Record g and Abandon Temp g Back Wate including estimated starting dat	uction (Start/Resume imation mplete worarily Abandon r Disposal e of any proposed work	
testing has been completed. Final A determined that the site is ready for Burk Royalty Co., plugging rig for ea We will hire a plu approximately tw plugging and aba SEE ATT	ed operations. If the operation results in a Abandonment Notices must be filed only af final inspection.) Ltd. is preparing to plug and any April, 2017. This work will agging crew to plug seven who to three days. Therefore andoning of all seven wells in ACHED FOR OF APPROVAL	d abandon this well. I be done under the a ells back-to-back wi , Burk's plan is to April, 2017.	Burk Royalty is attached Bond N th each plugging commence and OR <u>3</u> MCN	s scheduling a o. 141880550. g job requiring complete the
1110 Th:		Title Vice President		
Signature / WMM	THIS SPACE FOR FEDE			
that the applicant holds legal or equitable ti entitle the applicant to conduct operations t	. Approval of this notice does not warrant or tle to those rights in the subject lease which w	rould Office	Da	
	entations as to any matter within its jurisdiction		FOR RE	CORD ONLY

.....

PROPOSED P&A PROCEDURE FOR:

DOUBLE L QUEEN, WELL #1 (001A) LEASE SERIAL NO. NMNM--0 317354 API NO. 30-005-20320

WELL HISTORY:

 SPUD: 1/9/1970
 COMPLETION: 1/26/1970
 ELEV: 3889' DF

 SURFACE:
 12 ¼" HOLE; 8 5/8" 24# SET @ 387' W/ 300 SXS CEMENT

 PROD CSG:
 7 7/8" HOLE; 4 ½" 9.5# SET @ 1954' W/200 SXS CEMENT

 TD:
 1972'

 PERFORATION:
 1962-72'

- 1. Move in and rig up.
- 2. Rig up wireline unit, set cast iron bridge plug at 1915'.
- 3. Spot 25 sacks cement at 1915'. Tage Or Above 1815'
- 4. Perforate casing at 390' 4-37'
- 5. Circulate 125 sacks of cement to the surface
- 6. Cut off pipe 3' below surface and weld plate on casing.
- 7. Clean up and move off location.

BUREAU OF LAND MANAGEMENT Roswell Field Office 2909 West Second Street Roswell, New Mexico 88201 (575) 627-0272

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety** (90) days from the approval date of this Notice of Intent to Abandon. If you are unable to plug the well by the 90th day provide the BLM Roswell Field Office (RFO), prior to the 90th day, with the reason for not meeting the deadline and a date when the BLM Roswell Field Office can expect the well to be plugged. Failure to do so will result in enforcement action. Unless the well has been properly plugged, the rig shall not be removed from over the hole without prior approval.

2. <u>Notification</u>: Contact the BLM Roswell Field Office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, during office hours or after office hours call (575) 627-0205. Engineer on call during office hours phone (575) 627-0275 or phone (after hours) call (575) 626-5749.

3. <u>Blowout Preventers:</u> A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9090 feet; a 3M system for a well not deeper than 13636 feet; and a 5M system for a well not deeper than 22727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at a rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement:</u> Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 50 feet of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C" for up to 7500 feet of depth, mixed at 14.8 lbs./gal with 6.3 gallons of fresh water per sack or class "H" for deeper than 7500 feet plugs, mixed at 16.4 lbs./gal with 4.3 gallons of fresh water per sack.

6. <u>Monument:</u> Upon abandonment of the well, all casing shall be cut-off at the base of the cellar or 3-feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¹/₄ inch thick and welded in place. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized officer; such as metes and bounds).

7. <u>Timing Limitation Lease Stipulation / Condition of Approval For Lesser Prairie-Chicken:</u> Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1 through June 15 annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D seismic operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

8. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to the BLM Roswell Field Office. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged.</u>

Following the submittal and approval of the Subsequent Report of Abandonment, a Notice of Intent for Final Abandonment with the proposed surface restoration procedure must be submitted for approval.