30-025-43606

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

GAS	CA	PTI	RE.	PI.A	N

Dat	e: 04/03/2017		Grio Cri		2 2 1 4				
	Original - Gas is used Amended - Reason fo		1	& OGRID	No.: Occide	ntal Permian L	_TD 157984		
new	v completion (new dri	ll, recomplete to	o new zone, re-fra	ac) activity.			n facility flaring/venting for 4 of 19.15.18.12 NMAC).		
Well(s)/Production Facility – Name of facility The well(s) that will be located at the production facility are shown in the table below.									
	Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments		
	NHU 667	025-43606	C-24-18S-37E	842 FNL 1858 FWL	2100	N/A	re-injected		
	NHU 678	025-43579	L-24-18S-37E	2135 FSL 1289 FWL	2100	N/A	re-injected		
Wei The pres faci estin	e gas produced from prossure gathering system lity to low/high pressurated first production nsporter have periodic	to a production of toduction facility of a production facility of the content of the conference calls to a production of the c	facility after flowly is dedicated to County, Notes. County, Notes are scheduled to to discuss change	Gas Transpor New Mexico provides (peri to be drilled in the sto drilling a	ter and will lead to the control of the control of the completion	be connected uire	ansporter system is in place. to <u>Gas Transporter</u> low/high of pipeline to connect the ter a drilling, completion and addition, <u>Operator</u> and <u>Gas</u> Gas from these wells will be County New Mexico. The		
	processed at <u>Gas Transporter</u> Processing Plant located in Sec, Twn, Rng, County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.								

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Gas Transporter</u> system at that time. Based on current information, it is <u>Operator's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines