Office	State of New Mexico Energy, Minerals and Natural Resources	Form C-103 Revised July 18, 2013
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Divigy, Williotals and Natural Resources	WELL API NO.
<u>District II</u> - (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-025-42264
District III - (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE X FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		
SUNDRY NO	TICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A LICATION FOR PERMIT" (FORM C-101) FOR SUCH	Chincoteague 32 State Com
PROPOSALS.)	_	0 W-11 N
1. Type of Well: Oil Well	Gas Well  Other	311
Name of Operator     Devon Energy Production	n Co., L.P. Linda Good	9. OGRID Number 6137
3. Address of Operator	11 00 000 000	10. Pool name or Wildcat
333 West Sheridan Ave, Ol	dahoma City, OK 73102 405-552-6558	WC-025-G-06 S253206M; Bone Spring
4. Well Location	: 200 feet from the S line and	880 feet from the E line
Unit Letter O Section 32	: 200 feet from the S line and Township 24S Range 32E	
Section 32	11. Elevation (Show whether DR, RKB, RT, GR, etc.	
	3470' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF I	NTENTION TO: SUE	SSEQUENT REPORT OF:
PERFORM REMEDIAL WORK		
TEMPORARILY ABANDON	Control of the second of the s	RILLING OPNS. P AND A
PULL OR ALTER CASING		IT JOB 🖸
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM		
OTHER:	OTHER: Dril	ling Operations
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed w	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Co	
of starting any proposed w proposed completion or re	york). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.	empletions: Attach wellbore diagram of
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set	empletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C	york). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.	empletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.	empletions: Attach wellbore diagram of  859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  psi & annular preventer to 250 psi/3500 psi
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  0 psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87,
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  0 psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87,
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  0 psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87,
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.	mpletions: Attach wellbore diagram of @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8 0 psi & annular preventer to 250 psi/3500 psi @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.	mpletions: Attach wellbore diagram of @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8 0 psi & annular preventer to 250 psi/3500 psi @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.	mpletions: Attach wellbore diagram of @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8 0 psi & annular preventer to 250 psi/3500 psi @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho 2.91, 11.00 cf/sx. Tail w/785 sx c	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  ole @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCE mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To	mpletions: Attach wellbore diagram of @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8 0 psi & annular preventer to 250 psi/3500 psi @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.	mpletions: Attach wellbore diagram of @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8 0 psi & annular preventer to 250 psi/3500 psi @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho 2.91, 11.00 cf/sx. Tail w/785 sx c	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  ole @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCE mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To	mpletions: Attach wellbore diagram of @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8 0 psi & annular preventer to 250 psi/3500 psi @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho 2.91, 11.00 cf/sx. Tail w/785 sx c	ork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  ole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  ole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  ole @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCE mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  D psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87,  It to surf. WOC. Test BOP to 250 psi/5000 psi.  ITQ csg set @ 15,506'. Lead w/695 sx cmt, yld  DC @ 1474'.
of starting any proposed w proposed completion or re 4/16/17 - 4/17/17: TD 17-1/2" ho cf/sx. Displace w/126 bbl wtr. C for 10 mins, good tests. Test csg 4/18/17 - 4/22/17: TD 12-1/4" ho 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" ho 2.91, 11.00 cf/sx. Tail w/785 sx c	rork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  Sole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Sirc 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  Sole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  Sole @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCH mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  D psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87,  It to surf. WOC. Test BOP to 250 psi/5000 psi.  ITQ csg set @ 15,506'. Lead w/695 sx cmt, yld  DC @ 1474'.
of starting any proposed we proposed completion or re  4/16/17 - 4/17/17: TD 17-1/2" he cf/sx. Displace w/126 bbl wtr. Of for 10 mins, good tests. Test csg  4/18/17 - 4/22/17: TD 12-1/4" he 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi for 4/23/17 - 5/5/2017: TD 8-3/4" he 2.91, 11.00 cf/sx. Tail w/785 sx complete the start of the star	rork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  Sole @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  Sole @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  Sole @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCF mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To Rig Release Date:	mpletions: Attach wellbore diagram of @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8 0 psi & annular preventer to 250 psi/3500 psi @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi. ITQ csg set @ 15,506'. Lead w/695 sx cmt, yld DC @ 1474'.
of starting any proposed we proposed completion or re  4/16/17 - 4/17/17: TD 17-1/2" he cf/sx. Displace w/126 bbl wtr. Of for 10 mins, good tests. Test csg  4/18/17 - 4/22/17: TD 12-1/4" he 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi fe 4/23/17 - 5/5/2017: TD 8-3/4" he 2.91, 11.00 cf/sx. Tail w/785 sx c  Spud Date:	Nork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  All @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set inc 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  All @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set inc d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  All @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCH mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To above is true and complete to the best of my knowledg showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged showledged showledged showledged above is true and complete to the best of my knowledged showledged showl	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  0 psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.  ITQ csg set @ 15,506'. Lead w/695 sx cmt, yld DC @ 1474'.  ge and belief.  hee Specialist DATE 5/9/2017
of starting any proposed we proposed completion or re  4/16/17 - 4/17/17: TD 17-1/2" he cf/sx. Displace w/126 bbl wtr. Of for 10 mins, good tests. Test csg  4/18/17 - 4/22/17: TD 12-1/4" he 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi fe 4/23/17 - 5/5/2017: TD 8-3/4" he 2.91, 11.00 cf/sx. Tail w/785 sx ce  Spud Date:  I hereby certify that the information  SIGNATURE  Type or print name  Linda Good	Nork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  All @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set inc 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  All @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set inc d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  All @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCH mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To above is true and complete to the best of my knowledg showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged showledged showledged showledged above is true and complete to the best of my knowledged showledged showl	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  0 psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.  ITQ csg set @ 15,506'. Lead w/695 sx cmt, yld DC @ 1474'.  ge and belief.  hee Specialist DATE 5/9/2017
of starting any proposed we proposed completion or re  4/16/17 - 4/17/17: TD 17-1/2" he cf/sx. Displace w/126 bbl wtr. Of for 10 mins, good tests. Test csg  4/18/17 - 4/22/17: TD 12-1/4" he 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi fe 4/23/17 - 5/5/2017: TD 8-3/4" he 2.91, 11.00 cf/sx. Tail w/785 sx c  Spud Date:	Nork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  All @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set Circ 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  All @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set @ d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  All @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCF mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To Rig Release Date:  Rig Release Date:    Rig Release Date:	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  0 psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.  ITQ csg set @ 15,506'. Lead w/695 sx cmt, yld OC @ 1474'.  ge and belief.  here Specialist DATE 5/9/2017  lvn.com PHONE: 405-552-6558
of starting any proposed we proposed completion or re  4/16/17 - 4/17/17: TD 17-1/2" he cf/sx. Displace w/126 bbl wtr. Of for 10 mins, good tests. Test csg  4/18/17 - 4/22/17: TD 12-1/4" he 1290 cf/sx. Tail w/430 sx ClC, yl Good test. Test csg to 1500 psi fe 4/23/17 - 5/5/2017: TD 8-3/4" he 2.91, 11.00 cf/sx. Tail w/785 sx ce  Spud Date:  I hereby certify that the information  SIGNATURE  Type or print name  Linda Good	Nork). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.  All @ 870'. RIH w/20 jts 13-3/8" 54.5# J-55 BTC csg set inc 377 sx cmt to surf. WOC. Test BOP to 250 psi/500 to 1500 psi for 30 min. Good test.  All @ 4545'. RIH w/107 jts 9-5/8" 40# J-55 BTC csg set inc d 1.33, 14.80 cf/sx. Disp w/341 bbl wtr. Circ 312 sx cm or 30 min. Good test.  All @ 15,521'. RIH w/359 jts 5-1/2" 17# P-110RY CDCH mt, yld 1.46, 13.20 cf/sx. Displ w/358 bbls FW. Est. To above is true and complete to the best of my knowledg showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged above is true and complete to the best of my knowledged showledged showledged showledged showledged above is true and complete to the best of my knowledged showledged showl	mpletions: Attach wellbore diagram of  @ 859'. Lead w/1090 sx ClC cmt, yld 1.34, 14.8  0 psi & annular preventer to 250 psi/3500 psi  @ 4534'. Lead w/1155 sx ClC cmt, yld 1.87, t to surf. WOC. Test BOP to 250 psi/5000 psi.  ITQ csg set @ 15,506'. Lead w/695 sx cmt, yld OC @ 1474'.  ge and belief.  here Specialist DATE 5/9/2017  lvn.com PHONE: 405-552-6558