Form 3160-5 (June 2015) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS BBS OCD Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals, 1,0,2017					FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018 5. Lease Serial No. NMNM84651 6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agree NMNM134709	ment, Name and/or No.	
1. Type of Well Oil Well Gas Well Other				VED	8. Well Name and No. HAMON A FEDERAL COM 1H		
2. Name of Operator / Contact: D. PATRICK DARDEN, PE LEGACY RESERVES OPERATING LIE-Mail: pdarden@legacylp.com					9. API Well No. 30-025-41616-00-S1		
3a. Address         3b. Phone No.           303 W WALL SUITE 1600         Ph: 432-68           MIDLAND, TX 79702         Ph: 432-68			. (include area code) 9-5200		10. Field and Pool or Exploratory Area TEAS		
4. Location of Well (Footage, Sec., T		11. County or Parish, State					
Sec 18 T20S R34E Lot 1 200		LEA COUNTY, NM					
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA							
TYPE OF SUBMISSION	TYPE OF ACTION						
□ Notice of Intent	tice of Intent		eepen 🗖 Produ		ion (Start/Resume)	UWater Shut-Off	
	Alter Casing	🗖 Hyd	raulic Fracturing	🗖 Reclam	ation	U Well Integrity	
Subsequent Report	Casing Repair	_	□ New Construction		olete	Other Well Spud	
Final Abandonment Notice	<ul> <li>Change Plans</li> <li>Convert to Injection</li> </ul>	Plug	and Abandon	<ul> <li>Temporarily Abandon</li> <li>Water Disposal</li> </ul>		Wen Spud	
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection. 02/12/14 Set 1600' of 54# J-55 13 3/8" csg. Cmt csg w/1020sx. Circulated cmt to surface. 02/17/2014 Spud 03/01/2014 Set 5400' of 40# J-55 & N-80 9 5/8" csg (DVT @ 3925', ECP @ 3928'). Cmt csg w/2505 sx cmt. Circulated cmt to surface. 03/02/2014 RDMO drlg rig.							
06/01/2014 MIRU drlg rig.							
06/09/2014 to 07/02/2014 Rotate & slide drilled to TD @ 16,194' MD.							
14. I hereby certify that the foregoing is true and correct. Electronic Submission #368785 verified by the BLM Well Information System For LEGACY RESERVES OPERATING LP, sent to the Hobbs Committed to AFMSS for processing by PRISCILLA PEREZ on 03/06/2017 (17PP0322SE) Name (Printed/Typed) D. PATRICK DARDEN, PE Title SR. ENGINEERING ADVISOR FOR RECORD							
						1/1/1	
Signature (Electronic Submission)			Date 03/03/20		MAR 24 2	DR AMANA	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
_Approved By			Title	/€	VREAU OF LAND MA	OFFICEDate	
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent which would entitle the applicant to condu-	Office						
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United V States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.							
(Instructions on page 2) <b>** BLM REV</b>	ISED ** BLM REVISEI	D ** BLM RE	EVISED ** BLN		) ** BLM REVISED	** Kas	

## Additional data for EC transaction #368785 that would not fit on the form

## 32. Additional remarks, continued

07/05/2014 to 07/25/2014 Attempt to run 5 1/2" csg. Reamed hole.

07/26/2014 Run 26# P-110 7"x11.6# P-110 FJ csg to 11,421' & became stuck. Cut off 7" csg @ 6030' & set cmt plug fr/6030' to 5017' as per orders fr/BLM. RDMO drlg rig.

11/28/2014 Spud side track well. Drill out plug back cmt fr/5017'-5355'.

11/29/2014 Set Whipstock @ 5350'. Mill window in 9 5/8" csg fr/5333'-5357'.

12/01/2014 to 12/23/2014 Rotate & slide drilled to TD @ 14,466' MD.

12/26/2014 Run 14,466' of 20# P-110 5 1/2" csg. Cmt csg w/2561sx cmt. Circulated cmt to surface.

