Form 3160-5 (June 2015)

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS

not use this form for proposals to drill or to recent to the state of t

Do not use thi abandoned we	s form for proposals to II. Use form 3160-3 (API	drill or to re- D) for such p	roposals.	1100	6. If Indian, A	llottee or	Tribe Name
SUBMIT IN	TRIPLICATE - Other inst	ructions on	pagHOBB	S OCI	7. If Unit or C	A/Agree	ment, Name and/or No.
Type of Well		AUG (8 2017	8. Well Name ANTIETAN		COM 704H /	
 Name of Operator EOG RESOURCES INCORPO 		STAN WAGN er@eogresourc	ER ces.com	EIVE	9. API Well N 30-025-4		0-X1
3a. Address MIDLAND, TX 79702	3b. Phone No. (include area code) Ph: 432-686-3689			10. Field and Pool or Exploratory Area WC025G09S253509D-UPPER WC			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, State			
Sec 9 T25S R33E NENW 164FNL 2033FWL 32.151901 N Lat, 103.579193 W Lon				LEA COUNTY, NM			
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE O	F NOTICE,	REPORT, O	R OTH	ER DATA
TYPE OF SUBMISSION	TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	☐ Deepen		☐ Production (Start/Resume)		■ Water Shut-Off	
	☐ Alter Casing	☐ Hydraulic Fracturing		☐ Reclam	lamation		■ Well Integrity
Subsequent Report Subsequent Re	Casing Repair			☐ Recomplete			☑ Other Change to Original A
☐ Final Abandonment Notice	☐ Change Plans		and Abandon		Temporarily Abandon		PD PD
13. Describe Proposed or Completed Ope	☐ Convert to Injection		☐ Plug Back ☐ Wat				
If the proposal is to deepen directions. Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for f 5/04/17 Spud 14-3/4" hole. 5/05/17 Ran 30 jts 10-3/4", 4(6/06/17 Cement lead w/ 655 tail w/ 250 sx Class C, 14.8 pt	rk will be performed or provide operations. If the operation revandonment Notices must be fillinal inspection. 0.5#, J-55 STC casing set sx Class C, 13.5 ppg, 1.70 pg, 1.36 CFS yield.	the Bond No. or sults in a multipled only after all states at 1201'. 6 CFS yield;	file with BLM/BIA e completion or reco requirements, includ	Required sul	bsequent reports new interval, a F	must be orm 3160	filed within 30 days 0-4 must be filed once
Circulated 121 bbls cement to surface. WOC 4 hrs. Released surface rig. 6/28/17 Tested casing to 1500 psi for 30 minutes. Test good. Resumed drilling 9-7/8" hole.							
7/05/17 Ran 7-5/8", 29.7#, (139 jts) ECP-110 LTC & (122 jts) HCP-110 FXL casing set at 11733'. DV tool at 4989'.							
¥							
14. I hereby certify that the foregoing is	Electronic Submission #	IRCES INCOR	PORATED, sent	to the Hobbs	i	Ε)	
Name (Printed/Typed) STAN WAGNER			Title REGULATORY ANALYST				
Signature (Electronic S	Submission)		Date ACCE	PTED F	OR RECO	RD	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
Approved By ACCEPTED			MUSTAFA _{Title} PETROLE	HAQUE UM ENGINI	2 2017 EER		Date 08/02/2017
Conditions of approval, if any, are attached. Approval of this notice does not we certify that the applicant holds legal or equitable title to those rights in the subjective which would entitle the applicant to conduct operations thereon.			Office Hobbs C		MANAGEME ELD OFFICE	NT	
Title 19 II S.C. Section 1001 and Title 42	U.S.C. Section 1212 make it a	orima for any na	rean knowingly and	willfully to m	ake to any denor	tment or	agency of the United

Additional data for EC transaction #381095 that would not fit on the form

32. Additional remarks, continued

 $7/06/17\,$ 1st stage: Cement lead w/ 500 sx Class C, 10.8 ppg, 3.48 CFS yield; tail w/ 520 sx Class H, 15.6 ppg, 1.22 CFS yield. Did not circulate. Notified BLM. ETOC at 6000'.

 $7/07/17\,$ 2nd stage: Cement lead w/ 1220 sx Class C, 12.7 ppg, 2.37 CFS yield; tail w/ 50 sx Class C, 14.8 ppg, 1.45 CFS yield. Circulated 100 bbls cement to surface.

 $7/08/17\,$ Tested casing to 2600 psi for 30 minutes. Test good. Resumed drilling 6-3/4" hole.