Form 3160-5 (June 2015) UNITED STATES DEPARTMENT OF THE INTERIOR					FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018		
SUNDEX NOTICES AND REPORTS ON BEISDAR Field OF F							
Do not use thi abandoned we	is form for proposals to II. Use form 3160-3 (API	drill or to re- D) for such pi	D I	lobb	6. If Indian, Allottee or	Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on pages OCD					 If Unit or CA/Agreement, Name and/or No. NMNM137151 		
1. Type of Well ⊠ Oil Well □ Gas Well □ Oth	8. Well N		8. Well Name and No. ARABIAN 30-19 F	II Name and No. RABIAN 30-19 FED COM 3H			
2. Name of Operator DEVON ENERGY PRODUCT) 9. Al		 API Well No. 30-025-43774-00 	D. API Well No. 30-025-43774-00-X1			
					10. Field and Pool or E WOLFCAMP	Exploratory Area	
4. Location of Well (Footage, Sec., T., B., M., or Survey Description)					11. County or Parish, State		
Sec 30 T25S R32E SWNE 24 32.101849 N Lat, 103.710213				LEA COUNTY, NM			
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE OI	F NOTICE,	REPORT, OR OTH	IER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	Acidize		Deepen		tion (Start/Resume)	□ Water Shut-Off	
_	□ Alter Casing	🗖 Hyd	draulic Fracturing w Construction	🗖 Reclam	ation	 □ Well Integrity ☑ Other Change to Original A PD 	
Subsequent Report	Casing Repair	_		Recom			
Final Abandonment Notice	 Change Plans Convert to Injection 	Plug	and Abandon	□ Tempor	rarily Abandon		
13. Describe Proposed or Completed Op						vimate duration thereof	
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f Devon Energy Prod Co., LP re the drilling plan.	rk will be performed or provide l operations. If the operation re bandonment Notices must be fi inal inspection.	the Bond No. on sults in a multiple led only after all n	file with BLM/BIA e completion or reco requirements, includ	. Required su mpletion in a ing reclamation	new interval, a Form 516 on, have been completed a	0-4 must of	
- All previous Co	pan nfill apply) Addi	frond co	DA 75,	st require	4.	
14. I hereby certify that the foregoing is	the and correct						
	Electronic Submission # For DEVON ENER(nmitted to AFMSS for proc	GY PRODUCTI	ON COMPAN, sei	nt to the Ho 07/31/2017	bbs (17MH0034SE)		
Name (Printed/Typed) LINDA GOOD			Title REGULATORY COMPLIANCE SPECIALI				
Signature (Electronic Submission)			Date 07/27/2017				
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE U	SE		
Approved_ByMUSTAFA_HAQUE					EER	Date 07/31/2017	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Hobbs				
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a statements or representations as	crime for any pe to any matter wi	rson knowingly and thin its jurisdiction.	willfully to m	ake to any department or	agency of the United	
(Instructions on page 2)	ISED ** BLM REVISE					D ** Va	
	ISED BLIN KEVISE		VISED BLIV	I REVISE		NO	

Devon Energy APD SUNDRY DATA

OPERATOR NAME: Devon Energy

1. SUMMARY OF CHANGES:

Devon Energy respectfully requests approval for the following changes and additions to the drilling plan:

1. Utilize a spudder rig to pre-set surface casing.

2. Description of Operations

- 1. Spudder rig contractor Transend Drilling will move in their rig to drill the surface hole section and preset surface casing on the Arabian 30-19 Fed Com 3H.
 - **a.** After drilling the surface hole section, the rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
 - **b.** Rig will utilize fresh water based mud to drill 17¹/₂" surface hole to TD. Solids control will be handled entirely on a closed loop basis. No earth pits will be used.
- 2. The wellhead will be installed and tested once the 13-3/8" surface casing is cut off and the WOC time has been reached.
- 3. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wingvalves.
 - a. A means for intervention will be maintained while the drilling rig is not over the well.
- 4. Spudder rig operations is expected to take 8-10 days on a multi well pad
- 5. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 6. Drilling operation will be performed with the big rig. At that time an approved BOP stack will be nippled up and tested on the wellhead before drilling operations commences on each well.
 - a. The BLM will be contacted / notified 24 hours before the big rig moves back on to the pad with the pre-set surface casing. The big rig needs to move in within 90 dept
- 7. Devon Energy will have supervision on the ig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
- 8. Once the rig is removed, Devon Energy will secure the wellhead area by placing a guard rail around the cellar area.