	State of New Mexico	Form C-103		
Office <u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013		
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	SOCD	WELL API NO. 30-025-21625		
911 C First Ct Artagia NIM 99210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease		
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410SEP 0	7 2017 220 South St. Francis Dr.	STATE FEE X		
District IV – (505) 476-3460	Santa Fe, NM 87505	6. State Oil & Gas Lease No.		
1220 S. St. Francis Dr., Santa Fe, NM 87505	EIVED			
SUNDRY NOTICES	AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name		
(DO NOT USE THIS FORM FOR PROPOSALS DIFFERENT RESERVOIR. USE "APPLICATION"	TO DRILL OR TO DEEPEN OR PLUG BACK TO A	HUGH ✓		
PROPOSALS.)		8. Well Number		
	Well Other	8		
2. Name of Operator CHEVRON U.S.A. INC.		9. OGRID Number		
3. Address of Operator		10. Pool name or Wildcat		
6301 DEAUVILLE BOULEVARD RM	I #N3007 MIDLAND, TX. 79706	BLINEBERRY OIL & GAS		
4. Well Location Y- LAT 32.393	X-LONG103.14021			
Unit LetterE_:200	30feet from theNORTH line and	_560feet from theWESTline		
Section 14 T	Fownship 22-S Range 37-E	NMPM County LEA		
11. Elevation (Show whether DR, RKB, RT, GR, etc.)				
3,	524' GL			
12 (1 1 1		D		
12. Check Appr	opriate Box to Indicate Nature of Notice	, Report or Other Data		
	·	SSEQUENT REPORT OF:		
Approved for Plugging of wellbore on	y. Liability	RK ALTERING CASING		
under bond is retained pending restor completion of the C-103, Specific for S		RILLING OPNS. PANDA X		
Report of Well Plugging, which may be	e found on	NT JOB		
the OCD web page under forms.	P&A R			
Restoration Due By <u>68-29-2017</u>		П		
13. Describe proposed or completed	operations. (Clearly state all pertinent details, an	nd give pertinent dates, including estimated date		
of starting any proposed work).	SEE RULE 19.15.7.14 NMAC. For Multiple Co			
proposed completion or recomple		UTDC 6 DVD		
08/24/17 MOVE IN & SPOT EQUIPME	NT, NDWH & NU BOP, TEST TBG. , POOH W	// IBG & PKR.		
08/25/17 RIH SET CIBP @ 6,300'. CIR	MLF, MIX & SPOT 30 SX CL "C" CMT FROM	1 6,300'-6,000'.		
08/28/17 DIH SET CIDD @ 5 200' SDO'	T 60 SV CL "C" CMT EDOM 5 200', 4 602', W			
	08/28/17 RIH SET CIBP @ 5,300', SPOT 60 SX CL "C" CMT FROM 5,300'- 4,692', WOC & TAG @ 4,523' TEST CSG 500# GOOD. MIX & SPOT 30 SX CL "C" CMT FROM 3,852'- 3,551'.			
mine of or so on on on		OC & TAG @ 4,523' TEST CSG 500# GOOD.		
		OC & TAG @ 4,523' TEST CSG 500# GOOD.		
	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065			
08/29/17 RIH & TAG @ 3,565', MIX & 2,560'-2,259', MIX & SPOT 40 SX CL	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065			
2,560'-2,259', MIX & SPOT 40 SX CL	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'.	', MIX & SPOT 30 SX CL "C" CMT FROM		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50'		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ MIX & SPOT 45 SX CL "C" CMT FRO	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'.	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE,		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SUR D MEET WITH RULE 19.15.7.14 NMAC REQU	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE,		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SUR	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE,		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL.	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329.	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE,		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SUR D MEET WITH RULE 19.15.7.14 NMAC REQU	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE,		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL.	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329.	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE,		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL. Spud Date:	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SUR D MEET WITH RULE 19.15.7.14 NMAC REQU ASS "C" CEMENT USED. CA BOND 0329. Rig Release Date:	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS.		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL. Spud Date:	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329.	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS.		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL Spud Date: I hereby certify that the information above	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329. Rig Release Date:	", MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS.		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL. Spud Date:	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329. Rig Release Date:	', MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS.		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL Spud Date: I hereby certify that the information above SIGNATURE	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329. Rig Release Date: TITLE Agent for Chevron U.S	", MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS. ge and belief. .ADATE09 / 05 / 17		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ 9 MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL Spud Date: I hereby certify that the information above SIGNATURE	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329. Rig Release Date: TITLE Agent for Chevron U.S. Ver E-mail address: _ monty.mccarver@cjes.com	", MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS. ge and belief. .ADATE09 / 05 / 17		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL. Spud Date: Thereby certify that the information above SIGNATURE Type or print nameMonty L. McCarve For State Use Only	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329. Rig Release Date: TITLE Agent for Chevron U.S. Ver E-mail address: _ monty.mccarver@cjes.com	", MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS. ge and belief. A DATE09 / 05 / 17 DM PHONE: _713-325-6288		
2,560'-2,259', MIX & SPOT 40 SX CL 08/30/17 RIH & TAG @ 926', PERF @ MIX & SPOT 45 SX CL "C" CMT FROM NIPPLE DOWN CUT & CAP WELL TO TURN OVER TO RECLAMATION CLOSED LOOP SYSTEM USED, CL. Spud Date: I hereby certify that the information above SIGNATURE Type or print nameMonty L. McCare	M 3,852'- 3,551'. SPOT 30 SX CL "C" CMT FROM 3,366'-3,065 "C" CMT FROM 1,300'-895'. 400', UNABLE TO PUMP IN CALLED MARK M 453' TO SURFACE, VERFIY CMT TO SURD MEET WITH RULE 19.15.7.14 NMAC REQUASS "C" CEMENT USED. CA BOND 0329. Rig Release Date: TITLE Agent for Chevron U.S	", MIX & SPOT 30 SX CL "C" CMT FROM WHITAKER W/ NM OCD OK DROP 50' FACE, JIRMENTS. ge and belief. .ADATE09 / 05 / 17		