

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

WELL API NO.
30-025-43757 ✓

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Ares 4 State ✓

8. Well Number 201H ✓

9. OGRID Number
7377 ✓

10. Pool name or Wildcat
Triple X; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
EOG Resources, Inc. ✓

3. Address of Operator
P.O. Box 2267 Midland, TX 79702

4. Well Location
Unit Letter O : 773 feet from the South line and 1646 feet from the East line
Section 4 Township 24S Range 33E NMPM County Lea ✓

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3579' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/09/17 Spud 17-1/2" hole. ✓

8/15/17 Ran 13-3/8", 54.5#, J-55 STC casing set at 1346'.
Cemented lead w/ 840 sx Class C, 13.5 ppg, 1.76 CFS yield;
tail w/ 310 sx Class C, 14.8 ppg, 1.36 CFS yield. WOC 4 hrs.
Circulated 142 bbls cement to surface.
Released surface rig.

8/18/17 Tested casing to 1500 psi for 30 minutes. Test good.

8/21/17 Resumed drilling 12-1/4" hole. ✓

Spud Date: 8/9/17

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Analyst DATE 8/25/2017

Type or print name Stan Wagner E-mail address: Petroleum Engineer PHONE: 432-686-3689

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 09/22/17
Conditions of Approval (if any):