Submit 1 Copy To Appropriate District Office <u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	ce rict I – (575) 393-6161 5 N. French Dr., Hobbs, NM 88240 rict II – (575) 748-1283 OIL CONSERVATION DIVISION			Form C-103 Revised July 18, 2013 WELL API NO. 30-025-43807	
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	1220 South St. Fran Santa Fe, NM 87	505 OCD	 5. Indicate Type of L STATE 6. State Oil & Gas Le 	FEE	
SUNDRY NOTICES AND REPORTS ON VIELS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLOS BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			 Lease Name or Unit Agreement Name Neptune 10 State Com 8. Well Number 704H 		
1. Type of Well: Oil Well Gas Well Other 2. Name of Operator Gas Well Other			9. OGRID Number 7377		
EOG Resources, Inc. / 3. Address of Operator P.O. Box 2267 Midland, TX 79702			10. Pool name or Wildcat *WC-025 G-09 S243310P; Upper Wolfcamp		
4. Well Location Unit Letter N	629 feet from the South	line and 20 ²	12 feet from th	e West line	
Section 10	Township 24S Ra	nge 33E		ounty Lea	
	11. Elevation (Show whether DR, 3607' GR	RKB, RT, GR, etc.)		a the second second	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL	COMMENCE DRII CASING/CEMENT	LING OPNS.		
 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 					
 10/7/17 Spud 14-3/4" hole. Ran 32 jts 10-3/4", 40.5#, J55 STC casing set at 1358'. 10/8/17 Cement lead w/ 755 sx Class C, 13.8 ppg, 1.64 CFS yield; tail w/ 250 sx Class C, 14.8 ppg, 1.36 CFS yield. Circulated 135 bbls cement to surface. Tested casing to 1500 psi for 30 minutes. Test good. WOC 4 hrs. Released surface rig. 					
Spud Date: 10/7/17	Rig Release Da	te:			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE Hon Way	TITLE Reg	ulatory Analyst	DATE	10/11/2017	
Type or print name Stan Wagn	er E-mail address	:	PHON	E: 432-686-3689	
For State Use Only APPROVED BY: Conditions of Approval (if any):	TITLE	Petroleum E	ngineerDATE	10/14/17	
Conditions of Approval (If any).					