Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

OCD Hobbs

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

NMLC032582A

5. Lease Serial No.

	BUREAU OF	LAND	MANAGEMENT	
SUNDRY	NOTICES	AND	REPORTS ON WEL	LS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2

7 If Unit or CA Agreement, Name and or No

6. If Indian, Allottee or Tribe Name

Type of Well					NMNM 116183		
Oil Well Gas Well Other Name of Operator					wells A #2	/	
Prime Operating Company					9. API Well No.		
3a. Address		3b. Phone No. (mclude area code)		30-025-09720			
3300 N. A, Bldg I-238, Midland, TX 79705		432-682-5774		10. Field and Pool, or Exploratory Area			
4 Location of Well (Footage, Sec. T., R., M., or Survey Description)					Jalmat (Pro Gas)		
Sec 1, T25S, R36E					11 County or Parish, State		
1980' FNL 660'FWL				Lea Co, NM			
12. CHECK AF	PPROPRIATE BOX	K(ES) TO INDICATE NA	TURE OF NOTICE, REP	ORT, OR OT	THER DATA		
TYPE OF SUBMISSION			TYPE OF ACTION				
Notice of Intent Subsequent Report	Acidize Alter Casing Casing Repair	Deepen Fracture Treat New Construction	Production (Start/Resume Reclamantion Recomplete	Water Well Other	INT TO PA P&A NR	PM	
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon	Temporarily Abandon Water Disposal		P&A R		
13. Describe Proposed or Completed If the proposal is to deepen direct Attach the Bond under which the following completion of the involtesting has been completed. Final determined that the site is ready for 1. Set 5 1/2" CIBP @ 2816.	etionally or recomplete work will be perform ved operations. If the I Abandonment Notices final inspection.)	horizontally, give subsurface le ned or provide the Bond No. operation results in a multiple s shall be filed only after all	ocations and measured and true on file with BLM/BIA. Require completion or recompletion in requirements, including reclama-	vertical depths d subsequent re a new interval, intion, have been	of all pertinent markers eports shall be filed with a Form 3160-4 shall be en completed, and the	and zones. hin 30 days e filed once	

3. Perf & Sqz 50 sx cmt @ 1219-1119'. WOC & Tag (Shoe)
4. Spot-15 sx cmt @ 100-Surface.

Perf @ 100' SOZ cont to Su. F.

2. Perf & Sqz 25 sx cmt @ 1457-1357'. WOC & Tag (T/Salt) 1280 - 1119 (T/Sact /she

5. Cut off well head, verify cmt to surface, weld on Dry Hole Marker.

RECLAMATION PROCEDURE
ATTACHED

SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. Thereby certify that the foregoing is true and correct.)						
Name (Printed Typed) CHAD (TARNER)	Title DISTRICT MANAGER					
Signature Mid Harry	Date 09/18/2017					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by Conditions of approval of any, are attached Approval of this notice does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle applicant to conduct operations thereon		Date 10-19-17				
Fit 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person States any false dictitious or fraudulent statements or representations as to any matter within its		it or agency of the United				
(Instructions on page 2)	FOR I	RECORD ONLY				

Druce OPERATION COMPANY LEASE NO. 032582 A 4. Spot 15 sx cmt @ 100-Surface. CIEC SCORES TO SURFACE 88 24,2,36 01169 SEC.1, T-255, R-56E Caut wy 500 515 3. Perf & Sqz 50 sx cmt @ 1219-1119'. WOC & Tag (Shoe) 2. Perf & Sqz 25 sx cmt @ 1457-1357'. WOC & Tag (T/Salt) 1. Set 5 1/2" CIBP @ 2816'. Circulate hole w/ MLF. Pressure Test csg. Spot 25 sx cmt (a) 2816-2556'. (B/Salt) PERES 226 - 2958' Carry 1019 5K3 PERES 2910 - 3104 SEE WY 150 SES CIRC TO SURFACE 51/2" 15.5" @ 3/89 PBTD @ 3013 D.O. TU 3013 6-02-2006

Drume OPERATING COMPANY LEASE NO. 032582 A CIEC 900 900 TO SURFACE 1980 FUL : 660 RUL SEC.1, T-259, R-36E LEA CENATY, W. ac. 88 4,2,36 @ 1169 CONT OF 500 SIS - TO SURFACE T/Selt 1230 72 3090 PERES 226 - 2958' PERES 2970 - 3104 FOR WY 150 SKS Carry 1019 9K3 CIRC TO SURFACE 51/2" 15.5" @ 3/29 1019 Sx ent PBTD @ 3013 D.O. TU 3013 6-02-2006

32.1611061

-103.2251968

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Henryetta Price Environmental Protection Specialist 575-234-5951

Shelly Tucker Environmental Protection Specialist 575-234-5979

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612