

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-61278
5. Indicate Type of Lease FEDERAL STATE <input type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. NMNM-022060
7. Lease Name or Unit Agreement Name SHERRI
8. Well Number 1
9. OGRID Number 14424
10. Pool name or Wildcat Pecos Slope; Abo, West (Gas)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
State of New Mexico formerly McKay Oil Corp

3. Address of Operator
1625 N. French Drive Hobbs, NM 88240

4. Well Location
Unit Letter **J** : **1980** feet from the **SOUTH** line and **1880** feet from the **EAST** line
Section **28** Township **8S** Range **22E** NMPM County **CHAVES**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED PROCEDURE & SCHEMATICS

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mark Whitaker TITLE Petroleum Engr. Specialist DATE 8/22/2017

Type or print name Mark Whitaker E-mail address: marka.whitaker@state.nm.us PHONE: 575-393-6161

For State Use Only

APPROVED BY: Markus Brown TITLE AO/II DATE 11/1/2017

Conditions of Approval (if any)

McKay Oil Corp
Sherri No. 1
30-005-61278
UL – J, Sec. 28, T8S, R22E
1980' FSL & 1880' FEL
BLM Serial #: NMNM – 022060

13 3/8" 48# @ 96' w/ redi-mix
9 5/8" 40# @ 852' w/ 700 sx cmt
4 1/2" 10.5# @ 3233' w/ 325 sx cmt
Top Perforation 2472'

1. MIRU. POOH w/ production equipment.
2. Set CIBP at 2372'. Circulate hole with mud laden fluid. Pressure test casing to 500 psi. Spot 25 sx cement on CIBP.
3. Perf @ 902'. Sqz w/ 55 sx. WOC. Tag at 802' or better.
4. Perf @ 146'. Circulate cement to surface inside/outside 4 1/2" casing.
5. Cut off wellhead 3' below ground level and verify cement to surface all strings.
6. Install below ground P&A marker. Photos should be taken prior to and after welding on plate. Record GPS reading. BLM should be notified prior to cut off so it can be witnessed.

NOTES: Mud laden fluid consists of fresh water with 25 sx salt gel per 100 bbls of fluid. If casing will not hold pressure, contact the OCD for instructions prior to proceeding with P&A.

CURRENT
30-005-61278

McKay Oil
Sherri #1

13 3/8" 48# @ 96' w/ Redi-Mix. Circ


9 5/8" 40# @ 852' w/ 700 sx. Cmt circ.

Top Perf 2472'

4 1/2" 10.5# @ 3233' w/ 325 sx. TOC unknown

McKay Oil Corp
Sherri #1

PROPOSED
30-005-61278



13 3/8" 48# @ 96'

9 5/8" 40# @ 852'

Top Perf 2472

4 1/2" 10.5# @ 3233'

CUT OFF WELLHEAD 3' BELOW GL,
VERIFY CEMENT, & INSTALL BELOW GROUND
MARKER. TAKE PHOTO & GPS READINGS

PERF @ 146'. CIRC CMT TO SURFACE

PERF @ 902'. SQZ W/ 55 SX. WOC & TAG.

**PRESSURE TEST CASING
CIRCULATE MUD LADEN FLUID**

SET CIBP AT 2372'. CAP WITH 25 SX