Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5. Lease Serial No.

)	NMNM122622

Do not use thi abandoned we	6. If Indian, Allottee or	Tribe Name						
SUBMIT IN	7. If Unit or CA/Agreen	ment, Name and/or No.						
Type of Well	8. Well Name and No. OPHELIA 22 FED COM 705H							
Name of Operator EOG RESOURCES, INC.	Contact: E-Mail: stan_wagn		9. API Well No. 30-025-44007					
3a. Address ATTN: STAN WAGNER P.O. MIDLAND, TX 79702	3b. Phone No. (include area code) Ph: 432-686-3689			10. Field and Pool or Exploratory Area WC-025 S263327G UPPR WC				
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description,		11. County or Parish, State					
Sec 22 T26S R33E Mer NMP	NWNW 200FNL 679FWL		LEA COUNTY, NM					
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE OI	F NOTICE,	REPORT, OR OTH	ER DATA		
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION							
□ Notice of Intent	☐ Acidize ☐		Deepen Produc		on (Start/Resume)	☐ Water Shut-Off		
	☐ Alter Casing ☐ I		raulic Fracturing	☐ Reclamation		■ Well Integrity		
	☐ Casing Repair ☐		Construction	☐ Recomplete		Other Drilling Operations		
☐ Final Abandonment Notice			ig and Abandon		arily Abandon	Drining Operations		
8,	Convert to Injection		g Back	☐ Water Disposal				
13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection. 10/17/17 Spud 14-3/4" hole. Ran 24 jts 10-3/4", 40.5#, J55 STC casing set at 1006'. 10/18/17 Cement lead w/ 590 sx Class C, 13.8 ppg, 1.64 CFS yield; tail w/ 250 sx Class C, 14.8 ppg, 1.36 CFS yield. Circulated 105 bbls cement to surface. Tested casing to 1500 psi for 30 minutes. Test good. 10/19/17 Resumed drilling 9-7/8" hole. 10/25/17 Ran 7-5/8", 29.7#, HCP-110 LTC (0'-7526') DV tool at 4900'. Ran 7-5/8", 29.7#, ICYP-110 MO-FXL (7526'-11658') 1st stage: Cement lead w/ 610 sx Class C, 10.8 ppg, 3.48 CFS yield;								
Name (Printed/Typed) STAN WA	Electronic Submission # For EOG F Committed to AFMSS for	RESOURCES,	INC., sent to the I / JENNIFER SANC	Hobbs	30/2017 ()			
Signature (Electronic S	Submission)	Date 10/30/2017 ACCEPTED FOR/RECORD						
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE US	SE 3 0 017			
Approved By Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the second of the sec	uitable title to those rights in the act operations thereon. U.S.C. Section 1212, make it a	subject lease crime for any pe			OF LAND MANAZEM LSBAD FILLD OFFICE ke to any department or a			
States any false, fictitious or fraudulent	statements or representations as	to any matter w	unin its jurisdiction.		/			

(Instructions on page 2)

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **



Additional data for EC transaction #393456 that would not fit on the form

32. Additional remarks, continued

tail w/ $605 \, \mathrm{sx}$ Class H, $15.6 \, \mathrm{ppg}$, $1.25 \, \mathrm{CFS}$ yield. Circulated 93 bbls cement to surface

10/26/17 2nd stage: Cement lead w/ 1295 sx Class C, 12.7 ppg, 2.37 CFS yield; tail w/ 75 sx Class C, 14.8 ppg, 1.45 CFS yield. WOC 4 hrs. Circulated 438 sx cement to surface. Tested casing to 2600 psi for 30 minutes. Test good. Resumed drilling 6-3/4" hole.