District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

GAS CAPTURE PLAN

Date: 10/13/17						
□ Original		Operator & OG	RID No.: <u>BTA</u>	Oil Producers	LLC O	GRID # 26029°
☐ Amended - Reason for Amendme	nt:	<u>.</u>				
This Gas Capture Plan outlines actionew completion (new drill, recomple		•		well/production	on facility fla	ring/venting fo
Note: Form C-129 must be submitted and Well(s)/Production Facility - Name		_	days allowed by	Rule (Subsection	A of 19.15.18.	12 NMAC).
The well(s) that will be located at the	product	ion facility are sho	wn in the table	below.		
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Vaca Draw 9418 10 Federal #9H	NA	D-10-25S-33E	200'FNL 550'FWL	1000	0	NA
30	-029	-47251				

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Energy Transfer and will be connected to Energy Transfer's low pressure gathering system located in Lea County, New Mexico. It will require ~1100' of pipeline to connect the facility to low pressure gathering system. BTA Oil Producers, LLC provides (periodically) to Energy Transfer a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, BTA Oil Producers, LLC and Energy Transfer have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Jal 3 Plant located in Sec. 22, Twn. 24 South, Rng. 37 East, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on energy Transfers system at that time. Based on current information, it is BTA Oil Producers, LLC belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines