

District II

811 S. First St., Artesia, NM 88210 District III
 1000 Rio Brazos Road, Aztec, NM 87410 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources Department
 Oil Conservation Division 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Submit Original to Appropriate District Office

GAS CAPTURE PLAN

Date: 6/22/17

☒ Original

Operator & OGRID No.: McElvainEnergyInc (22044)

☐ Amended - Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

The well(s) that will be located at the production facility are shown in the table below.

Well(s)/Production Facility – Name of facility

EK 30 BS2 FED COM 2H.... P-30-18S-34E-150' FSL-876' FEL....800 MCFD....Targa Versado Station

EK 31 BS2 FED COM 1H..... P-30-18S-34E-124' FSL-892' FEL....800 MCFD....Targa Versado Station

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Targa and will be connected to Targa low pressure gathering system located in Lea County, New Mexico. It will require ~4,161' of pipeline to connect the facility to low pressure gathering system. McElvain provides (periodically) to Targa a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, McElvain and Targa have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Targa/Versado Processing Plant located near Monument, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on the Targa system at that time. Based on current information, it is McElvain's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines