	lexico	Form C-103
District I - (575) 393-6161 1625 N. French Dr., Hobbs, NM 8HOBE District II - (575) 748-1283 811 S. First St., Artesia, NM 88210  Energy, Minerals and Natural Resources OCD OIL CONSERVATION DIVISION		Revised August 1, 2011 WELL API NO.
		30-025-26833
District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 8741AN 03 2018 1220 South St. Fra	encis Dr.	5. Indicate Type of Lease  STATE ☑ FEE □
	37505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fc, NECEIVED  87505		
SUNDRY NOTICES AND REPORTS ON WELL	S	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR P	LUG BACK TO A	North Hobbs (G/SA) Unit
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101)   PROPOSALS.)	-OK SUCH	Section 30
1. Type of Well: Oil Well Gas Well Other: Injector		8. Well Number: 222
2. Name of Operator Occidental Permian Ltd.		9. OGRID Number: 157984
3. Address of Operator		10. Pool name or Wildcat Hobbs (G/SA)
HCR 1 Box 90 Denver City, TX 79323		,
4. Well Location		
Unit LetterF_:1470feet from theNorth line and1395feet from theWestline		
Section 30 Township 18S Range 38E NMPM Lea County		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3611' RDB		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO:	SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☑ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING [		
TEMPORARILY ABANDON	COMMENCE DRI	LLING OPNS. P AND A
PULL OR ALTER CASING MULTIPLE COMPL	CASING/CEMENT	I JOB
DOWNHOLE COMMINGLE		
OTHER:	OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
proposed completion of recompletion.		
		npletions: Attach wellbore diagram of
MIRU Pulling Unit		
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> </ol>	itly isolated between	packers)
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF AIH with reconfigured injection equipment leaving perf interval 4</li> </ol>	itly isolated between	packers) prations.
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4</li> <li>Turn well to injection.</li> </ol>	ntly isolated between and acidize all perfo 147'-4152' open to in	packers) orations. njection.
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4</li> <li>Turn well to injection.</li> </ol>	atly isolated between and acidize all performance 147'-4152' open to in	packers) prations. njection. uring this procedure we plan to use
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4</li> <li>Turn well to injection.</li> <li>Condition of Approval: notify</li> <li>OCD Hobbs office 24 hours</li> </ol>	atly isolated between and acidize all performance 147'-4152' open to in D	packers) orations. njection. uring this procedure we plan to use ne closed-loop system with a steel
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4 Turn well to injection.</li> <li>Condition of Approval: notify</li> <li>OCD Hobbs office 24 hours</li> </ol>	atly isolated between and acidize all performance 147'-4152' open to in D	packers) prations. njection. uring this procedure we plan to use
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4 Turn well to injection.</li> <li>Condition of Approval: notify</li> <li>OCD Hobbs office 24 hours</li> <li>prior of running MIT Test &amp; Chart</li> </ol>	atly isolated between and acidize all perfo 147'-4152' open to in D ti	packers) prations. njection. uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4 Turn well to injection.</li> <li>Condition of Approval: notify</li> <li>OCD Hobbs office 24 hours</li> </ol>	atly isolated between and acidize all perfo 147'-4152' open to in D ti	packers) prations. njection. uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4 Turn well to injection.</li> <li>Condition of Approval: notify</li> <li>OCD Hobbs office 24 hours</li> <li>prior of running MIT Test &amp; Chart</li> </ol>	atly isolated between and acidize all perfo 147'-4152' open to in D ti	packers) prations. njection. uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required
<ol> <li>MIRU Pulling Unit</li> <li>POOH with injection equipment (perf interval 4147'-4152' currer</li> <li>Re-perforate all existing perf intervals in 4" liner (currently 2 SPF RIH with reconfigured injection equipment leaving perf interval 4 Turn well to injection.</li> <li>Condition of Approval: notify</li> <li>OCD Hobbs office 24 hours</li> <li>prior of running MIT Test &amp; Chart</li> </ol>	atly isolated between (1) and acidize all performance (147'-4152' open to in the control of the	packers) prations. njection. uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required isposal per ODC Rule 19.15.17
1. MIRU Pulling Unit 2. POOH with injection equipment (perf interval 4147'-4152' currer 3. Re-perforate all existing perf intervals in 4" liner (currently 2 SPF 4. RIH with reconfigured injection equipment leaving perf interval 4 5. Turn well to injection. 6. 7. Condition of Approval: notify 8. OCD Hobbs office 24 hours 9. prior of running MIT Test & Chart  Spud Date: Rig Release I	atly isolated between (1) and acidize all performance (147'-4152' open to in the control of the	packers) prations. njection. uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required isposal per ODC Rule 19.15.17
1. MIRU Pulling Unit 2. POOH with injection equipment (perf interval 4147'-4152' currer 3. Re-perforate all existing perf intervals in 4" liner (currently 2 SPF 4. RIH with reconfigured injection equipment leaving perf interval 4 5. Turn well to injection. 6. 7. Condition of Approval: notify 8. 9. OCD Hobbs office 24 hours 9. prior of running MIT Test & Chart  Spud Date: Rig Release I	otly isolated between (1) and acidize all performance (1) and	packers) prations. njection.  uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required isposal per ODC Rule 19.15.17
1. MIRU Pulling Unit 2. POOH with injection equipment (perf interval 4147'-4152' currer 3. Re-perforate all existing perf intervals in 4" liner (currently 2 SPF 4. RIH with reconfigured injection equipment leaving perf interval 4 5. Turn well to injection. 6. 7. Condition of Approval: notify 8. OCD Hobbs office 24 hours 9. Prior of running MIT Test & Chart  Spud Date: Rig Release I	otly isolated between (1) and acidize all performance (147'-4152' open to in the control of the	packers) prations. njection.  uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required isposal per ODC Rule 19.15.17  e and belief.
1. MIRU Pulling Unit 2. POOH with injection equipment (perf interval 4147'-4152' currer 3. Re-perforate all existing perf intervals in 4" liner (currently 2 SPF 4. RIH with reconfigured injection equipment leaving perf interval 4 5. Turn well to injection. 6. 7. Condition of Approval: notify 8. 9. OCD Hobbs office 24 hours 9. prior of running MIT Test & Chart  Spud Date: Rig Release I  I hereby certify that the information above is true and complete to the  SIGNATURE May Be E-mail address right interval 4147'-4152' currer  Type or print name _Rick Reeves E-mail address_right.	otly isolated between (1) and acidize all performance (1) and	packers) prations. njection.  uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required isposal per ODC Rule 19.15.17  e and belief.
1. MIRU Pulling Unit 2. POOH with injection equipment (perf interval 4147'-4152' currer 3. Re-perforate all existing perf intervals in 4" liner (currently 2 SPF 4. RIH with reconfigured injection equipment leaving perf interval 4 5. Turn well to injection. 6. 7. Condition of Approval: notify 8. OCD Hobbs office 24 hours 9. Prior of running MIT Test & Chart  Spud Date: Rig Release I  I hereby certify that the information above is true and complete to the  SIGNATURE Mandal TITLE for the SIGNATURE E-mail address_rig  For State Use Only	otly isolated between (1) and acidize all performance (147'-4152' open to in the control of the	packers) prations. njection.  uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required isposal per ODC Rule 19.15.17  e and belief.  PHONE: 713-215-7653
1. MIRU Pulling Unit 2. POOH with injection equipment (perf interval 4147'-4152' currer 3. Re-perforate all existing perf intervals in 4" liner (currently 2 SPF 4. RIH with reconfigured injection equipment leaving perf interval 4 5. Turn well to injection. 6. 7. Condition of Approval: notify 8. 9. OCD Hobbs office 24 hours 9. prior of running MIT Test & Chart  Spud Date: Rig Release I  I hereby certify that the information above is true and complete to the  SIGNATURE May Be E-mail address right interval 4147'-4152' currer  Type or print name _Rick Reeves E-mail address_right.	otly isolated between (1) and acidize all performance (147'-4152' open to in the control of the	packers) prations. njection.  uring this procedure we plan to use ne closed-loop system with a steel ank and haul contents to the required isposal per ODC Rule 19.15.17  e and belief.