District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

GAS	CA	PT	URF	' PI	AN

☐ Original	Operator & OGRID	No.: Chevron U.S.A. Inc 4323
NEW DRILLS		Date:08/23/2017
Reason for Amendment:_		Duty. 00/25/2017
_		· · · · · · · · · · · · · · · · · · ·

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
SD EA 29 32 FED COM P11 13H 30-0	NEW 25 - 4433 3	D,SEC 29, T26S R33E	195 FNL 828 FWL	2081	0	
SD EA 29 32 FED COM P11 14H	NEW	D,SEC 29,T26S, R33E	195 FNL 853 FWL	2287	0	
SD EA 29 32 FED COM P11 15H	NEW	D,SEC 29,T26S, R33E	195 FNL 878 FWL	2081	0	
SD EA 29 32 FED COM P11 16H	NEW	D,SEC 29,T26S, R33E	195 FNL 903 FWL	2287	0 .	

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <u>Delaware Basin Midstream</u>, <u>LLC (DBM)</u> and will be connected to <u>DBM's</u> low/high pressure gathering system located in Lea County, New Mexico. It will require <u>500'</u> of pipeline to connect the facility to low/high pressure gathering system. <u>Chevron U.S.A.</u> provides (periodically) to <u>DBM</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>Chevron U.S.A.</u> and <u>DBM</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>DBM's Ramsey</u> Processing Plant located in Sec. 36, Block 57-T1, Reeves County, Texas. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to permanent production facilities. Temporary sand separation equipment will be installed at the well and will be blown down to an atmospheric tank as needed during the initial flow period. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on the DBM system at that time. Based on current information, it is CHEVRON'S belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared

- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines