(DO NOT USE THIS FORM FOR PROPO	State of New Mexic Energy, Minerals and Natural OIL CONSERVATION D 1220 South St. Francis Santa Fe, NM 8750 ICES AND REPORTS ON WELLS DISALS TO DRILL OR TO DEEPEN OR PLUG CATION FOR PERMIT" (FORM C-101) FOR S	Resources WELL API N 30-005-61446 5. Indicate Ty STATE 6. State Oil & 7. Lease Nam Camp State	ype of Lease E X FEE & Gas Lease No ne or Unit Agreement Name
Type of Well: Oil Well Name of Operator State of New Mexico formerly Mc Address of Operator 1625 N. French Drive Hobbs 4. Well Location	Kay Oil Corp JAN 082 RECEI	9. OGRID No	umber
Unit Letter J : 1980 feet from the South line and 1980 feet from the East line Section 25			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INT			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE			
SIGNATURE	IIILE		_DATE
Type or print name For State Use Only APPROVED BY: Conditions of Approval (if any):	E-mail address: _		PHONE:

Plugging Report Camp State #1

Lat: 33.8428786639 Lon: -104.584880025

Moved equipment, cleared location and rigged up. The $4\frac{1}{2}$ " casing has a large hole in it below the wellhead. The wellhead began to break off when we were removing the old valves. We will address the problem in the morning. SION

12/20/2017 Brought in workstring to location. Cut off 4 ½" casing flush with the 8 5/8" surface head. Welded 5 ½" collar to the top plates of the surface head and installed a 5 ½" X 8 5/8" Larkin wellhead. Installed the BOP and started picking up the workstring. Tagged up at 3082'. Circulated MLF and tested casing to 550#. Casing good. Spotted 25 sx cement on top of the CIBP. POOH with pipe and perforated at 1544'. RIH and set packer at 1202'. While establishing circulation, the cap on the surface head started leaking and fluid would not travel to the pit and filled up the cellar. Cut a plate and put around the 5 ½" collar that was used to address the original problem. Welded the plate to the 5½" collar and the surface cap to seal the leak. Squeezed the perfs with 45 sx and SION.

12/21/2017 Released packer and tagged cement at 1393'. Laid down remaining pipe and perforated at 110'. Circulated cement to surface with 30 sacks. Rigged down and cut off wellhead. Filled up both strings with less than 1 sack of cement. Installed marker, cut off anchors, and cleaned the pit.