

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Carlsbad Field Office

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

OCD Hobbs

5. Lease Serial No.
NMNM26079

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

EOG RESOURCES INCORPORATED

Contact: STAN WAGNER

E-Mail: stan_wagner@eogresources.com

3a. Address

MIDLAND, TX 79702

3b. Phone No. (include area code)

Ph: 432-686-3689

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 15 T25S R33E SWSE 250FSL 1450FEL

8. Well Name and No.

STREETCAR 15 FED 7031

9. API Well No.

30-025-42879-00-X1

10. Field and Pool or Exploratory Area

WC025G09S253309A-UPR WOLFCAM

11. County or Parish, State

LEA COUNTY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Hydraulic Fracturing☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☒ Other
Change to Original A
PD

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompletable horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletable in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

EOG Resources requests an amendment to our approved APD for this well to reflect the addition of a DV tool to the intermediate casing string.

Casing design information attached.

- The well has been plugged.

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #386684 verified by the BLM Well Information System
For EOG RESOURCES INCORPORATED, sent to the Hobbs
Committed to AFMSS for processing by PRISCILLA PEREZ on 09/20/2017 (17PP0615SE)

Name (Printed/Typed) STAN WAGNER

Title REGULATORY ANALYST

Signature (Electronic Submission)

Date 08/29/2017

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

WITHDRAWN

MUSTAFA HAQUE
Title PETROLEUM ENGINEER

Date 01/09/2018

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Hobbs

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

EOG RESOURCES, INC.
STREETCAR 15 FED NO. 703H

Cementing Program:

Depth	No. Sacks	Wt. ppg	Yld Ft ³ /ft	Mix Water Gal/sk	Slurry Description
7-5/8" 11,400' DV Tool w/ ECP @ 5,000'	500	10.8	3.48	20.96	Stage 1 Lead: Class C + 0.3% GXT-C + 0.4% CPT-503P + 0.2% CPT-45 + 3 pps Kol Seal + 0.6% CPT-30 + 0.1% CPT-20A + 0.1% Citric Acid + 5% Gypsum + 5% Salt
	540	15.6	1.22	5.38	Stage 2 Tail: Class H + 3% MagOx + 0.5% CPT-30 + 0.3% CPT-20A
	1350	12.7	2.37	13.27	Stage 2 Lead: Class C + 10% Salt + 6% Gel + 3% MagOx + 0.25 pps Celloflake + 0.4% CPT-20A
	75	14.8	1.45	6.90	Stage 2 Tail: Class C + 10% Salt + 3% MagOx + 0.25% CPT-20A

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.