

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

AMENDED

WELL API NO.

30-025-44161

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Red Tank 30-31 State Com

8. Well Number 24Y

9. OGRID Number 16696

10. Pool name or Wildcat
Red Tank; Bone Spring, East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

HOBBS OCD

2. Name of Operator OXY USA INC.

JAN 17 2018

3. Address of Operator P.O. BOX 50250 MIDLAND, TX 79710

RECEIVED

4. Well Location

Unit Letter A : 200 feet from the NORTH line and 270 feet from the EAST line

Section 30 Township 22S Range 33E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3660' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/24/17 drill 12-1/4" hole to 6880', 11/28/17. RIH & set 9-5/8" 47# L-80 BTC csg @ 6867', pump 20BFW spacer w/red dye then cmt w/ 2015sx (1007bbl) PPC w/ additives 11ppg 2.8 yield followed by 370sx (87bbl) PPC w/ additives 14.8ppg 1.33 yield, circ 1140sx (570bbl) cmt to surface, WOC. Install pack-off, test to 5000#, good test. 11/30/17 Pressure test csg to 4700# for 30 min, good test. Drill new formation to 6890', perform FIT test EMW=8.4ppg, 680psi, good test.

11/30/17 Drill 8-1/2" hole to 20600'M 10863'V 12/13/17. RIH & set 5-1/2" 20# P-110 csg @ 20590'. Pump 40BFW spacer then cmt w/ 560sx (282bbl) PPC w/ additives @ 11ppg 2.8 yield followed by 1700sx (498bbl) PPH w/ additives @ 13.2ppg 1.65 yield, calc. TOC @ 1865', WOC. ND BOP, Install wellhead cap. RD Rel Rig 12/17/17.

NOTE: Amended production casing TOC.

Spud Date:

11/21/17

Rig Release Date:

12/17/17

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Regulatory Coordinator DATE 1/11/18

Type or print name Jana Mendiola E-mail address: janalyn_mendiola@oxy.com PHONE: 432-685-5936

For State Use Only

APPROVED BY:  TITLE Petroleum Engineer DATE 01/23/18

Conditions of Approval (if any):