Submit 1 Copy To Appropriate District Office District I – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 District III – (575) 748-1283 811 S. First St., Artesia, NM 88240 District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410.8  State of New Mexico Fiergy, Minerals and Natural Resources 1220 South St. Francis Dr.	Form C-103 Revised July 18, 2013
District I – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283 811 S. First St., Artesia, NM 88310 District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 874 10 District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	WELL API NO. 30-025-44338
811 S. First St., Artesia, NM 8871 District III – (505) 334-6178	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505	STATE FEE  6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Python 36 State Com
Type of Well: Oil Well  Gas Well Other      Name of Operator	8. Well Number 702H 9. OGRID Number
EOG Řesources, Inc.	7377
3. Address of Operator P.O. Box 2267 Midland, TX 79702	10. Pool name or Wildcat WC-025 G-09 S253309A; Upper WC
4. Well Location M 310 South , 736	West
Unit Letter : feet from the line and Section 36 Township 24S Range 32E	feet from the line  NMPM County Lea
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3557' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  TEMPORARILY ABANDON  CHANGE PLANS  COMMENCE DRIL	
PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMENT DOWNHOLE COMMINGLE	JOB 🔽
CLOSED-LOOP SYSTEM	
OTHER:  OTHER:  OTHER:  OTHER:	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Comproposed completion or recompletion.	pletions: Attach wellbore diagram of
2/20/18 Resumed drilling 12-1/4" hole. 2/22/18 Ran 9-5/8", 40#, J-55 LTC (0' - 3952')	
Ran 9-5/8", 40#, HCK-55 LTC (3952' - 4286')	
Cement lead w/ 1115 sx Class C, 12.7 ppg, 2.24 CFS yield; tail w/265 sx class C, 14.8 ppg, 1.34 CFS yield.	
Circulated 150 bbls cement to surface. WOC 4 hrs Tested casing to 2250 psi for 30 minutes. Test good.	
Released surface rig.	
Spud Date: 2/12/18 Rig Release Date:	
Spud Date: 2/12/18 Rig Release Date:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Thereby certify that the information above is true and complete to the best of my knowledge	and benefit.
SIGNATURE SIGNATURE Regulatory Tech	DATE 3/2/2018
Type or print name Elizabeth Castillo E-mail address:	PHONE: 432-686-3697
For State Use Only	
APPROVED BY: Men That TITLE Haff Mgr.	DATE 3-7-18