District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department 2018

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

GAS CAPTURE TO

Submit Original to Appropriate District Office



Date	: 10-13-2017		OA5 CA	TICKETE	AII		
	Original mended - Reason for A	Amendment:_	Operator	& OGRID 1	No.: <u>Mewbo</u>	urne Oil Con	npany - 14744
new Note:	Gas Capture Plan out completion (new drill, Form C-129 must be sub (s)/Production Facili	recomplete to	o new zone, re-fra	activity.		,	facility flaring/venting for a of 19.15.18.12 NMAC).
The well(s) that will be located at the production facility are shown in the table below.							
	Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
-	IBEX 10 B3NC FED COM #111 30-0	25-44-58	C-15-23S-34E	185' FNL & 1750' FWL	0	NA	ONLINE AFTER FRAC
Well place Ene 200 (perio be di confe	e. The gas produced rgy Transfer low/h of pipeline to c odically) to Energy Trans rilled in the foreseeable	o a production from production production pressure onnect the farger and le future. In a changes to Processing F	n facility after flotion facility is de gathering system cility to low/high drilling, completio addition, Mewbodrilling and complant located in Se	dicated to not located in pressure gas not	LEA Cuthering syst ted first produmpany and dules. Gas n. 245, Rn	County, New em. Mewbo uction date for these g. 37E, Lea	wells will be processed at County, New Mexico.
After flared sand, produ	d or vented. During flo the wells will be turn	wback, the fled to product there are operated	uids and sand contion facilities. Gastational issues on _	tent will be r s sales shoul Energy Transfer	nonitored. V d start as so system at	When the procon as the well	uction tanks and gas will be duced fluids contain minimal lls start flowing through the sed on current information, it

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease