

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-041-20965
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name STOLTENBERG
8. Well Number 002
9. OGRID Number 263940
10. Pool name or Wildcat TULE MONTOYA;PENN

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
SOVEREIGN EAGLE LLC

3. Address of Operator
PO BOX 968, ROSWELL NM 88202-0968

4. Well Location

Unit Letter F : 1650 feet from the NORTH line and 2260 feet from the WEST line
Section 26 Township 2S Range 29E NMPM County Roosevelt Unit

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4394'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT

REMEDIAL WORK
COMMENCE DRILLING OPNS
CASING/CEMENT JOB
OTHER: ☐

INT TO PA
P&A NR
P&A R

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of
proposed completion or recompletion.

PROPOSE TO PLUG AND ABANDON:

Cement is circulated behind 5 1/2" casing.

1. SET CAST IRON BRIDGE PLUG AT 7201' ABOVE MONTOYA PERFS 7212-7218' WITH 35' OF CEMENT ON IT.
2. Run in hole with tubing and squeeze packer and squeeze CANYON PERFS 6670-7106 and leave 100' of cement above perfs.
3. CIRCULATE MUD LADEN FLUIDS & PRESSURE TEST CASING.
4. SET 35 SX CEMENT PLUG INSIDE CASING FROM 4000'-4100'.
5. SET 35 SX CEMENT PLUG INSIDE CASING FROM 2150'-2250', WOC & TAG CEMENT 2360'-2460'
6. SET 35 SX CEMENT PLUG INSIDE FROM 275'-375' WOC & TAG CEMENT SURFACE-425'
7. NIPPLE DOWN WELLHEAD AND SET CEMENT PLUG FROM 60' TO SURFACE, CUT OFF WELLHEAD 3' BELOW
GROUND LEVEL & INSTALL DRY HOLE MARKER AND CLEAN LOCATION AFTER CEMENT IS VERIFIED AT SURFACE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Paul Ragdale TITLE: OPERATIONS MANAGER DATE 3/12/2018

Type or print name PAUL RAGSDALE E-mail address: pragsdale@stratanm.com PHONE: 575-622-1127 ext 18

For State Use Only

APPROVED BY: Manuel Brittan TITLE Petroleum Engr. Specialist DATE 03/20/2018
Conditions of Approval (if any):

NOTIFY OCD 24 HOURS PRIOR TO
BEGINNING PLUGGING OPERATIONS

C103 INTENT TO P&A EXPIRES
03-20-2019

COMPANY SOVEREIGN EAGLE, LLC			LEASE TYPE <input type="checkbox"/> STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> FEDERAL			API NO. #30-041-20965		SPUD DATE 11/09/14	
WELL NAME STOLTENBERG #2		SECTION 26		TWP. 2-S		RANGE 29-E		COUNTY / STATE ROOSEVELT / NM	
FOOTAGE 1650' FSL & 2260' FWL		ELEVATION = 4394'		KELLY BUSHING = 4411'		STATUS Gas		TOTAL DEPTH = 7290'	
FIELD/POOL/AREA TULE		Size		Sks. Cmt.		TOC		Weight	
		SURF. CASING		13 3/8"		350		CIRC. 48#	
		INT. CASING		8 5/8"		1000		CIRC. 24#	
		CASING		5 1/2"		1405		CIRC. 17# LT&C	
LOCATION DESCRIPTION 20 MI NW OF Elida, NM									
Depth ft.		Description		O.D.		Length		Depth	
300		13 3/8" CSG. 48# @375' w/350 sacks							
1000									
2000									
3000		8 5/8" CSG. 24# @ 2410' w/1000 sacks							
4000									
5000									
6000									
6500									
7000		6767-6773 squeezed with 250 sx		Cisco					
		6883-6898		Penn A Lime					
		7043-7049		Penn A sand					
		7103-7106		Penn C sand					
		RBP @7201'							
		Perfs 7212-7218 open 15 holes		Montoya					
		Perfs 7256-7270 squeezed		lower Montoya					
8000		5 1/2" CSG. 17# @7349' w/1405 sacks							
		TD = 7290'		PBSD = 7290'					
COMMENTS:				<div style="display: flex; align-items: center;"> =Existing Packer =Cement Plug =Perfs-Open =Perfs-Squeezed =CIBP In Place </div>		SOVEREIGN EAGLE, LLC P.O. BOX 3900 ROSWELL, NEW MEXICO 88202 <small>Revised 07/21/2014</small>			