Submit 1 Copy To Appropriate District Office	State of New Mexico		Form C-103
District I - (575) 393-6161	Energy, Minerals and Natural H	Resources	Revised August 1, 2011 WELL API NO.
District II - (575) 748-1283			30-025-44312
811 S. First St., Artesia, NM 88210 District III – (505) 334-6178	1220 South St. Francis		5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	a charter of the first of the f	STATE FEE 6. State Oil & Gas Lease No.
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM			0. State Off & Gas Lease No.
87505 SUNDRY NOTICE	ES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSAL DIFFERENT RESERVOIR. USE "APPLICA" PROPOSALS.)	LS TO DRILL OR TO DEEPEN OR PLUG BA		South Hobbs (G/SA) Unit
	as Well 🗌 Other: Injector	600	8. Well Number: 291
2. Name of Operator Occidental Permian Ltd.	HOBES	200	9. OGRID Number: 157984
3. Address of Operator HCR 1 Box 90 Denver City, TX 7932	MAR 20	2018	10. Pool name or Wildcat Hobbs (G/SA)
4. Well Location Unit Letter J : 1608 feet from the South Received 1468 feet from the East line			
Section 6		ange 38E	NMPM Lea County
	11. Elevation (Show whether DR, RK	0	
3636.1 (KB)			
12. Charle Ammennicate Device Indicate Mature of Matice, Depart on Other Date			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB			
DOWNHOLE COMMINGLE			
OTHER: Initial Completi	on 🛛 OT	HER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date			
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
	an lation	1	
proposed completion of recom	pletion.		
1. MIRU PU. NU BOP			procedure we plan to use
 MIRU PU. NU BOP RIH with bit and drill out well to f 		During this	procedure we plan to use
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) 	loat collar	During this	loop system with a steel
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 	loat collar formations w/ 4 SPF at: 4306-12,	During this the closed- tank and ha	loop system with a steel aul contents to the required
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40,	During this the closed- tank and ha	loop system with a steel
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40,	During this the closed- tank and ha disposal pe	loop system with a steel aul contents to the required r ODC Rule 19.15.17
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40,	During this the closed- tank and ha disposal pe	loop system with a steel aul contents to the required
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40,	During this the closed- tank and ha disposal pe Condition	loop system with a steel aul contents to the required r ODC Rule 19.15.17
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool	During this the closed- tank and ha disposal pe Condition OCD Hob	loop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bbs office 24 hours
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool	During this the closed- tank and ha disposal pe Condition OCD Hob	loop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool	During this the closed- tank and ha disposal pe Condition OCD Hob	loop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bbs office 24 hours
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online 	loat collar formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool	During this the closed- tank and ha disposal pe Condition OCD Hob	loop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bbs office 24 hours
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online 	Tormations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool	During this the closed- tank and ha disposal pe Condition OCD Hob rior of runn	loop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bs office 24 hours ing MIT Test & Chart
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online 	Tormations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool	During this the closed- tank and ha disposal pe Condition OCD Hob rior of runn	loop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bs office 24 hours ing MIT Test & Chart
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online 	Tormations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool	During this the closed- tank and ha disposal pe Condition OCD Hob rior of runn	loop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bs office 24 hours ing MIT Test & Chart
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online Spud Date: I hereby certify that the information ab SIGNATURE Type or print name	loat collar formations w/ 4 SPF at: 4306-12, .90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool Rig Release Date	During this the closed- tank and ha disposal pe Condition OCD Hob rior of runn f my knowledge	and belief.
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online Spud Date: I hereby certify that the information ab	loat collar Formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool Rig Release Date ove is true and complete to the best of Cox	During this the closed- tank and ha disposal pe Condition OCD Hob rior of runn f my knowledge	boop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bs office 24 hours ing MIT Test & Chart
 MIRU PU. NU BOP RIH with bit and drill out well to f Log well (GR/CCL/CBL) Selectively perforate San Andres f 4336-42, 4347-49, 4354-64, 4380- 4454-68 AT new perfs with 6,700 gal 15% RIH with injection equipment Set injection packer at ±4256' Bring well online Spud Date: I hereby certify that the information ab SIGNATURE Type or print name	loat collar Formations w/ 4 SPF at: 4306-12, 90, 4403-13, 4422-24, 4432-40, HCL using 20' PPI tool Rig Release Date ove is true and complete to the best of Cox	During this the closed- tank and ha disposal pe Condition OCD Hob rior of runn f my knowledge	boop system with a steel aul contents to the required r ODC Rule 19.15.17 of Approval: notify bs office 24 hours ing MIT Test & Chart