District_I 1625 N. French Dr., Hobbs, NM 88240 District_II 811 S. First St., Artesia, NM 88210 District_III 1000 Rio Brazos Road, Aztec, NM 87410 District_IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources OCD

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505



GAS CAPTURE PLAN

Date: 03//9/2018		
■ Original Amended - Reason for Amendment:	Operator & OGRID No.: _MAMMOTH EXPLORATION, LLC (37)	2233)

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
MORTON UNIT #3	30-025-35422	P-32-14S-35E	800 FSL 660 FEL	50	NA	SALES LINE

Gathering System and Pipeline Notification

*Pipeline is already in place and connected.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Stakeholder Gas Services</u> system at that time. Based on current information, it is <u>Mammoth Exploration, LLC's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines