

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

MAR 23 2018

WELL API NO.
30-025-44338

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Python 36 State Com

8. Well Number 702H

9. OGRID Number

7377

10. Pool name or Wildcat

WC-025 G-09 S253309A; Upper WC

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

EOG Resources, Inc.

3. Address of Operator

P.O. Box 2267 Midland, TX 79702

4. Well Location

Unit Letter M : 310 feet from the South line and 736 feet from the West line
Section 36 Township 24S Range 32E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3557' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/12/18 Spud 17-1/2" hole.

2/13/18 Ran 13-3/8", 54.5#, J55 STC set at 1108'.

Cement lead w/ 870 sx Class C, 13.5 ppg, 1.76 CFS yield;

tail w/ 310 sx Class C, 14.8 ppg, 1.35 CFS yield.

Circulated 175 bbls cement to surface. Tested casing to 1500 psi fro 30 minutes.

WOC 4 hrs. Released surface rig.

Spud Date: 2/12/18

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Stan Wagner

TITLE

Regulatory Analyst

DATE

2/16/2018

Type or print name

Stan Wagner

E-mail address:

Petroleum Engineer

PHONE:

432-686-3689

For State Use Only

APPROVED BY:

TITLE

DATE

Conditions of Approval (if any):