District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Date:3/29/18	GAS CAPTURE PLAN
X Original ☐ Amended - Reason for Amendment:	Operator & OGRID No.: Special Energy Corporation 138008

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

 went by that will be reduced at the production racing are blown in the table core.								
Well Name	API	Well Location	Footages	Expected	Flared or	Comments		
		(ULSTR)		MCF/D	Vented			
Coronado State	30-025-	E-28-11S-38E	2485 FNL	100	Flared	Waiting	on	
1-H			400 FWL			Pipeline Build		

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Stakeholder Midstream and will be connected to Stakeholder Midstream and will be connected to Stakeholder Midstream and will be connected to Stakeholder Midstream a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Special Energy Corporation and Stakeholder Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Stakeholder Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Stakeholder Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Stakeholder Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Stakeholder Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Stakeholder Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Stakeholder Midstream</u> system at that time. Based on current information, it is <u>Special Energy Corporation's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines