OCD Hobbsos Soco

Form 3160 -3 (March 2012)

FORM APPROVED OMB No. 1004-0137 Expires October 31, 2014

UNITED STATES 5. Lease Serial No. DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT If Indian. Allotee or Tribe Name APPLICATION FOR PERMIT TO DRILL OR REENTER 7. If Unit or CA Agreement, Name and No DRILL REENTER la. Type of work: \(\frac{\partial}{8}\). Lease Name and Well No. Oil Well ✓ Single Zone Gas Well Multiple Zone DÒMINATOR 25 FEDERAL 1021 Type of Well: 9. APÌ Well-No. Name of Operator COG OPERATING LLC 3b. Phone No. (include area code) 3a. Address 10. Field and Pool, or Explorate 600 West Illinois Ave Midland TX 79701 (432)683-7443 WILDCAT / BONE SPRING 11, Sec., T. R. M. or Blk, and Survey or Area Location of Well (Report location clearly and in accordance with any State requirements.*) . At surface SESE / 310 FSL / 690 FEL / LAT 32.095115 / LONG -103.519755 SEC 25 / T25S / R33E / NMP At proposed prod. zone NENE / 200 FNL / 990 FEL / LAT 32.108213 / LONG -103.520721-13. State 12. County or Parish 14. Distance in miles and direction from nearest town or post office* NM 19 miles LEA Distance from proposed* 16. No. of acres in lease 17. Spacing Unit dedicated to this well 15. location to nearest 200 feet 280 property or lease line, ft. (Also to nearest drig. unit line, if any) 19 Proposed Depth 20. BLM/BIA Bond No. on file 18. Distance from proposed location* to nearest well, drilling, completed, 351 feet FED: NMB000215 applied for, on this lease, ft. 9640 feet / 14377 feet 22. Approximate date work will start 23. Estimated duration Elevations (Show whether DF, KDB, RT, GL, etc.) 3323 feet 03/01/2018/ 30 days 24. Attachments The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form: Bond to cover the operations unless covered by an existing bond on file (see 1. Well plat certified by a registered surveyor Item 20 above). 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the Operator certification SUPO must be filed with the appropriate Forest Service Office). Such other site specific information and/or plans as may be required by the BLM Date 25. Signature Name (Printed/Typed) Mayte Reyes / Ph: (575)748-6945 (Electronic-Submission) 12/05/2017 Title Regulatory Analyst Approved by (Signature) Name (Printed/Typed) Date (Electronic Submissión) Cody Layton / Ph: (575)234-5959 04/09/2018 Office Title Supervisor Multiple Resources CARLSBAD Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. (Continued on page 2) (Instructions on page 2) KX/20118

proval Date: 04/09/2018

ŗ

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new-reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2:48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396, 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts. ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant-to-civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to allow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

(Continued on page 3)

(Form 3160-3, page 2)

Additional Operator Remarks

Location of Well

1. SHL: SESE / 310 FSL / 690 FEL / TWSP: 25S / RANGE: 33E / SECTION: 25 / LAT: 32.095115 / LONG: -103.519755 (TVD: 0 feet) PPP: SESE / 330 FSL / 990 FEL / TWSP: 25S / RANGE: 33E / SECTION: 25 / LAT: 32.095168 / LONG: -103.520724 (TVD: 5500 feet, MD: 5500 feet) BHL: NENE / 200 FNL / 990 FEL / TWSP: 25S / RANGE: 33E / SECTION: 25 / LAT: 32.108213 / LONG: -103.520724 (TVD: 9640 feet) MD: 14377 feet)

BLM Point of Contact

Name: Sipra Dahal

Title: Legal Instruments Examiner

Phone: 5752345983 Email: sdahal@blm.gov

(Form 3160-3, page 3)

Approval Date: 04/09/2018

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.



(Form 3160-3, page 4)

Approval Date: 04/09/2018



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Application Data Report

APD ID: 10400025212

Submission Date: 12/05/2017

Highlighted data reflects the most

Operator Name: COG OPERATING LLC

Well Number: 102H

recent changes

Well Type: OIL WELL

Show Final Text

Well Work Type: Drill

Section 1 - General

APD ID:

10400025212

Well Name: DOMINATOR 25 FEDERAL

Tie to previous NOS?

Submission Date: 12/05/2017

BLM Office: CARLSBAD

User: Mayte Reves

Title: Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM114987

Lease Acres: 280

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: COG OPERATING LLC

Operator letter of designation:

Operator Info

Operator Organization Name: COG OPERATING LLC

Operator Address: 600 West Illinois Ave

Operator PO Box:

Zip: 79701

Operator City: Midland

State: TX

Operator Phone: (432)683-7443

Operator Internet Address: RODOM@CONCHO.COM

Section 2 - Well Information

Well in Master Development Plan? NO

Mater Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: WILDCAT

Pool Name: BONE SPRING

Is the proposed well in an area containing other mineral resources? USEABLE WATER,OIL

Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

Describe other minerals:

Is the proposed well in a Helium production area? N Use Existing Well Pad? NO

New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name: **DOMINATOR 25 FEDERAL** Number: 102H, 301H, 401H, 501H, 601H, 602H, 701H AND

702H

Well Class: HORIZONTAL

Number of Legs:

Well Work Type: Drill Well Type: OIL WELL

Describe Well Type:

Well sub-Type: EXPLORATORY (WILDCAT)

Describe sub-type:

Distance to town: 19 Miles

Distance to nearest well: 351 FT

Distance to lease line: 200 FT

Reservoir well spacing assigned acres Measurement: 160 Acres

Well plat:

COG_Dominator_102H_C102_20171204115603.pdf

Well work start Date: 03/01/2018

Duration: 30 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88


Survey number:

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL	310	FSL	690	FEL	25S	33E	25	Aliquot SESE	32.09511 5	103.5197	LEA	MEXI		F	NMNM 114987	332 3	0	0
#1										55		со	СО					
KOP Leg #1	310	FSL	690	FEL	25S	33E	25	Aliquot SESE	32.09511 5	- 103.5197 55	LEA	MEXI CO	MEXI CO	F		332 3	0	0
PPP Leg #1	330	FSL	990	FEL	25\$	33E	25	Aliquot SESE	32.09516 8	- 103.5207 24	LEA	NEW MEXI CO	• • • • •	F	NMNM 114987	- 217 7	550 0	550 0

Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
EXIT Leg #1	330	FNL	990	FEL	258	33E	25	Aliquot NENE	32.10785 5	- 103.5207 21	LEA	MEXI	NEW MEXI CO	F	NMNM 114987	- 629 7	143 00	962 0
BHL Leg #1	200	FNL	990	FEL	258	33E	25	Aliquot NENE	32.10821 3	- 103.5207 21	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 114987	- 631 7	143 77	964 0





U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

04/10/2018

APD ID: 10400025212

Submission Date: 12/05/2017

Highlighted data reflects the most

recent changes

Operator Name: COG OPERATING LLC

Well Number: 102H

Show Final Text

Well Name: DOMINATOR 25 FEDERAL Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing
1	UNKNOWN	3323	0	0	Littlologies	NONE	No
2	RUSTLER	2150	1173	1173		NONE	No
3	TOP SALT	1749	1574	1574	SALT	NONE	No
4	BASE OF SALT	-1811	5134	5134	ANHYDRITE	NONE	No
5	LAMAR	-1929	5252	5252	LIMESTONE	NONE	No
6	BELL CANYON	-1971	5294	5294	<u> </u>	NONE	No .
7	CHERRY CANYON	-2970	6293	6293		NATURAL GAS,OIL	No
8	BRUSHY CANYON	-4550	7873	7873		NATURAL GAS,OIL	No
9	BONE SPRING LIME	-6016	9339	9339	SANDSTONE	NATURAL GAS,OIL	No
10	UPPER AVALON SHALE	-6090	9413	9413	SHALE	NATURAL GAS,OIL	No
11		-6701	10024	10024		NATURAL GAS,OIL	No
12		-6851	10174	10174		NATURAL GAS,OIL	Yes
13	BONE SPRING 1ST	-7048	10371	10371		NATURAL GAS,OIL	No

Section 2 - Blowout Prevention

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

Pressure Rating (PSI): 2M

Rating Depth: 5280

Equipment: Annular, Blind Ram, Pipe Ram. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP to the choke manifold. See attached for specs and hydrostatic test chart.

Testing Procedure: BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested. Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

Choke Diagram Attachment:

COG_Dominator_102H_2M_Choke_20171204120710.pdf

BOP Diagram Attachment:

COG_Dominator_102H_2M_BOP_20171204120715.pdf

COG Dominator 102H FlexHose 20171204120722.pdf

Pressure Rating (PSI): 3M

Rating Depth: 9640

Equipment: Annular, Blind Ram, Pipe Ram. Accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold.

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP to the choke manifold. See attached for specs and hydrostatic test chart.

Testing Procedure: BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested. Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

Choke Diagram Attachment:

COG_Dominator_102H_3M_Choke_20171204120626.pdf

BOP Diagram Attachment:

COG_Dominator_102H_2M_BOP_20171204120632.pdf

COG_Dominator_102H_FlexHose_20171204120640.pdf

Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1200	0	1200	-8653	-9678	1200	J-55	54.5	STC	2.06	1.15	DRY	7.86	DRY	7.86
2	INTERMED IATE	12.2 5	9.625	NEW	API	Y	0	5280	0	5280	-8653	- 20153	5280	L-80	40	LTC	1.11	1.55	DRY	5.73	DRY	5.73
3	PRODUCTI ON	8.75	5.5	NEW	API	N	0	14377	0	14377	-8653	- 21064	14377	P- 110	17	LTC	1.6	2.88	DRY	2.72	DRY	2.72

Casing Attachments

Casing ID: 1

String Type:SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

 $COG_Dominator_102H_Casing_Rpt_20171204120843.pdf$

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

Casing Attachments

Casing ID: 2

String Type: INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

COG_Dominator_102H_Casing_Rpt_20171204120851.pdf

Casing Design Assumptions and Worksheet(s):

COG_Dominator_102H_Casing_Rpt_20171204120859.pdf

Casing ID: 3

String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

COG Dominator 102H Casing Rpt 20171204120905.pdf

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1200	530	1.75	13.5	927	50	Lead: Class C	4% Gel + 1% CaCl2
SURFACE	Tail		0	1200	250	1.34	14.8	335	50	Tail: Class C	2% CaCl2
INTERMEDIATE	Lead		0	5280	1010	2	12.7	2020	50	Lead: 35:65:6 C Blend	As needed
INTERMEDIATE	Tail		0	5280	250	1.34	14.8	335	50	Tail: Class C	2% CaCl
PRODUCTION	Lead		0	1437 7	610	2.5	11.9	1525	25	Lead: 50:50:10 H Blend	As needed

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

String Type	Lead/Tail	Stage Tool Depth	Тор МD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
PRODUCTION	Tail		0	1437 7	1330	1.24	14.4	1649	25	Tail: 50:50:2 Class H Blend	As needed

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	Hd	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
5280	1437 7	OTHER : Cut Brine	8.6	9.3					_		Cut Brine
0	1200	OTHER : FW Gel	8.6	8.8							FW Gel
1200	5280	OTHER : Saturated Brine	10	10.1							Saturated Brine

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

None planned

List of open and cased hole logs run in the well:

CNL,GR

Coring operation description for the well:

None planned

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 4665

Anticipated Surface Pressure: 2544.19

Anticipated Bottom Hole Temperature(F): 155

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

COG_Dominator_102H_H2S_Schem_20171204121312.pdf COG_Dominator_102H_H2S_SUP_20171204121319.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

COG_Dominator_102H_AC_Rpt_20171204121339.pdf COG_Dominator_102H_Direct_Rpt_20171204121346.pdf

Other proposed operations facets description:


Drilling Program Attached


Other proposed operations facets attachment:


COG_Dominator_102H_Drill_Rpt_20171204121355.pdf

Other Variance attachment:












CLOSED LOOP)




3,000 psi BOP Schematic




5,000 psi BOP Schematic





2,000 psi BOP Schematic





Midwest Hose & Specialty, Inc.

Customer: LATSHAW DRILLING Sales Order # 242739	Customer P.O.# RIG#44 Date Assembled: 2/9/2015	
Sales Order # 242739		
	Date Assembled: 2/9/2015	
Speci		
	fications	
Hose Assembly Type: Choke & Kill		
Assembly Serial # 292614-1	Hose Lot # and Date Code	10900-08/13
Hose Working Pressure (psi) 10000	Test Pressure (psi)	15000
Ve hereby certify that the above material supplied foothe requirements of the purchase order and curren upplier: Aidwest Hose & Specialty, Inc. 312 S I-35 Service Rd Oklahoma City, OK 73129		to be true according
omments:		
Approved By	Date	
Hama Alama	2/10/20	115



Midwest Hose & Specialty, Inc.

	Certifica	te of Conformity	
Customer: LATSHAW D	RILLING	Customer P.O.# RIG#44	
Sales Order # 242739		Date Assembled: 2/9/2015	
	Spe	ecifications	
Hose Assembly Type:	Choke & Kill		
Assembly Serial #	292614-2	Hose Lot # and Date Code	11794-10/14
,			

We hereby certify that the above material supplied for the referenced purchase order to be true according to the requirements of the purchase order and current industry standards.

Supplier:

Midwest Hose & Specialty, Inc.

3312 S I-35 Service Rd


Oklahoma City, OK 73129

Comments:

Approved By	Date
Fran Alaura	2/10/2015

Hole Size	Ca	sing	Csg. Size	Weight	Grade	Conn	SF	SF Burst	SF
noie Size	From	То	Csg. Size	(lbs)	Grade	Comm.	Collapse	or burst	Tension
17.5"	0	1200	13.375"	54.5	J55	STC	2.06	1,15	7.86
12.25"	0	4000	9.625"	40	J55	LTC	1.22	1.07	3.25
12.25"	4000	5280	9.625"	40	L80	LTC	1.11	1.55	5.73
8.75"	0	14,377	5.5"	17	P110	LTC	1.60	2.88	2.72
			ВІ	LM Minimun	n Safety	Factor	1.125	1	1.6 Dry 1.8 Wet

Intermediate casing will be kept at least 1/3 full while running casing to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface. All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h



COG Operating LLC, Columbus Federal Com 21H

Casing Program

Hole	Casing	g Interval	Csg. Size	Weight	Grade	Conn.	SF	SF	SF
Size	From	To		(lbs)			Col	Burst	Tension
13.5"	0'	1025'	10 3/4"	45.5	L80	STC	5.14	.86	14.7
9 7/8"	0'	11,500'	7 5/8"	29.7	HCP110	BTC	1.125	1.27	2.74
6 3/4"	0'	22,397'	5.5"	23	P110	Ultra SF	1.95	1.95	2.5
				BLM M	inimum Sa	fety Factor	1.125	1.125	1.6 Dry
						-			1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

- Burst SF on Surf is 0.86 > 0.7.
- 5.5" Ultra SF connection OD = 5.65".

COG Operating LLC, Columbus Federal Com 21H

Casing Program

Hole	Casing	g Interval	Csg. Size	Weight	Grade	Conn.	SF	SF	SF
Size	From	To		(lbs)			Col	Burst	Tension
13.5"	0'	1025'	10 ¾"	45.5	L80	STC	5.14	.86	14.7
9 7/8"	0'	11,500'	7 5/8"	29.7	HCP110	BTC	1.125	1.27	2.74
6 3/4"	0'	22,397'	5.5"	23	P110	Ultra SF	1.95	1.95	2.5
				BLM M	inimum Sa	fety Factor	1.125	1.125	1.6 Dry
						-			1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

- Burst SF on Surf is 0.86 > 0.7.
- 5.5" Ultra SF connection OD = 5.65".

COG Operating LLC, Columbus Federal Com 21H

Casing Program

Hole	Casing	g Interval	Csg. Size	Weight	Grade	Conn.	SF	SF	SF
Size	From	To		(lbs)			Col	Burst	Tension
13.5"	0'	1025'	10 3/4"	45.5	L80	STC	5.14	.86	14.7
9 7/8"	0,	11,500'	7 5/8"	29.7	HCP110	BTC	1.125	1.27	2.74
6 3/4"	0'	22,397'	5.5"	23	P110	Ultra SF	1.95	1.95	2.5
				BLM M	inimum Sa	fety Factor	1.125	1.125	1.6 Dry
	•					-			1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

- Burst SF on Surf is 0.86 > 0.7.
- 5.5" Ultra SF connection OD = 5.65".

Hole Size	Ca	asing	Com Sino	Weight	Grade	Conn	SF	SF Burst	SF
HOIE SIZE	From	То	Csg. Size	(lbs)	Grade	Conn.	Collapse	or burst	Tension
17.5"	0	1200	13,375"	54.5	J55	STC	2.06	1.15	7.86
12.25"	0	4000	9.625"	40	J55 -	LTC	1.22	1.07	3.25
12.25"	4000	5280	9.625"	40	L80	· LTC	1.11	1.55	5.73
8.75"	0.	14,377	.5.5"	17	P110	LTC	1.60	2.88	2.72
		· · · · · · · · · · · · · · · · · · ·	BLM	Minimun	n Safety	Factor	1.125	1	1.6 Dry 1.8 Wet

Intermediate casing will be kept at least 1/3 full while running casing to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface.

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h.

Hole Size	Ca	sing	Csg. Size	Weight	Weight Grade		SF	SF Burst	SF
Hole Size	From	То	Csg. Size	(lbs)			Collapse	or buist	Tension
17.5"	0	1200	13.375"	54.5	J55	STC	2.06	1.15	7.86
12.25"	0	4000	9.625"	40	J55	LTC	1.22	1.07	3.25
12.25"	4000	5280	9.625"	40	L80	LTC	1.11	1.55	5.73
8.75"	0	14,377	5.5"	17	P110	LTC	1.60	2.88	2.72
			В	BLM Minimun	n Safety	/ Factor	1.125	1	1.6 Dry 1.8 Wet

Intermediate casing will be kept at least 1/3 full while running casing to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface. All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Hole Size	Ca	asing	Csg. Size	Weight	Grade	Conn	SF	SF Burst	SF
noie Size	From	To Csg. Size (lbs) Grade		Collapse		or burst	Tension		
17.5"	0	1200	13.375"	54.5	J55	STC	2.06	1.15	7.86
. 12.25"	0	4000	9.625"	40	J55	LTC	- 1.22	1.07	3.25
· 12.25"	4000	: 5280°	., 9.625 "	40	L80 <i>∂</i>	LTC	1.11	1.55	5.73
8.75"	0	14,377	5.5"	17	-P110	LTC	1.60	2.88	2.72
1	igen (*) Ger	1	BLM	Minimun	n Safety	Factor	1.125		1.6 Dry 1.8 Wet

Intermediate casing will be kept at least 1/3 full while running casing to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface.

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

· ·	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Υ
Does casing meet API specifications? If no, attach casing specification sheet.	Υ
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Υ
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary?	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
is 2 string set 100 to 600 below the base of sait?	
ls well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program

Casing	# Sks	Wt. lb/	YId ft3/ sack	H₂0 gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	530	13.5	1.75	9	12	Lead: Class C + 4% Gel + 1% CaCl2
Suri.	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl2
Inter.	1010	12.7	2.0	9.6	16	Lead: 35:65:6 C Blend
iriter.	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl
5.5 Prod	610	11.9	2.5	19	72	Lead: 50:50:10 H Blend
5.5 Prod F	1330	14.4	1.24	5.7	19	Tail: 50:50:2 Class H Blend

Volumes Subject to Observed Hole Conditions and/or Fluid Caliper Results Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Casing String	тос	% Excess
Surface	0'	50%
1 st Intermediate	0'	50%
Production	3,500'	25% OH in Lateral (KOP to EOL) – 40% OH in Vertical

4. Pressure Control Equipment

N A variance is requested for the use of a diverter on the surface casing. See attached for schematic.

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Ту	pe	x	Tested to:
			Ann	ular	Х	2000 psi
		2M	Blind	Ram		
12-1/4"	13-5/8"		Pipe Ram			2M
			Double Ram			
			Other*			
,			Ann	ular	×	50% testing pressure
8-3/4"	13-5/8"	3M	Blind Ram		Х	3М
,			Pipe Ram		Х	
		•	Double Ram			
		·	Other*			

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

	Formation integrity test will be performed per Onshore Order #2.
×	On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Υ	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
	N Are anchors required by manufacturer?
Ν	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

5. Mud Program

	Depth	Time	Weight	Viscosity	Water Loss	
From	То	Туре	(ppg)	viscosity	water Loss	
0	Surf. Shoe	FW Gel	8.6 - 8.8	28-34	N/C	
Surf csg	9-5/8" Int shoe	Saturated Brine	10 - 10.1	28-34	N/C	
9-5/8" Int shoe	Lateral TD	Cut Brine	8.6 - 9.3	28-34	N/C	

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
	<u>. </u>

6. Logging and Testing Procedures

Logging, Coring and Testing.		
Y	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.	
Y	No Logs are planned based on well control or offset log information.	
N	Drill stem test? If yes, explain.	
N	Coring? If yes, explain.	

Add	ditional logs planned	Interval
N	Resistivity	Pilot Hole TD to ICP
N	Density	Pilot Hole TD to ICP
Y	CBL	Production casing (If cement not circulated to surface)
Υ	Mud log	Intermediate shoe to TD
N	PEX	

COG Operating, LLC - Dominator 25 Federal #102H

7. Drilling Conditions

Condition	Specify what type and where?			
BH Pressure at deepest TVD	4665 psi at 9640' TVD			
Abnormal Temperature	NO 155 Deg. F.			

No abnormal pressure or temperature conditions are anticipated. Sufficient mud materials to maintain mud properties and weight increase requirements will be kept on location at all times.

Sufficient supplies of Paper/LCM for periodic sweeps to control seepage and losses will be maintained on location.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

-		
N	H2S is present	·
Y	H2S Plan attached	,

8. Other Facets of Operation

Υ	Is it a walking operation?
N	ls casing pre-set?

×	H2S Plan.
×	BOP & Choke Schematics.
×	Directional Plan



SUPO Data Report
04/10/2018

APD ID: 10400025212

Operator Name: COG OPERATING LLC

Well Name: DOMINATOR 25 FEDERAL

Well Type: OIL WELL

Submission Date: 12/05/2017

Well Number: 102H

Well Work Type: Drill

Highlighted data reflects the most

recent changes

Show Final Text

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

COG_Dominator_Existing_Rd_20171121094216.pdf

Existing Road Purpose: ACCESS

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

COG_Dominator_102H_Roads_20171204121414.pdf

New road type: TWO-TRACK

Length: 112773

Feet

Width (ft.): 30

Max slope (%): 33

Max grade (%): 1

Army Corp of Engineers (ACOE) permit required? NO

ACOE Permit Number(s):

New road travel width: 14

New road access erosion control: Water will be diverted where necessary to avoid ponding, prevent erosion, maintain good drainage, and to be consistent with local drainage patterns.

New road access plan or profile prepared? NO

New road access plan attachment:

Access road engineering design? NO

Access road engineering design attachment:

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

Access surfacing type: OTHER

Access topsoil source: ONSITE

Access surfacing type description: Caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: Blading

Access other construction information: No turnouts are planned. Re routing access road around proposed well location.

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: OTHER

Drainage Control comments: None necessary.

Road Drainage Control Structures (DCS) description: None needed.

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

COG_Dominator_102H_1Mile_Data_20171204121441.pdf

Existing Wells description:

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: Production will be sent to the Dominator 25 Federal CTB 4 facility. A surface flow line of approximately 60.6' of 3.5" steel pipe carrying oil, gas and water under a maximum pressure of 125 psi will follow the road to the facility at the Dominator 25 Federal CTB 4 location. We plan to install a 4" surface polyethylene pipe transporting Gas Lift Gas from the Dominator 25 Federal CTB 4 to the multiple well pad that includes the Dominator 25 Federal Com #102H, #301H, #401H, #501H, #602H, 701H and #702H wells. The surface Gas Lift Gas pipe of approximately 60.6' under a maximum pressure of 125 psi will be installed no farther than 10 feet from the edge of the road.

Production Facilities map:

COG_Dominator_CTB_4_20171201102558.pdf

COG_Dominator_102H_Flowlines_20171204121454.pdf

COG_Dominator_102H_ProdFacil_20171204121504.pdf

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

Section 5 - Location and Types of Water Supply

Water Source Table

Water source use type: INTERMEDIATE/PRODUCTION CASING

Water source type: OTHER

Describe type: Brine Water.

Source latitude:

Source longitude:

Source datum:

Water source permit type: PRIVATE CONTRACT, PRIVATE

CONTRACT

Source land ownership: COMMERCIAL

Water source transport method: TRUCKING, TRUCKING

Source transportation land ownership: COMMERCIAL

Water source volume (barrels): 15000 Source volume (acre-feet): 1.9333965

Source volume (gal): 630000

Water source use type: STIMULATION, SURFACE CASING

Water source type: OTHER

Describe type: Fresh Water.

Source latitude:

Source longitude:

Source datum:

Water source permit type: PRIVATE CONTRACT, PRIVATE

CONTRACT

Source land ownership: PRIVATE

Water source transport method: PIPELINE, PIPELINE

Source transportation land ownership: PRIVATE

Water source volume (barrels): 225000 Source volume (acre-feet): 29.000946

Source volume (gal): 9450000

Water source and transportation map:

COG_Dominator_Frac_Pond_20171127081721.pdf

COG_Dominator_102H_BrineH2O_20171204121656.pdf

COG_Dominator_102H_FreshH2O_20171204121709.pdf

Water source comments: Fresh water will be obtained from the C-01285 Dinwiddle Cattle Co Water Well located in Section 5, T26S, R36E. The water will be stored in the proposed Dominator 25 Federal Frac Pond located in section 25, T25S. R33E. Brine water will be obtained from the Malaga II Brine station located in Section 12. T23S. R28E.

New water well? NO

New Water Well Info

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aguifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Construction Materials description: Caliche will be obtained from the actual well site if available. If not available onsite, caliche will be purchased from approved BLM federal pit located in Section 23. T25S. R33E.

Construction Materials source location attachment:

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Drilling fluids and produced oil and water during drilling and completion operations

Amount of waste: 6000

barrels

Waste disposal frequency: One Time Only

Safe containment description: All drilling waste will be stored safely and disposed of properly

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL

Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Trucked to an approved disposal facility

Waste type: SEWAGE

Waste content description: Human waste and gray water

Amount of waste: 250

gallons

Waste disposal frequency: Weekly

Safe containment description: Waste will be properly contained and disposed of properly at a state approved disposal

facility

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

Safe containment attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Trucked to an approved disposal facility

Waste type: GARBAGE

Waste content description: Garbage and trash produced during drilling and completion operations

Amount of waste: 125

pounds

Waste disposal frequency: Weekly

Safe containment description: Garbage and trash produced during drilling and completion operations will be collected in a

trash container and disposed of properly at a state approved disposal facility

Safe containment attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Trucked to an approved disposal facility

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit?

Reserve pit length (ft.)

Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? YES

Description of cuttings location Roll off cuttings containers on tracks

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Well Name: DOMINATOR 25 FEDERAL Well Number: 102H

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: YES

Ancillary Facilities attachment:

COG_Dominator_102H_GCP_20171204121728.pdf

Comments: GCP Attached

Section 9 - Well Site Layout

Well Site Layout Diagram:

COG_Dominator_CTB_4 20171201102619.pdf

COG_Dominator_102H_Flowlines_20171204121626.pdf

COG Dominator 102H ProdFacil 20171204121633.pdf

Comments: Production will be sent to the Dominator 25 Federal CTB 4 facility. A surface flow line of approximately 60.6' of 3.5" steel pipe carrying oil, gas and water under a maximum pressure of 125 psi will follow the road to the facility at the Dominator 25 Federal CTB 4 location. We plan to install a 4" surface polyethylene pipe transporting Gas Lift Gas from the Dominator 25 Federal CTB 4 to the multiple well pad that includes the Dominator 25 Federal Com #102H, #301H, #401H, #501H, #601H, #602H, 701H and #702H wells. The surface Gas Lift Gas pipe of approximately 60.6' under a maximum pressure of 125 psi will be installed no farther than 10 feet from the edge of the road.

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: DOMINATOR 25 FEDERAL

Multiple Well Pad Number: 102H, 301H, 401H, 501H, 601H, 602H,

701H AND 702H

Recontouring attachment:

Drainage/Erosion control construction: Due to the relatively flat topography of this well pad, 460' of waddles would be placed on the north side of the well pad to avoid surface erosion to reduce sediment impacts to fragile/sensitive soils. Drainage/Erosion control reclamation: Reclaim the east side 80'.

Well pad proposed disturbance

(acres): 3.67

Road proposed disturbance (acres):

3.62

Powerline proposed disturbance

(acres): 0

Pipeline proposed disturbance

(acres): 0.01

Other proposed disturbance (acres):

22.96

Total proposed disturbance: 30.26

Well pad interim reclamation (acres):

(acres): 2.94

Road interim reclamation (acres): 3.62 Road long term disturbance (acres):

Powerline interim reclamation (acres):

Pipeline interim reclamation (acres):

Other interim reclamation (acres): 0

Total interim reclamation: 4.36

Well pad long term disturbance

Powerline long term disturbance (acres): 0

Pipeline long term disturbance

(acres): 0.01

Other long term disturbance (acres):

Total long term disturbance: 29.53

Reconstruction method: New construction of pad.

Operator Name: COG OPERATING LLC
Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

Topsoil redistribution: East.

Soil treatment: None

Existing Vegetation at the well pad: Shinnery Oak/Mesquite grassland

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: Shinnery Oak/Mesquite grassland

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline: Shinnery Oak/Mesquite grassland

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances: N/A

Existing Vegetation Community at other disturbances attachment:

Non native seed used? NO

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? NO

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? NO

Seed harvest description:

Seed harvest description attachment:

Seed Management

Seed Table

Seed type:

Seed source:

Seed name:

Source name:

Source address:

Source phone:

Seed cultivar:

Seed use location:

PLS pounds per acre:

Proposed seeding season:

Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

Seed Summary

Seed Type

Pounds/Acre

Total pounds/Acre:

Seed reclamation attachment:

Operator Contact/Responsible Official Contact Info

First Name: Rand

Last Name: French

Phone: (432)254-5556

Email: rfrench@concho.com

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? NO

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Weed treatment plan description: N/A

Weed treatment plan attachment:

Monitoring plan description: N/A

Monitoring plan attachment:

Success standards: N/A

Pit closure description: N/A

Pit closure attachment:

COG_Dominator_102H_Closed_Loop_20171204121828.pdf

Section 11 - Surface Ownership

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

Operator Name: COG OPERATING LLC
Well Name: DOMINATOR 25 FEDERAL

Well Number: 102H

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Section 12 - Other Information

Right of Way needed? NO

Use APD as ROW?

ROW Type(s):

ROW Applications

SUPO Additional Information:

Use a previously conducted onsite? YES

Previous Onsite information: Onsite completed on 10/5/2017 by Rand French (COG); Gerald Herrera (COG) and Jeff Robertson (BLM).

Other SUPO Attachment

COG_Dominator_102H_Certif_20171204121931.pdf



PWD Data Report 04/10/2018

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

PWD disturbance (acres):

Section 3 - Unlined Pits

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:	
PWD surface owner:	PWD disturbance (acres):
Unlined pit PWD on or off channel:	(,
Unlined pit PWD discharge volume (bbl/day):	
Unlined pit specifications:	
Precipitated solids disposal:	
Decribe precipitated solids disposal:	
Precipitated solids disposal permit:	
Unlined pit precipitated solids disposal schedule:	
Unlined pit precipitated solids disposal schedule attachment:	
Unlined pit reclamation description:	
Unlined pit reclamation attachment:	
Unlined pit Monitor description:	
Unlined pit Monitor attachment:	
Do you propose to put the produced water to beneficial use?	
Beneficial use user confirmation:	
Estimated depth of the shallowest aquifer (feet):	
Does the produced water have an annual average Total Disso that of the existing water to be protected?	Ived Solids (TDS) concentration equal to or less than
TDS lab results:	
Geologic and hydrologic evidence:	
State authorization:	
Unlined Produced Water Pit Estimated percolation:	
Unlined pit: do you have a reclamation bond for the pit?	
Is the reclamation bond a rider under the BLM bond?	
Unlined pit bond number:	
Unlined pit bond amount:	
Additional bond information attachment:	
Section 4 - Injection	
Would you like to utilize Injection PWD options? NO	
Produced Water Disposal (PWD) Location:	
PWD surface owner:	PWD disturbance (acres):

Injection well type: Injection well name: Injection well number: Assigned injection well API number? Injection well API number: Injection well new surface disturbance (acres): Minerals protection information: Mineral protection attachment: **Underground Injection Control (UIC) Permit? UIC Permit attachment:** Section 5 - Surface Discharge Would you like to utilize Surface Discharge PWD options? NO **Produced Water Disposal (PWD) Location:** PWD surface owner: PWD disturbance (acres): Surface discharge PWD discharge volume (bbl/day): **Surface Discharge NPDES Permit?** Surface Discharge NPDES Permit attachment: Surface Discharge site facilities information: Surface discharge site facilities map: Section 6 - Other Would you like to utilize Other PWD options? NO Produced Water Disposal (PWD) Location: PWD surface owner: PWD disturbance (acres): Other PWD discharge volume (bbl/day): Other PWD type description: Other PWD type attachment: Have other regulatory requirements been met? Other regulatory requirements attachment:

Bond Information

Federal/Indian APD: FED

BLM Bond number: NMB000215

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment:



Operator Certification Data Report 04/10/2018

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Mayte Reyes

Signed on: 12/04/2017

Title: Regulatory Analyst

Street Address: 2208 W Main Street

City: Artesia

State: NM

Zip: 88210

Phone: (575)748-6945

Email address: Mreyes1@concho.com

Field Representative

Representative Name: Rand French

Street Address: 2208 West Main Street

City: Artesia

State: NM

Zip: 88210

Phone: (575)748-6940

Email address: rfrench@concho.com

COG Operating, LLC - Dominator 25 Federal #102H

1. Geologic Formations

TVD of target	9,640' EOL	Pilot hole depth	NA
MD at TD:	14,377'	Deepest expected fresh water:	142'

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*		
Quaternary Fill	Surface	Water			
Rustler	1173	Water			
Top of Salt	1574	Salt			
Base of Salt	5134	Salt			
Lamar	5252	Salt Water			
Bell Canyon	5294	Salt Water			
Cherry Canyon	6293	Oil/Gas			
Brushy Canyon	7873	Oil/Gas			
Bone Spring Lime	9339	Oil/Gas			
U. Avalon Shale	9413	Oil/Gas			
L. Avalon Shale	10024	Oil/Gas			
Basal Avalon	10174	Oil/Gas			
1st Bone Spring Sand	10371	Not Penatrated			
2nd Bone Spring Sand	0	Not Penatrated			
3rd Bone Spring Sand	0	Not Penatrated			

2. Casing Program

Hole Size	Casing		Con Sino W	Weight	Weight Grade	Co	SF	SE Burnet	SF
	From	То	Csg. Size	(lbs)	Grade	Conn.	Collapse	SF Burst	Tension
17.5"	0	1200	13.375"	54.5	J55	STC	2.06	1.15	7.86
12.25"	0	4000	9.625"	40	J55	LTC	1.22	1.07	3.25
12.25"	4000	5280	9.625"	40	L80	LTC	1.11	1.55	5.73
8.75"	0	14,377	5.5"	17	P110	LTC	1.60	2.88	2.72
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

Intermediate casing will be kept at least 1/3 full while running casing.to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface.

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h