

OCD Hobbs OCD

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM110840
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		6. If Indian Allottee or Tribe Name
2. Name of Operator EOG RESOURCES INCORPORATED (7377)		7. If Unit or CA Agreement Name and No.
3a. Address 1111 Bagby Sky Lobby2 Houston TX 77002		8. Lease Name and Well No. PHILLY 31 FED COM 702H (321381)
3b. Phone No. (include area code) (713)651-7000		9. API Well No. 30-025-44767
4. Location of Well (Report location clearly and in accordance with any State requirements*) At surface LOT 2 / 290 FSL / 630 FWL / LAT 32.00106 / LONG -103.5155072 At proposed prod. zone LOT 1 / 230 FNL / 750 FWL / LAT 32.0210231 / LONG -103.5151223		10. Field and Pool, or Exploratory RED HILLS / WC-025 S263327G (98097)
11. Sec., T. R. M. or Blk. and Survey or Area SEC 31 / T26S / R34E / NMP		12. County or Parish LEA
13. State NM		14. Distance in miles and direction from nearest town or post office* 27 miles
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 230 feet	16. No. of acres in lease 1335.19	17. Spacing Unit dedicated to this well 238.26
18. Distance from proposed location* to nearest well, drilling, completed, 420 feet applied for, on this lease, ft.	19. Proposed Depth 12693 feet / 19992 feet	20. BLM/BIA Bond No. on file FED: NM2308
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3366 feet	22. Approximate date work will start* 03/01/2018	23. Estimated duration 25 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM. |

25. Signature (Electronic Submission)	Name (Printed/Typed) Stan Wagner / Ph: (432)686-3689	Date 09/27/2017
Title Regulatory Specialist		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Cody Layton / Ph: (575)234-5959	Date 04/18/2018
Title Supervisor Multiple Resources		
Office CARLSBAD		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

GCP Rec 05/07/18

APPROVED WITH CONDITIONS
Approval Date: 04/18/2018

K2
04/10/18

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices; either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to allow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications.

Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Additional Operator Remarks

Location of Well

1. SHL: LOT 2 / 290 FSL / 630 FWL / TWSP: 26S / RANGE: 34E / SECTION: 31 / LAT: 32.00106 / LONG: -103.5155072 (TVD: 0 feet, MD: 0 feet)
PPP: LOT 2 / 330 FSL / 750 FWL / TWSP: 26S / RANGE: 34E / SECTION: 31 / LAT: 32.0011702 / LONG: -103.5151202 (TVD: 12649 feet, MD: 12763 feet)
BHL: LOT 1 / 230 FNL / 750 FWL / TWSP: 26S / RANGE: 34E / SECTION: 30 / LAT: 32.0210231 / LONG: -103.5151223 (TVD: 12693 feet, MD: 19992 feet)

BLM Point of Contact

Name: Katrina Ponder
Title: Geologist
Phone: 5752345969
Email: kponder@blm.gov

CONFIDENTIAL

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

CONFIDENTIAL



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Application Data Report

04/19/2018

APD ID: 10400022612

Submission Date: 09/27/2017

Highlighted data
reflects the most
recent changes

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

APD ID: 10400022612

Tie to previous NOS?

Submission Date: 09/27/2017

BLM Office: CARLSBAD

User: Stan Wagner

Title: Regulatory Specialist

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM110840

Lease Acres: 1335.19

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: EOG RESOURCES INCORPORATED

Operator letter of designation:

Operator Info

Operator Organization Name: EOG RESOURCES INCORPORATED

Operator Address: 1111 Bagby Sky Lobby2

Zip: 77002

Operator PO Box:

Operator City: Houston

State: TX

Operator Phone: (713)651-7000

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: PHILLY 31 FED COM

Well Number: 702H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: RED HILLS

Pool Name: WC-025 S263327G

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Describe other minerals:

Is the proposed well in a Helium production area? N

Use Existing Well Pad? NO

New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:

Number: 701H/702H

Well Class: HORIZONTAL

PHILLY 31 FED COM

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:

Distance to town: 27 Miles

Distance to nearest well: 420 FT

Distance to lease line: 230 FT

Reservoir well spacing assigned acres Measurement: 238.26 Acres

Well plat: Philly_31_Fed_Com_702H_signed_C_102_20170927152923.pdf

Well work start Date: 03/01/2018

Duration: 25 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD27

Vertical Datum: NAVD88

Survey number:

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL Leg #1	290	FSL	630	FWL	26S	34E	31	Lot 2	32.00106	- 103.5155 072	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 110840	336 6	0	0
KOP Leg #1	53	FSL	744	FWL	26S	34E	31	Lot 2	32.00040 79	- 103.5151 42	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 110840	- 883 5	122 05	122 01
PPP Leg #1	330	FSL	750	FWL	26S	34E	31	Lot 2	32.00117 02	- 103.5151 202	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 110840	- 928 3	127 63	126 49



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

04/19/2018

APD ID: 10400022612

Submission Date: 09/27/2017

Highlighted data
reflects the most
recent changes

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
1	PERMIAN	3366	0	0	ALLUVIUM	NONE	No
2	RUSTLER	2545	821	821	ANHYDRITE	NONE	No
3	TOP OF SALT	1940	1426	1426	SALT	NONE	No
4	BASE OF SALT	-232	3598	3598	SALT	NONE	No
5	LAMAR LS	-1996	5362	5362	LIMESTONE	NONE	No
6	BELL CANYON	-2022	5388	5388	SANDSTONE	NATURAL GAS,OIL	Yes
7	CHERRY CANYON	-3079	6445	6445	SANDSTONE	NATURAL GAS,OIL	Yes
8	BRUSHY CANYON	-4612	7978	7978	SANDSTONE	NATURAL GAS,OIL	Yes
9	BONE SPRING LIME	-6209	9575	9575	LIMESTONE	NONE	No
10	BONE SPRING 1ST	-7129	10495	10495	SANDSTONE	NATURAL GAS,OIL	Yes
11	BONE SPRING 2ND	-7684	11050	11050	SANDSTONE	NATURAL GAS,OIL	Yes
12	BONE SPRING 3RD	-8769	12135	12135	SANDSTONE	NATURAL GAS,OIL	Yes
13	WOLFCAMP	-9187	12553	12553	SHALE	NATURAL GAS,OIL	Yes

Section 2 - Blowout Prevention

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Pressure Rating (PSI): 10M

Rating Depth: 12693

Equipment: The minimum blowout preventer equipment (BOPE) shown in Exhibit #1 will consist of a single ram, mud cross and double ram-type (10,000 psi WP) preventer and an annular preventer (5000-psi WP). Both units will be hydraulically operated and the ram-type will be equipped with blind rams on bottom and drill pipe rams on top. All BOPE will be tested in accordance with Onshore Oil & Gas order No. 2.

Requesting Variance? YES

Variance request: Variance is requested to use a co-flex line between the BOP and choke manifold (instead of using a 4" OD steel line). Variance is requested to wave the centralizer requirements for the 7-5/8" FJ casing in the 8-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4" hole interval to maximize cement bond and zonal isolation. Centralizers will be placed in the 9-7/8" hole interval at least one every third joint. Variance is also requested to wave any centralizer requirements for the 5-1/2" FJ casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

Testing Procedure: Before drilling out of the surface casing, the ram-type BOP and accessory equipment will be tested to 10000/ 250 psig and the annular preventer to 5000/ 250 psig. The surface casing will be tested to 1500 psi for 30 minutes. Before drilling out of the intermediate casing, the ram-type BOP and accessory equipment will be tested to 10000/ 250 psig and the annular preventer to 5000/ 250 psig. The intermediate casing will be tested to 2000 psi for 30 minutes. Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A hydraulically operated choke will be installed prior to drilling out of the intermediate casing shoe.

Choke Diagram Attachment:

Philly_31_FC_702H_10_M_Choke_Manifold_20170925103522.pdf

Philly_31_FC_702H_Co_Flex_Hose_Certification_20170925103522.PDF

Philly_31_FC_702H_Co_Flex_Hose_Test_Chart_20170925103523.pdf

BOP Diagram Attachment:

Philly_31_FC_702H_10_M_BOP_Diagram_20170925103534.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	14.75	10.75	NEW	API	N	0	850	0	850	3366	2516	850	J-55	40.5	STC	1.125	1.25	BUOY	1.6	BUOY	1.6
2	INTERMEDIATE	9.875	7.625	NEW	API	Y	0	1000	0	1000	3366	2366	1000	HCP-110	29.7	LTC	1.125	1.25	BUOY	1.6	BUOY	1.6
3	PRODUCTION	6.75	5.5	NEW	API	Y	0	11100	0	11100	3366	-7734	11100	OTHER	20	OTHER - DW/C-ISM	1.125	1.25	BUOY	1.6	BUOY	1.6

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Philly_31_FC_702H_BLM_Plan_20170925103716.pdf

Casing ID: 2 **String Type:** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

See_previously_attached_Drill_Plan_20170925103739.pdf

Philly_31_FC_702H_7.625in_29.70_P_110_FlushMax_III_20170925103739.pdf

Philly_31_FC_702H_7.625in_29.7_P110EC_VAM_SLIJ_II_20170925103738.pdf

Casing Design Assumptions and Worksheet(s):

See_previously_attached_Drill_Plan_20170925103753.pdf

Casing ID: 3 **String Type:** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

See_previously_attached_Drill_Plan_20170925103657.pdf

Philly_31_FC_702H_5.500in_20.00_VST_P110EC_DWC_C_IS_MS_20170925103656.pdf

Philly_31_FC_702H_5.500in_20.00_VST_P110EC_VAM_SFC_20170925103657.pdf

Casing Design Assumptions and Worksheet(s):

See_previously_attached_Drill_Plan_20170925103807.pdf

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	850	325	1.73	13.5	562	25	Class C	Class C + 4.0% Bentonite + 0.6% CD-32 + 0.5% CaCl ₂ + 0.25 lb/sx Cello-Flake (TOC@Surface)
SURFACE	Tail		850	850	200	1.34	14.8	268	25	Class C	Class C + 0.6% FL-62 + 0.25 lb/sx Cello-Flake + 0.2% Sodium Metasilicate
INTERMEDIATE	Lead		0	1160 0	2250	1.38	14.8	3105	25	Class C	Class C + 5% Gypsum + 3% CaCl ₂ pumped via Bradenhead (TOC @ Surface)
INTERMEDIATE	Tail		1160 0	1160 0	550	1.2	14.4	660	25	Class H	50:50 Class H:Poz + 0.25% CPT20A + 0.40% CPT49 + 0.20% CPT35 + 0.80% CPT16A + 0.25% CPT503P pumped Conventionally
PRODUCTION	Lead		1110 0	1999 2	850	1.26	14.1	1071	25	Class H	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 (TOC @ 11,100')

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: (A) A Kelly cock will be kept in the drill string at all times. (B) A full opening drill pipe-stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times. (C) H₂S monitoring and detection equipment will be utilized from surface casing point to TD.

Describe the mud monitoring system utilized: An electronic pit volume totalizer (PVT) will be utilized on the circulating system to monitor pit volume, flow rate, pump pressure and stroke rate.

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
850	1160 0	SALT SATURATED	8.8	10							
1160 0	1269 3	OIL-BASED MUD	10	14							
0	850	WATER-BASED MUD	8.6	8.8							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Open-hole logs are not planned for this well.

List of open and cased hole logs run in the well:

DS

Coring operation description for the well:

None

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 7590

Anticipated Surface Pressure: 4797.54

Anticipated Bottom Hole Temperature(F): 181

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Philly_31_FC_702H_H2S_Plan_Summary_20170925104128.pdf

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Philly_31_Fed_Com_702H_Planning_Report_20170925104146.pdf

Philly_31_Fed_Com_702H_Wall_Plot_20170925104147.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:






Philly_31_FC_702H_Proposed_Wellbore_20170925104211.pdf

Philly_31_FC_702H_Rig_Layout_20170925104211.pdf

Philly_31_FC_702H_Wellhead_Cap_20170925104212.pdf

Philly_31_Fed_Com_702H_gas_capture_20170927160018.pdf

Other Variance attachment:



PROPRIETARY
THIS DRAWING AND THE IDEAS AND INFORMATION INCLUDED IN THIS
DRAWING ARE PROPRIETARY AND ARE NOT TO BE REPRODUCED,
DISTRIBUTED OR DISCLOSED IN ANY MANNER WITHOUT THE PRIOR
WRITTEN CONSENT OF A DULY AUTHORIZED OFFICER
OF HELMERICH & PAYNE INT'L DRILLING CO.

**ISSUED FOR
FABRICATION**
February-10-2014
DRAFTSMAN *MW*
ENGINEER *PLK*

STANDARD TOLERANCES			
FABRICATION DIMENSIONS			
1. FABRICATION DIMENSIONS	A-0" TO 3"	± 1/16"	
	B-3" TO 12"	± 1/8"	
	C-12" TO 36"	± 1/4"	
2. MACHINED DIMENSIONS	D-36" TO 48"	± 3/16"	
	E-48" TO 60"	± 1/4"	
	F-60" TO 72"	± 5/16"	
	G-72" TO 96"	± 3/8"	
	H-96" TO 120"	± 1/2"	
	I-120" TO 144"	± 5/8"	
	J-144" TO 168"	± 3/4"	
	K-168" TO 192"	± 7/8"	
	L-192" TO 216"	± 1"	
	M-216" TO 240"	± 1 1/8"	
	N-240" TO 264"	± 1 1/4"	
	O-264" TO 288"	± 1 1/2"	
	P-288" TO 312"	± 1 3/4"	
	Q-312" TO 336"	± 1 7/8"	
	R-336" TO 360"	± 2"	
	S-360" TO 384"	± 2 1/8"	
	T-384" TO 408"	± 2 1/4"	
	U-408" TO 432"	± 2 1/2"	
	V-432" TO 456"	± 2 3/4"	
	W-456" TO 480"	± 2 7/8"	
	X-480" TO 504"	± 3"	
	Y-504" TO 528"	± 3 1/8"	
	Z-528" TO 552"	± 3 1/4"	
	AA-552" TO 576"	± 3 1/2"	
	AB-576" TO 600"	± 3 3/4"	
	AC-600" TO 624"	± 3 7/8"	
	AD-624" TO 648"	± 4"	
	AE-648" TO 672"	± 4 1/8"	
	AF-672" TO 696"	± 4 1/4"	
	AG-696" TO 720"	± 4 1/2"	
	AH-720" TO 744"	± 4 3/4"	
	AI-744" TO 768"	± 4 7/8"	
	AJ-768" TO 792"	± 5"	
	AK-792" TO 816"	± 5 1/8"	
	AL-816" TO 840"	± 5 1/4"	
	AM-840" TO 864"	± 5 1/2"	
	AN-864" TO 888"	± 5 3/4"	
	AO-888" TO 912"	± 5 7/8"	
	AP-912" TO 936"	± 6"	
	AQ-936" TO 960"	± 6 1/8"	
	AR-960" TO 984"	± 6 1/4"	
	AS-984" TO 1008"	± 6 1/2"	
	AT-1008" TO 1032"	± 6 3/4"	
	AU-1032" TO 1056"	± 6 7/8"	
	AV-1056" TO 1080"	± 7"	
	AW-1080" TO 1104"	± 7 1/8"	
	AX-1104" TO 1128"	± 7 1/4"	
	AY-1128" TO 1152"	± 7 1/2"	
	AZ-1152" TO 1176"	± 7 3/4"	
	BA-1176" TO 1200"	± 7 7/8"	
	BB-1200" TO 1224"	± 8"	
	BC-1224" TO 1248"	± 8 1/8"	
	BD-1248" TO 1272"	± 8 1/4"	
	BE-1272" TO 1296"	± 8 1/2"	
	BF-1296" TO 1320"	± 8 3/4"	
	BG-1320" TO 1344"	± 8 7/8"	
	BH-1344" TO 1368"	± 9"	
	BI-1368" TO 1392"	± 9 1/8"	
	BJ-1392" TO 1416"	± 9 1/4"	
	BK-1416" TO 1440"	± 9 1/2"	
	BL-1440" TO 1464"	± 9 3/4"	
	BM-1464" TO 1488"	± 9 7/8"	
	BN-1488" TO 1512"	± 10"	
	BO-1512" TO 1536"	± 10 1/8"	
	BP-1536" TO 1560"	± 10 1/4"	
	BQ-1560" TO 1584"	± 10 1/2"	
	BR-1584" TO 1608"	± 10 3/4"	
	BS-1608" TO 1632"	± 10 7/8"	
	BT-1632" TO 1656"	± 11"	
	BU-1656" TO 1680"	± 11 1/8"	
	BV-1680" TO 1704"	± 11 1/4"	
	BW-1704" TO 1728"	± 11 1/2"	
	BX-1728" TO 1752"	± 11 3/4"	
	BY-1752" TO 1776"	± 11 7/8"	
	BZ-1776" TO 1800"	± 12"	
	CA-1800" TO 1824"	± 12 1/8"	
	CB-1824" TO 1848"	± 12 1/4"	
	CC-1848" TO 1872"	± 12 1/2"	
	CD-1872" TO 1896"	± 12 3/4"	
	CE-1896" TO 1920"	± 12 7/8"	
	CF-1920" TO 1944"	± 13"	
	CG-1944" TO 1968"	± 13 1/8"	
	CH-1968" TO 1992"	± 13 1/4"	
	CI-1992" TO 2016"	± 13 1/2"	
	CJ-2016" TO 2040"	± 13 3/4"	
	CK-2040" TO 2064"	± 13 7/8"	
	CL-2064" TO 2088"	± 14"	
	CM-2088" TO 2112"	± 14 1/8"	
	CN-2112" TO 2136"	± 14 1/4"	
	CO-2136" TO 2160"	± 14 1/2"	
	CP-2160" TO 2184"	± 14 3/4"	
	CQ-2184" TO 2208"	± 14 7/8"	
	CR-2208" TO 2232"	± 15"	
	CS-2232" TO 2256"	± 15 1/8"	
	CT-2256" TO 2280"	± 15 1/4"	
	CU-2280" TO 2304"	± 15 1/2"	
	CV-2304" TO 2328"	± 15 3/4"	
	CW-2328" TO 2352"	± 15 7/8"	
	CX-2352" TO 2376"	± 16"	
	CY-2376" TO 2400"	± 16 1/8"	
	CZ-2400" TO 2424"	± 16 1/4"	
	DA-2424" TO 2448"	± 16 1/2"	
	DB-2448" TO 2472"	± 16 3/4"	
	DC-2472" TO 2496"	± 16 7/8"	
	DD-2496" TO 2520"	± 17"	
	DE-2520" TO 2544"	± 17 1/8"	
	DF-2544" TO 2568"	± 17 1/4"	
	DG-2568" TO 2592"	± 17 1/2"	
	DH-2592" TO 2616"	± 17 3/4"	
	DI-2616" TO 2640"	± 17 7/8"	
	DJ-2640" TO 2664"	± 18"	
	DK-2664" TO 2688"	± 18 1/8"	
	DL-2688" TO 2712"	± 18 1/4"	
	DM-2712" TO 2736"	± 18 1/2"	
	DN-2736" TO 2760"	± 18 3/4"	
	DO-2760" TO 2784"	± 18 7/8"	
	DP-2784" TO 2808"	± 19"	
	DQ-2808" TO 2832"	± 19 1/8"	
	DR-2832" TO 2856"	± 19 1/4"	
	DS-2856" TO 2880"	± 19 1/2"	
	DT-2880" TO 2904"	± 19 3/4"	
	DU-2904" TO 2928"	± 19 7/8"	
	DV-2928" TO 2952"	± 20"	
	DW-2952" TO 2976"	± 20 1/8"	
	DX-2976" TO 3000"	± 20 1/4"	
	DY-3000" TO 3024"	± 20 1/2"	
	DZ-3024" TO 3048"	± 20 3/4"	
	EA-3048" TO 3072"	± 20 7/8"	
	EB-3072" TO 3096"	± 21"	
	EC-3096" TO 3120"	± 21 1/8"	
	ED-3120" TO 3144"	± 21 1/4"	
	EE-3144" TO 3168"	± 21 1/2"	
	EF-3168" TO 3192"	± 21 3/4"	
	EG-3192" TO 3216"	± 21 7/8"	
	EH-3216" TO 3240"	± 22"	
	EI-3240" TO 3264"	± 22 1/8"	
	EJ-3264" TO 3288"	± 22 1/4"	
	EK-3288" TO 3312"	± 22 1/2"	
	EL-3312" TO 3336"	± 22 3/4"	
	EM-3336" TO 3360"	± 22 7/8"	
	EN-3360" TO 3384"	± 23"	
	EO-3384" TO 3408"	± 23 1/8"	
	EP-3408" TO 3432"	± 23 1/4"	
	EQ-3432" TO 3456"	± 23 1/2"	
	ER-3456" TO 3480"	± 23 3/4"	
	ES-3480" TO 3504"	± 23 7/8"	
	ET-3504" TO 3528"	± 24"	
	EU-3528" TO 3552"	± 24 1/8"	
	EV-3552" TO 3576"	± 24 1/4"	
	EW-3576" TO 3600"	± 24 1/2"	
	EX-3600" TO 3624"	± 24 3/4"	
	EY-3624" TO 3648"	± 24 7/8"	
	EZ-3648" TO 3672"	± 25"	
	FA-3672" TO 3696"	± 25 1/8"	
	FB-3696" TO 3720"	± 25 1/4"	
	FC-3720" TO 3744"	± 25 1/2"	
	FD-3744" TO 3768"	± 25 3/4"	
	FE-3768" TO 3792"	± 25 7/8"	
	FG-3792" TO 3816"	± 26"	
	FH-3816" TO 3840"	± 26 1/8"	
	FI-3840" TO 3864"	± 26 1/4"	
	FJ-3864" TO 3888"	± 26 1/2"	
	FK-3888" TO 3912"	± 26 3/4"	
	FL-3912" TO 3936"	± 26 7/8"	
	FM-3936" TO 3960"	± 27"	
	FN-3960" TO 3984"	± 27 1/8"	
	FO-3984" TO 4008"	± 27 1/4"	
	FP-4008" TO 4032"	± 27 1/2"	
	FQ-4032" TO 4056"	± 27 3/4"	
	FR-4056" TO 4080"	± 27 7/8"	
	FS-4080" TO 4104"	± 28"	
	FT-4104" TO 4128"	± 28 1/8"	
	FU-4128" TO 4152"	± 28 1/4"	
	FV-4152" TO 4176"	± 28 1/2"	
	FW-4176" TO 4200"	± 28 3/4"	
	FX-4200" TO 4224"	± 28 7/8"	
	FY-4224" TO 4248"	± 29"	
	FZ-4248" TO 4272"	± 29 1/8"	
	GA-4272" TO 4296"	± 29 1/4"	
	GB-4296" TO 4320"	± 29 1/2"	
	GC-4320" TO 4344"	± 29 3/4"	
	GD-4344" TO 4368"	± 29 7/8"	
	GE-4368" TO 4392"	± 30"	
	GF-4392" TO 4416"	± 30 1/8"	
	GG-4416" TO 4440"	± 30 1/4"	
	GH-4440" TO 4464"	± 30 1/2"	
	GI-4464" TO 4488"	± 30 3/4"	
	GJ-4488" TO 4512"	± 30 7/8"	
	GK-4512" TO 4536"	± 31"	
	GL-4536" TO 4560"	± 31 1/8"	
	GM-4560" TO 4584"	± 31 1/4"	
	GN-4584" TO 4608"	± 31 1/2"	
	GO-4608" TO 4632"	± 31 3/4"	
	GP-4632" TO 4656"	± 31 7/8"	
	GQ-4656" TO 4680"	± 32"	
	GR-4680" TO 4704"	± 32 1/8"	
	GS-4704" TO 4728"	± 32 1/4"	
	GT-4728" TO 4752"	± 32 1/2"	
	GU-4752" TO 4776"	± 32 3/4"	
	GV-4776" TO 4800"	± 32 7/8"	
	GW-4800" TO 4824"	± 33"	
	GX-4824" TO 4848"	± 33 1/8"	
	GY-4848" TO 4872"	± 33 1/4"	
	GZ-4872" TO 4896"	± 33 1/2"	
	HA-4896" TO 4920"	± 33 3/4"	
	HB-4920" TO 4944"	± 33 7/8"	
	HC-4944" TO 4968"	± 34"	
	HD-4968" TO 4992"	± 34 1/8"	
	HE-4992" TO 5016"	± 34 1/4"	
	HF-5016" TO 5040"	± 34 1/2"	
	HG-5040" TO 5064"	± 34 3/4"	
	HH-5064" TO 5088"	± 34 7/8"	
	HI-5088" TO 5112"	± 35"	
	HJ-5112" TO 5136"	± 35 1/8"	
	HK-5136" TO 5160"	± 35 1/4"	
	HL-5160" TO 5184"	± 35 1/2"	
	HM-5184" TO 5208"	± 35 3/4"	
	HN-5208" TO 5232"	± 35 7/8"	
	HO-5232" TO 5256"	± 36"	
	HP-5256" TO 5280"	± 36 1/8"	
	HQ-5280" TO 5304"	± 36 1/4"	
	HR-5304" TO 5328"	± 36 1/2"	
	HS-5328" TO 5352"	± 36 3/4"	
	HT-5352" TO 5376"	± 36 7/8"	
	HU-5376" TO 5400"	± 37"	
	HV-5400" TO 5424"	± 37 1/8"	
	HW-5424" TO 5448"	± 37 1/4"	
	HX-5448" TO 5472"	± 37 1/2"	
	HY-5472" TO 5496"	± 37 3/4"	
	HZ-5496" TO 5520"	± 37 7/8"	
	IA-5520" TO 5544"	± 38"	
	IB-5544" TO 5568"	± 38 1/8"	
	IC-5568" TO 5592"	± 38 1/4"	
	ID-5592" TO 5616"	± 38 1/2"	
	IE-5616" TO 5640"	± 38 3/4"	
	IF-5640" TO 5664"	± 38 7/8"	
	IG-5664" TO 5688"	± 39"	
	IH-5688" TO 5712"	± 39 1/8"	
	II-5712" TO 5736"	± 39 1/4"	
	IJ-5736" TO 5760"	± 39 1/2"	
	IK-5760" TO 5784"	± 39 3/4"	
	IL-5784" TO 5808"	± 39 7/8"	
	IM-5808" TO 5832"	± 40"	
	IN-5832" TO 5856"	± 40 1/8"	
	IO-5856" TO 5880"	± 40 1/4"	
	IP-5880" TO 5904"	± 40 1/2"	
	IQ-5904" TO 5928"	± 40 3/4"	
	IR-5928" TO 5952"	± 40 7/8"	
	IS-5952" TO 5976"	± 41"	
	IT-5976" TO 6000"	± 41 1/8"	
	IU-6000" TO 6024"	± 41 1/4"	
	IV-6024" TO 6048"	± 41 1/2"	
	IV-6048" TO 6072"	± 41 3/4"	
	IV-6072" TO 6096"	± 41 7/8"	
	IV-6096" TO 6120"	± 42"	

Manufacturer: Midwest Hose & Specialty

Serial Number: SN#90067

Length: 35'

Size: OD = 8" ID = 4"

Ends: Flanges Size: 4-1/16"

WP Rating: 10,000 psi Anchors required by manufacturer: No

M I D W E S T

HOSE AND SPECIALTY INC.

INTERNAL HYDROSTATIC TEST REPORT		
Customer: CACTUS		P.O. Number: RIG #123 Asset # M10761
HOSE SPECIFICATIONS		
Type: CHOKER LINE		Length: 35'
I.D. 4" INCHES		O.D. 8" INCHES
WORKING PRESSURE 10,000 PSI	TEST PRESSURE 15,000 PSI	BURST PRESSURE PSI
COUPLINGS		
Type of End Fitting 4 1/16 10K FLANGE		
Type of Coupling: SWEDGED		MANUFACTURED BY MIDWEST HOSE & SPECIALTY
PROCEDURE		
<i>Hose assembly pressure tested with water at ambient temperature.</i>		
TIME HELD AT TEST PRESSURE 1 MIN.		ACTUAL BURST PRESSURE: 0 PSI
COMMENTS: SN#90067 M10761 Hose is covered with stainless steel armour cover and wrapped with fire resistant vermiculite coated fiberglass insulation rated for 1500 degrees complete with lifting eyes		
Date: 6/6/2011	Tested By: BOBBY FINK	Approved: MENDI JACKSON



Midwest Hose
& Specialty, Inc.

Internal Hydrostatic Test Graph

Customer: CACTUS


SALES ORDER# 90067

Hose Specifications

<u>Hose Type</u>	<u>Length</u>
C & K	35'
<u>I.D.</u>	<u>O.D.</u>
4"	8"
<u>Working Pressure</u>	<u>Burst Pressure</u>
10000 PSI	Standard Safety Multiplier Applies

Verification

<u>Type of Fitting</u>	<u>Coupling Method</u>
4 1/16 10K	Swage
<u>Die Size</u>	<u>Final O.D.</u>
6.62"	6.68"
<u>Hose Serial #</u>	<u>Hose Assembly Serial #</u>
	90067



Test Pressure
15000 PSI

Time Held at Test Pressure
11 1/4 Minutes

Actual Burst Pressure

Peak Pressure
15439 PSI

Comments: Hose assembly pressure tested with water at ambient temperature.

Tested By: Bobby Fink

Bobby Fink

Approved By: Mendi Jackson


Mendi Jackson

Exhibit 1


EOG Resources

10M BOPE

Rig Floor



1. 13 5/8" Rotating Head
2. Hydril 13 5/8" 10,000 PSI WP GK Annular Preventor
3. 13 5/8" Cameron Type "U" 10,000 PSI WP Ram Preventors
4. 2 1/16" - 10,000 PSI WP Check Valve
5. 10,000 PSI WP - 1502 Union to kill line
6. 2 1/16" - 10,000 PSI WP Manual Valves
7. 13 5/8" 3,000 PSI WP x 13 5/8" 5,000 PSI WP Spacer Spool
8. 4 1/16" 10,000 PSI WP HCR Valve
9. 4 1/16" 10,000 PSI WP Manual Valve
10. 6" OD x 3" ID 10,000 PSI WP Steel Armoured Flex Choke Line
11. DSA - 13 5/8" 10,000 PSI WP x 13 5/8" 5,000 PSI WP
12. Mud Cross - 13 5/8" 10,000 PSI WP
13. Blind Rams
14. Pipe Rams
15. 13 5/8" Cameron Type "U" 10,000 PSI WP Pipe Rams
16. Flow Line
17. 2" Fill Line



OD	Weight	Wall Th.	Grade	API Drift	Connection
7 5/8 in.	29.70 lb/ft	0.375 in.	VM 110 HC	6.750 in.	VAM® SLIJ-II

PIPE PROPERTIES

Nominal OD	7.625 in.
Nominal ID	6.875 in.
Nominal Cross Section Area	8.541 sqin.
Grade Type	High Collapse
Min. Yield Strength	110 ksi
Max. Yield Strength	140 ksi
Min. Ultimate Tensile Strength	125 ksi

CONNECTION PROPERTIES

Connection Type	Premium integral semi-flush
Connection OD (nom)	7.711 in.
Connection ID (nom)	6.820 in.
Make-up Loss	4.822 in.
Critical Cross Section	5.912 sqin.
Tension Efficiency	69.2 % of pipe
Compression Efficiency	48.5 % of pipe
Internal Pressure Efficiency	100 % of pipe
External Pressure Efficiency	100 % of pipe

CONNECTION PERFORMANCES


Tensile Yield Strength	651 klb
Compression Resistance	455 klb
Internal Yield Pressure	9470 psi
Uniaxial Collapse Pressure	7890 psi
Max. Bending Capacity	TDB
Max Bending with Sealability	20 °/100 ft

FIELD TORQUE VALUES

Min. Make-up torque	11300 ft.lb
Opti. Make-up torque	12600 ft.lb
Max. Make-up torque	13900 ft.lb

VAM® SLIJ-II is a semi-flush integral premium connection for all casing applications. It combines a near flush design with high performances in tension, compression and gas sealability.

VAM® SLIJ-II has been validated according to the most stringent tests protocols, and has an excellent performance history in the world's most prolific HPHT wells.



Do you need help on this product? - Remember no one knows VAM® like VAM

canada@vamfieldservice.com
usa@vamfieldservice.com
mexico@vamfieldservice.com
brazil@vamfieldservice.com

uk@vamfieldservice.com
dubai@vamfieldservice.com
nigeria@vamfieldservice.com
angola@vamfieldservice.com

china@vamfieldservice.com
baku@vamfieldservice.com
singapore@vamfieldservice.com
australia@vamfieldservice.com


Over 140 VAM® Specialists available worldwide 24/7 for Rig Site Assistance

Other Connection Data Sheets are available at www.vamservices.com

Vallourec Group



Metal One Corp	FLUSHMAX-III Connection Data Sheet	Page	44-0
		Date	1-Oct-15
		Rev.	N-0



Pipe Body	Imperial		S.I.	
Grade	P110		P110	
Pipe OD (D)	7 5/8	in	193.68	mm
Weight	29.7	lb/ft	44.25	kg/m
Actual weight	29.0	lb/ft	43.26	kg/m
Wall thickness (t)	0.375	in	9.53	mm
Pipe ID (d)	6.875	in	174.63	mm
Pipe body cross section	8.537	in ²	5.508	mm ²
Drift Dia.	6.750	in	171.45	mm

Connection				
Box OD (W)	7.625	in	193.68	mm
PIN ID	6.875	in	174.63	mm
Pin critical area	4.420	in ²	2,852	mm ²
Box critical area	4.424	in ²	2,854	mm ²
Joint load efficiency	60	%	60	%
Make up loss	3.040	in	77.22	mm
Thread taper	1/16 (3/4 in per ft)			
Number of threads	5 thread per in.			

Connection Performance Properties

Tensile Yield load	563.4	kips	2,506	kN
M.I.Y.P.	7,574	psi	52.2	MPa
Collapse strength	5,350	psi	36.9	MPa

Note

M.I.Y.P. = Minimum Internal Yield Pressure of the connection

Torque Recommended


Min.	8,700	ft-lb	11,700	N-m
Opti.	9,700	ft-lb	13,100	N-m
Max.	10,700	ft-lb	14,500	N-m
Operational Max.	23,600	ft-lb	32,000	N-m


Note : Operational Max. torque can be applied for high torque application

See previously attached Drill Plan

Exhibit 4
EOG Resources
Philly 31 Fed Com #702H

Well Site Diagram





*CONCEPT QUOTE DRAWING
 *DIMENSIONS ARE APPROXIMATE

EOG RECOUPLED

10-3/4" X 7-5/8" X 5-1/2"
 FBI-100 WELLHEAD SYSTEM
 QUOTE: HOU - 102101

DWN	BAY	2/22/17
CHK		
APP		
	BY	DATE



Worldwide Expertise - Global Strength

DRAWING NO
 WH-16618

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

New road access plan attachment:

Access road engineering design? NO

Access road engineering design attachment:

Access surfacing type: OTHER

Access topsoil source: ONSITE

Access surfacing type description: 6" of Compacted Caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: An adequate amount of topsoil/root zone will be stripped by dozer from the proposed well location and stockpiled along the side of the well location as depicted on the well site diagram / survey plat.

Access other construction information:

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: OTHER

Drainage Control comments: No drainage crossings

Road Drainage Control Structures (DCS) description: N/A

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

PHILLY31FEDCOM702H_radius_20170927141204.pdf

Existing Wells description:

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: Philly 31 Fed Com CTB is located in lot 2 of section 31

Production Facilities map:

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Philly_31_Fed_CTB_20170927141220.pdf

Philly_31_Fed_infrastructure_20170927141221.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

Water source use type: OTHER

Water source type: RECYCLED

Describe type:

Source latitude:

Source longitude:

Source datum:

Water source permit type: WATER RIGHT

Source land ownership: STATE

Water source transport method: PIPELINE,TRUCKING

Source transportation land ownership: STATE

Water source volume (barrels): 720000

Source volume (acre-feet): 92.80303

Source volume (gal): 30240000

Water source and transportation map:

Philly_31_Fed_Com_water_and_caliche_map_20170927141310.jpg

Water source comments:

New water well? NO

New Water Well Info

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Construction Materials description: Caliche utilized for the drilling pad will be obtained either from an existing approved mineral pit, or by benching into a hill, which will allow the pad to be level with existing caliche from the cut, or extracted by "Flipping" the well location. A mineral material permit will be obtained from BLM prior to excavating any caliche on Federal Lands. Amount will vary for each pad.

Construction Materials source location attachment:

Philly_31_Fed_Com_water_and_caliche_map_20170927141326.jpg

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Drill fluids and produced oil and water from the well during drilling and completion operations will be stored safely and disposed of properly in an NMOCD approved disposal facility. Garbage and trash produced during drilling and completion operations will be collected in a trash container and disposed of properly. Human waste and grey water will be properly contained of and disposed of properly. After drilling and completion operations; trash, chemicals, salts, frac sand, and other waste material will be removed and disposed of properly at a state approved disposal facility.

Amount of waste: 0 barrels

Waste disposal frequency : Daily

Safe containment description: Steel Tanks

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: Trucked to NMOCD approved disposal facility

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit?

Reserve pit length (ft.)

Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Cuttings Area being used? NO

Are you storing cuttings on location? YES

Description of cuttings location Closed Loop System. Drill cuttings will be disposed of into steel tanks and taken to an NMOC approved disposal facility.

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: NO

Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

Philly_31_FC_702H_Rig_Layout_20170925104228.pdf

PHILLY31FEDCOM702H_padsite_20170927141349.pdf

PHILLY31FEDCOM702H_wellsite_20170927141350.pdf

Comments: Wellsite, Padsite, Rig Layout

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: PHILLY 31 FED COM

Multiple Well Pad Number: 701H/702H

Recontouring attachment:

PHILLY31FEDCOM702H_reclamation_20170927141403.pdf

Drainage/Erosion control construction: Proper erosion control methods will be used on the area to control erosion, runoff, and siltation of the surrounding area.

Drainage/Erosion control reclamation: The interim reclamation will be monitored periodically to ensure that vegetation has reestablished and that erosion is controlled.

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Wellpad long term disturbance (acres): 2.029385

Wellpad short term disturbance (acres): 4.178145

Access road long term disturbance (acres): 0.669421

Access road short term disturbance (acres): 0.669421

Pipeline long term disturbance (acres): 0.3443526

Pipeline short term disturbance (acres): 0.573921

Other long term disturbance (acres): 0

Other short term disturbance (acres): 0

Total long term disturbance: 3.0431585

Total short term disturbance: 5.421487

Reconstruction method: In areas planned for interim reclamation, all the surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads. Areas planned for interim reclamation will be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ratio, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.

Topsoil redistribution: Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations including cuts and fills. To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.

Soil treatment: Re-seed according to BLM standards. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, and that erosion is controlled.

Existing Vegetation at the well pad: Grass, forbs, and small woody vegetation, such as mesquite will be excavated as the topsoil is removed. Large woody vegetation will be stripped and stored separately and respreads evenly on the site following topsoil resspreading. Topsoil depth is defined as the top layer of soil that contains 80% of the roots. In areas to be heavily disturbed, the top 6 inches of soil material, will be stripped and stockpiled on the perimeter of the well location and along the perimeter of the access road to control run-on and run-off, to keep topsoil viable, and to make redistribution of topsoil more efficient during interim reclamation. Stockpiled topsoil should include vegetative material. Topsoil will be clearly segregated and stored separately from subsoils.

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.

Existing Vegetation Community at other disturbances attachment:

Non native seed used? NO

Non native seed description:

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Seedling transplant description:

Will seedlings be transplanted for this project? NO

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? NO

Seed harvest description:

Seed harvest description attachment:

Seed Management

Seed Table

Seed type:

Seed source:

Seed name:

Source name:

Source address:

Source phone:

Seed cultivar:

Seed use location:

PLS pounds per acre:

Proposed seeding season:

Seed Summary

Total pounds/Acre:

Seed Type	Pounds/Acre
-----------	-------------

Seed reclamation attachment:

Operator Contact/Responsible Official Contact Info

First Name: Stan

Last Name: Wagner

Phone: (432)686-3689

Email: stan_wagner@eogresources.com

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? NO

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

Weed treatment plan description: All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, erosion is controlled, and free of noxious weeds. Weeds will be treated if found.

Weed treatment plan attachment:

Monitoring plan description: Reclamation will be completed within 6 months of well plugging. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, erosion is controlled, and free of noxious weeds.

Monitoring plan attachment:

Success standards: N/A

Pit closure description: NA

Pit closure attachment:

Section 11 - Surface Ownership

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT, PRIVATE OWNERSHIP

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Section 12 - Other Information

Right of Way needed? NO

Use APD as ROW?

ROW Type(s):

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

ROW Applications

SUPO Additional Information: OnSite meeting conducted 1/12/17

Use a previously conducted onsite? NO

Previous Onsite information:

Other SUPO Attachment

Philly_31_Fed_CTB_20170927141601.pdf

PHILLY31FEDCOM702H_location_20170927141602.pdf

SUPO_Philly_31_Fed_Com_702H_20170927141603.pdf

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Injection well name:

Assigned injection well API number?

Injection well API number:

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Bond Info Data Report

04/19/2018

Bond Information

Federal/Indian APD: FED

BLM Bond number: NM2308

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment:

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
EXIT Leg #1	330	FNL	750	FWL	26S	34E	30	Lot 1	32.02074 8	- 103.5151 223	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 122626	- 932 7	198 92	126 93
BHL Leg #1	230	FNL	750	FWL	26S	34E	30	Lot 1	32.02102 31	- 103.5151 223	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 122626	- 932 7	199 92	126 93



APD ID: 10400022612

Submission Date: 09/27/2017

Highlighted data
reflects the most
recent changes

Operator Name: EOG RESOURCES INCORPORATED

Well Name: PHILLY 31 FED COM

Well Number: 702H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

PHILLY31FEDCOM702H_vicinity_20170927141055.pdf

Existing Road Purpose: ACCESS, FLUID TRANSPORT

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

Philly_31_Fed_infrastructure_20170927141138.pdf

PHILLY31FEDCOM702H_padsite_20170927141138.pdf

PHILLY31FEDCOM702H_wellsite_20170927141139.pdf

New road type: RESOURCE

Length: 1215 Feet

Width (ft.): 24

Max slope (%): 2

Max grade (%): 20

Army Corp of Engineers (ACOE) permit required? NO

ACOE Permit Number(s):

New road travel width: 24

New road access erosion control: Newly constructed or reconstructed roads will be constructed as outlined in the BLM "Gold Book" and to meet the standards of the anticipated traffic flow and all anticipated weather requirements as needed. Construction will include ditching, draining, crowning and capping or sloping and dipping the roadbed as necessary to provide a well-constructed and safe road. We plan to grade and water twice a year.

New road access plan or profile prepared? NO



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

PWD Data Report

04/19/2018

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment: