Form 3160-5 (June 2015) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT NMOCI SUNDRY NOTICES AND REPORTS ON WELLS Hobbs			OMB	FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018	
			5. Lease Serial No.	January 51, 2018	
SUNDR Do not use	Y NOTICES AND REPO this form for proposals to	drill or to re-enter an	~	m 11 - 53	
abandoned	this form for proposals to well. Use form 3160-3 (API	D) for such proposals.	6. If Indian, Allottee	or Tribe Name	
SUBMIT	N TRIPLICATE - Other inst	ructions on page 2	7. If Unit or CA/Agr	eement, Name and/or No.	
1. Type of Well ☑ Oil Well ☑ Gas Well ☑ Other			8. Well Name and No MESA VERDE		
Name of Operator OXY USA INC.		JANA MENDIOLA endiola@oxy.com	9. API Well No. 30-025-44185	1	
a. Address P.O. BOX 50250 MIDLAND, TX 79710		3b. Phone No. (include area (4) Ph: 432-685-5936		EXPLORATORY Area	
4. Location of Well (Footage, See	., T., R., M., or Survey Description,	MAY	11. County or Parish	, State	
Sec 17 T24S R32E SESE 32.211012 N Lat, 103.6914	280FSL 995FEL 🥕 04 W Lon	REC	082018 LEA COUNTY	, NM	
12. CHECK THE	APPROPRIATE BOX(ES)	TO INDICATE NATURE OI	F NOTICE, REPORT, OR OT	HER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION			
□ Notice of Intent	Acidize	Deepen	Production (Start/Resume)	U Water Shut-Off	
_	□ Alter Casing	Hydraulic Fracturing	Reclamation	U Well Integrity	
Subsequent Report	Casing Repair	□ New Construction	Recomplete	Other Drilling Operation	
Final Abandonment Notice	Change Plans	Plug and Abandon Plug Back	 Temporarily Abandon Water Disposal 	Straing Operation	
testing has been completed. Fina	Abandonment Notices must be fil	sults in a multiple completion or reco ed only after all requirements, includ	mpletion in a new interval, a Form 31 ing reclamation, have been completed	e filed within 30 days 60-4 must be filed once and the operator has	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13- PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', µ 1.36 yield, full returns throug & install wellhead cap. BLM	ed only after all requirements, includ It Hutchins) was notified of inte pump 20BFW spacer then cmf hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified	mpletion in a new interval, a Form 31 ing reclamation, have been completed ent to spud t w/ 1245sx (302bbl) cmt to	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-7 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', g 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r	ed only after all requirements, includ at Hutchins) was notified of inte bump 20BFW spacer then cmf hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults.	mpletion in a new interval, a Form 31 ing reclamation, have been completed ent to spud t w/ 1245sx (302bbl) cmt to prior to setting	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-3 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was original	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 8/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r Ily permitted as the MESA V	ed only after all requirements, includ It Hutchins) was notified of inte pump 20BFW spacer then cmf hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified	mpletion in a new interval, a Form 31 ing reclamation, have been completed ent to spud t w/ 1245sx (302bbl) cmt to prior to setting	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" bole 1/29/18, on 1/28/18, RIH & set 13-7 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 8/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r Ily permitted as the MESA V	ed only after all requirements, includ at Hutchins) was notified of inte bump 20BFW spacer then cmf hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults.	mpletion in a new interval, a Form 31 ing reclamation, have been completed ent to spud t w/ 1245sx (302bbl) cmt to prior to setting	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-7 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13705	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r Ily permitted as the MESA V 96X	ed only after all requirements, includ at Hutchins) was notified of inter bump 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5	mpletion in a new interval, a Form 31 ing reclamation, have been completed ent to spud t w/ 1245sx (302bbl) prior to setting 5H.	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-3 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13709	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r lly permitted as the MESA V MAX Mag is true and correct. Electronic Submission # For O Committed to AFMSS for	ed only after all requirements, includ at Hutchins) was notified of inter bourp 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5 403605 verified by the BLM Wel XY USA INC., sent to the Hobb r processing by PRISCILLA PE	mpletion in a new interval, a Form 31 ing reclamation, have been completed ant to spud t w/ 1245sx (302bbl) cmt to prior to setting 5H. IInformation System REZ on 02/12/2018 ()	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-7 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13705	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r lly permitted as the MESA V MAX Mag is true and correct. Electronic Submission # For O Committed to AFMSS for	ed only after all requirements, includ at Hutchins) was notified of inter bourp 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5 403605 verified by the BLM Wel XY USA INC., sent to the Hobb r processing by PRISCILLA PE	mpletion in a new interval, a Form 31 ing reclamation, have been completed ant to spud t w/ 1245sx (302bbl) cmt to prior to setting 5H.	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-3 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13709	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r lly permitted as the MESA V MAX Mag is true and correct. Electronic Submission # For O Committed to AFMSS for	ed only after all requirements, includ at Hutchins) was notified of inter bourp 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5 403605 verified by the BLM Wel XY USA INC., sent to the Hobb r processing by PRISCILLA PE	mpletion in a new interval, a Form 31 ing reclamation, have been completed ant to spud t w/ 1245sx (302bbl) cmt to prior to setting 6H. Information System REZ on 02/12/2018 () GULATORY ADVISOR CEPTED FOR RECO	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-3 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13709	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r Ily permitted as the MESA V 96X mg is true and correct. Electronic Submission # For O Committed to AFMSS fo STEWART	ed only after all requirements, includ at Hutchins) was notified of inter- bourp 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5 403605 verified by the BLM Well XY USA INC., sent to the Hobb r processing by PRISCILLA PEL Title SR. REC	mpletion in a new interval, a Form 31 ing reclamation, have been completed ent to spud w/ 1245sx (302bbl) cmt to prior to setting 5H. Information System Sez on 02/12/2018 () GULATORY ADVISOR CEPTED FOR RECO	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready f Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-3 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13709 14. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) DAVID Signature (Electron	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r Ily permitted as the MESA V 96X mg is true and correct. Electronic Submission # For O Committed to AFMSS fo STEWART	ed only after all requirements, includ at Hutchins) was notified of inter- bourp 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5 403605 verified by the BLM Well XY USA INC., sent to the Hobb r processing by PRISCILLA PEL Title SR. REC Date 02/06/2 DR FEDERAL OR STATE	mpletion in a new interval, a Form 31 ing reclamation, have been completed ent to spud w/ 1245sx (302bbl) cmt to prior to setting 5H. Information System Sez on 02/12/2018 () GULATORY ADVISOR CEPTED FOR RECO	60-4 must be filed once and the operator has	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18 RIH & set 13-3 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13709 (4. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) DAVID Signature (Electron Approved By	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r Ily permitted as the MESA V 96X mag is true and correct. Electronic Submission # For O Committed to AFMSS for STEWART hic Submission) THIS SPACE FO	ed only after all requirements, includ at Hutchins) was notified of inter- bourp 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5 403605 verified by the BLM Well XY USA INC., sent to the Hobb r processing by PRISCILLA PEL Title SR. REC Date 02/06/20 DR FEDERAL OR STATE Title SR ACCONS Date 02/06/20 DR FEDERAL OR STATE	mpletion in a new interval, a Form 31 ing reclamation, have been completed and to spud to w/ 1245sx (302bbl) cmt to prior to setting 6H. Information System REZ on 02/12/2018 () GULATORY ADVISOR CEPTED FOR RECO 018 OFFICE USE	60-4 must be filed once	
testing has been completed. Fina determined that the site is ready for Spud 17-1/2" hole 1/29/18, on 1/28/18, RIH & set 13-3 PPC w/ additives 14.8ppg surface, WOC. 2/1/18 RD & cementing surface casin Note: This well was origina Unit Number: NMNM13709 14. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) DAVID Signature (Electron Approved By onditions of approval, if any, are atta trify that the applicant holds legal o hich would entitle the applicant to c	I Abandonment Notices must be fil or final inspection. drill to 985' 2/1/18, BLM (Pa 3/8" 54.5# J-55 csg @ 974', p 1.36 yield, full returns throug & install wellhead cap. BLM g and after cement job with r Ily permitted as the MESA V 96X ag is true and correct. Electronic Submission # For O Committed to AFMSS fo STEWART hic Submission) THIS SPACE FO enched. Approval of this notice does requitable title to those rights in the onduct operations thereon. 43 U.S.C. Section 1212, make it a	ed only after all requirements, includ at Hutchins) was notified of inter- bourp 20BFW spacer then cmt hout job, circ 508sx (123bbl) of (Pat McKlelvey) was notified esults. ERDE 17-8 FEDERAL COM 5 403605 verified by the BLM Well XY USA INC., sent to the Hobb r processing by PRISCILLA PEL Title SR. REC Date 02/06/22 DR FEDERAL OR STATE Enot warrant or e subject lease Office BL	mpletion in a new interval, a Form 31 ing reclamation, have been completed aw/ 1245sx (302bbl) cmt to prior to setting 5H. Information System REZ on 02/12/2018 () GULATORY ADVISOR CEPTED FOR RECO 018 OFFICE USE ATT 2018	60-4 must be filed once and the operator has	