Form 3160-5 (June 2015) , B SUNDRY Do not use the abandoned we	FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018 5. Lease Serial No. NMLC063798 6. If Indian, Allottee or Tribe Name					
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agr	eement, Name and/or No.
1. Type of Well ☑ Oil Well □ Gas Well □ Other					8. Well Name and No BLUE KRAIT 23	
2. Name of Operator DEVON ENERGY PRODUCTION CONTRACT: BRITTNEY WHEATON DEVON ENERGY PRODUCTION CONTRACT: brittney.wheaton@dvn.com					9. API Well No. 30-025-43237	-
3a. Address 333 W. SHERIDAN AVE OKLAHOMA CITY, OK 7310	3b. Phone No. (include area code) Ph: 405.228.2810 MAY 0 8 2018			10. Field and Pool or Exploratory Area RED HILLS-BONE SPRING, N		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description		)		11. County or Parish, State		
Sec 23 T24S R33E Mer NMP	RECEIVED		LEA COUNTY, NM			
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE O	F NOTICE	, REPORT, OR OT	THER DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
<ul> <li>Notice of Intent</li> <li>Subsequent Report</li> <li>Final Abandonment Notice</li> </ul>	Casing Repair New Const		Iraulic Fracturing	□ Reclan	<ul> <li>Production (Start/Resume)</li> <li>Water Shut-Off</li> <li>Reclamation</li> <li>Well Integrity</li> <li>Recomplete</li> <li>Other</li> </ul>	
Final Abandonment Notice	<ul> <li>Change Plans</li> <li>Convert to Injection</li> </ul>		Plug and Abandon Plug Back		☐ Temporarily Abandon ☑ Water Disposal	
<ol> <li>Amount of water produced from all formations in barrels per day: 710 bbls</li> <li>How water is stored on lease: 6-750 bbl water tanks located at the Blue Krait 23 CTB</li> <li>How water is moved to the disposal facility: piped</li> </ol>					ubsequent reports must l new interval, a Form 3	2018
14. I hereby certify that the foregoing is true and correct. Electronic Submission #410949 verified by the BLM Well Information System For DEVON ENERGY PRODUCTION COMPAN, sent to the Hobbs Committed to AFMSS for processing by DEBORAH MCKINNEY on 04/11/2018 () Name (Printed/Typed) BRITTNEY WHEATON Title REGULATORY PROFESSIONAL						
Signature (Electronic S	Date 04/10/2018					
	THIS SPACE FO	DR FEDER	L OR STATE	OFFICE U	JSE	
Approved By Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease			Title Date			
Office Office Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						
(Instructions on page 2)	OR-SUBMITTED ** O	-		* OPERA	TOR-SUBMITTEI	)** KZ

No

# Additional data for EC transaction #410949 that would not fit on the form

9

## 32. Additional remarks, continued

A. Facility Operators Name: a) Owl SWD Operating, LLC b) Owl SWD Operating, LLC

B. Facility or well name/number: a) Madera SWD 1 b) McCloy SWD 2

C. Type of Facility or well (WDW) (WIW): a) WDW b) WDW

D.1) Location by 1/4 1/4 SE/4 SW/4 Section 14 Township 24S Range 34E

D.2) Location by 1/4 1/4 NW/4 SW/4 Section 15 Township 24S Range 32E

# State of New Mexico Energy, Minerals and Natural Resources Department

Susana Martinez Governor

David Martin Cabinet Secretary

Brett F. Woods, Ph.D. Deputy Cabinet Secretary David R. Catanach, Division Director Oil Conservation Division



Administrative Order SWD-1550 May 7, 2015

# ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Pursuant to the provisions of Division Rule 19.15.26.8B. NMAC, Owl SWD Operating, L.L.C. (the "operator") seeks an administrative order for its proposed Madera SWD Well No.1 with a proposed location 433 feet from the South line and 1970 feet from the West line, Unit letter N of Section 14, Township 24 South, Range 34 East, NMPM, Lea County, New Mexico, for commercial disposal of produced water.

### THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rule 19.15.26.8B. NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Rule 19.15.26.8 NMAC has been met and the operator is in compliance with Rule 19.15.5.9 NMAC.

# IT IS THEREFORE ORDERED THAT:

The applicant, Owl SWD Operating, L.L.C. (OGRID 308339) is hereby authorized to utilize its proposed Madera SWD Well No. 1 (API No. 30-025-42448) with a proposed location 433 feet from the South line and 1970 feet from the West line, Unit letter N of Section 14, Township 24 South, Range 34 East, NMPM, Lea County, New Mexico, for disposal of oil field produced water (UIC Class II only) through open-hole within the Devonian formation from 16200 feet to 17000 feet. Injection shall occur through internally-coated tubing and a packer set a maximum of 100 feet above the top of the open-hole interval. Injection will occur through internally-coated, 5 <sup>1</sup>/<sub>2</sub>- inch or smaller tubing and a packer set within 100 feet of the top of the open-hole interval.

# IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the completion and construction of the well as proposed in the application.

The operator shall supply the Division with a copy of a mudlog over the permitted disposal interval and an estimated insitu water salinity based on open-hole logs. If significant hydrocarbon shows occur while drilling, the operator shall notify the Division's District I and

> 1220 South St. Francis Drive • Santa Fe, New Mexico 87505 Phone (505) 476-3440 • Fax (505) 476-3462 • email: www.emnrd.state.nm.us/ocd

Administrative Order SWD-1550 Owl SWD Operating, L.L.C. May 7, 2015 Page 2 of 3

the operator shall be required to receive written permission prior to commencing disposal.

The operator shall run a CBL (or equivalent) across the entire 7-5/8-inch liner to determine the quality of cement throughout the interval, and to determine ensure a good bond with the 10-3/4-inch intermediate casing. The operator shall provide a copy of the log(s) to Division's District I office prior to commencing injection.

The approved injection interval includes only the Devonian formation. Prior to commencing disposal, the operator shall provide, to the Division's District I office and Santa Fe Bureau Engineering office, a summary of depths (picks) for contacts of the formations (based on mudlog or geophysical logs) which the Division shall use to amend this order for a final description of the depth for the injection interval.

If the upper contact of the Ordovician Ellenburger formation is encountered prior to the lower limit of the approved injection interval at 17000 feet, then the total depth of the well (and injection interval) shall be reduced to the upper contact of Ellenburger formation.

Within two years after commencing disposal, the operator shall conduct an injection survey, consisting of a temperature log or equivalent, over the entire injection interval using representative disposal rates. Copies of the survey results shall be provided to the Division's District I office and Santa Fe Engineering Bureau office.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11A. NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to **no more than 3240 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District I office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of

Administrative Order SWD-1550 Owl SWD Operating, L.L.C. May 7, 2015 Page 3 of 3

disposal to the Division's District office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and 19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District I office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection order after notice and hearing if the operator is in violation of Rule 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate two (2) years after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.

DAVID R. CATANACH Director

DRC/mam

cc: Oil Conservation Division – Hobbs District Office Well File 30-025-42448

30-025-42947

# State of New Mexico 2° Energy, Minerals and Natural Resources Department

Susana Martinez Governor

David Martin Cabinet Secretary

Brett F. Woods, Ph.D. Deputy Cabinet Secretary David R. Catanach, Division Director Oil Conservation Division



Administrative Order SWD-1593 November 5, 2015

# ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Pursuant to the provisions of Division Rule 19.15.26.8B. NMAC, OWL SWD Operating, LLC (the "operator") seeks an administrative order for its proposed McCloy SWD Well No. 2 with a proposed location 1595 feet from the South line and 369 feet from the West line, Unit L of Section 15, Township 24 South, Range 32 East, NMPM, Lea County, New Mexico, for commercial disposal of produced water.

# THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rule 19.15.26.8B. NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Division Rule 19.15.26.8 NMAC have been met and the operator is in compliance with Division Rule 19.15.5.9 NMAC.

### IT IS THEREFORE ORDERED THAT:

Owl SWD Operating, LLC (OGRID 308399), is hereby authorized to utilize its McCloy SWD Well No. 2 (API 30-025-pending) with a location of 1595 feet from the South line and 369 feet from the West line, Unit L of Section 15, Township 24 South, Range 32 East, NMPM, Lea County, for disposal of oil field produced water (UIC Class II only) into the Devonian formation through open hole interval from 16500 feet to 18250 feet. Injection will occur through internally-coated, 5½-inch or smaller tubing and a packer set within 100 feet of the uppermost perforation.

Prior to commencing disposal, the operator shall submit mudlog and geophysical logs information, to the Division's District geologist and Santa Fe Bureau Engineering office, showing evidence agreeable that only the permitted formations are open for disposal including a summary of depths (picks) for contacts of the formations which the Division shall use to amend this order for a final description of the depth for the injection interval.

This permit does not permit disposal into the Ellenburger formation (lower Ordovician) or lost circulation intervals directly on top and obviously connected to this formation.

The operator shall supply the Division with a copy of a mudlog over the permitted disposal interval and an estimated insitu water salinity based on open-hole logs. If significant hydrocarbon

1220 South St. Francis Drive • Santa Fe, New Mexico 87505 Phone (505) 476-3440 • Fax (505) 476-3462 • email: www.emnrd.state.nm.us/ocd

### Administrative Order SWD-1593 Owl SWD Operating, LLC November 5, 2015 Page 2 of 3

shows occur while drilling, the operator shall notify the Division's District I office and the operator shall be required to receive written permission prior to commencing disposal.

The operator shall run a CBL (or equivalent) across the 7-3/4 inch liner through the 10-3/4 casing to surface to demonstrate a good cement bond between the two casings and good cement across the 10-3/4 casing.

Within one year after commencing disposal, the operator shall submit to the Division copies of an injection survey run on this well consisting of a temperature log, or equivalent, run under representative disposal rates.

### IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the well construction proposed and described in the application.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11A. NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to <u>no more than 3350 psi.</u> In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District I office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and

Administrative Order SWD-1593 Owl SWD Operating, LLC November 5, 2015 Page 3 of 3

19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District I office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

The injection authority granted under this order is not transferable except upon division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection permit after notice and hearing if the operator is in violation of 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate two (2) years after the effective date of this order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.

DAVID R. CATANACH Director

DRC/mam

cc: Oil Conservation Division – Hobbs District Office Bureau of Land Management – Carlsbad Application Number – pMAM1529252667