

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283
811 S. First St., Artesia, NM 88210

District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

HOBBS OCD
MAY 21 2018
RECEIVED

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-44567
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Gem 36 State Com
8. Well Number 601H
9. OGRID Number 7377
10. Pool name or Wildcat *WC-025 G-08 S253235G; Lower Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator EOG Resources, Inc.	
3. Address of Operator P.O. Box 2267 Midland, TX 79702	
4. Well Location Unit Letter M : 330 feet from the South line and 294 feet from the West line Section 36 Township 25S Range 32E NMPM County Lea	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3341' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/01/18 Resumed drilling 12-1/4" hole.
5/03/18 Ran 9-5/8", 40#, J55 LTC (0'-3995')
Ran 9-5/8", 40#, HCK55 LTC (3995'-4667')
Cement lead w/ 1285 sx Class C, 12.9 ppg, 1.88 CFS yield;
tail w/ 245 sx Class C, 14.8 ppg, 1.37 CFS yield.
Circulated 510 sx cement to surface. Good casing test to 2050 psi.
5/04/18 Resumed drilling 8-3/4" hole.


Spud Date:

3/28/18

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE


Stan Wagner

TITLE

Regulatory Analyst

DATE

5/10/18

Type or print name


E-mail address:

PHONE:

432-686-3689

For State Use Only

APPROVED BY:



TITLE

Petroleum Engineer

DATE

05/23/18

Conditions of Approval (if any):