District I
1625 N. French Dr., Hobbs, NM 882440BBS OCD
District II
Energy,

State of New Mexico

Energy, Minerals and Natural Resources Department

811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 MAY 2 3 2018
District IV

District IV 1220 S. St. Francis Dr., Santa Fe. NM 87505 Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit	Original
to App	propriate
Distri	ct Öffice

GAS	CA	PTI	IDE	ΡĪ	ΛN
UAO	-			\mathbf{L}	

□ Original	Operator: Apache Corporation	OGRID No:	873	Date:	7/17/2017
☐ Amended				Date:	
Reason	for Amendment:		4		

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Onion Knight Federal Com 201H		Sec 4 T22S R34E	150' FSL & 1025' FWL	800	Flared	Flared only in an emergency
Onion Knight Federal Com 202H	30-024		150' FSL & 2315' FWL	800	Flared	Flared only in an emergency
Onion Knight Federal Com 203H		Sec 4 T22S R34E	150' FSL & 1675' FEL	800	Flared	Flared only in an emergency
Onion Knight Federal Com 204H		Sec 4 T22S R34E	277' FSL & 344' FEL	800	Flared	Flared only in an emergency

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to DCP MIDSTREAM, LP and will be connected to <a href="https://docs.py.ncb/bc/pc-ncb/bc

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **DCP MIDSTREAM, LP** system at that time. Based on current information, it is Apache Corporation's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines