Form 3160-3 (March 2012)	HO	310	JE	FORM AP OMB No. 1 Expires Octol	PROVED 004-0137 ber 31, 2014
UNITED S DEPARTMENT OF BUREAU OF LAND	TATES THE INTERIOR	MA. C	<b>, ()</b>	5. Lease Serial No. MMM120907	
APPLICATION FOR PERMI	T TO DRILL OR REE	NTER	-	6. If Indian, Allotee or	Tribe Name
la. Type of work: 🖌 DRILL	REENTER			7 If Unit or CA Agreem	ènt, Name and No
lb. Type of Well: 🗹 Oil Well 🗌 Gas Well 🗍 Oth	er Single Zone	e 🔲 Multiple	Zone	(8. Lease Name and Wel EIDER FEDERAL 10	1 No. <b>(3) 4 / 3</b>
2. Name of Operator COG PRODUCTION LLC	-17955)	,		9. APT Well-No.	14871
3a. Address 2208 West Main Street Artesia NM 882	3b.         Phone No. (include           10         (575)748-6940	area code)		10. Field and Pool, or Exp WILDCAT / BONE SF	PRING
<ol> <li>Location of Well (Report location clearly and in accordance At surface SWSE / 240 FSL / 2290 FEL / LAT 32 At proposed and zone NWSE / 2410 FSL / 2310 F</li> </ol>	2.167492 / LONG -103.6443	24	5	1. Sec., T. R. M. or Blk.	and Survey or Are
14. Distance in miles and direction from nearest town or post o	ffice*	3100.04455		12. County or Parish	13. State
15. Distance from proposed* location to nearest 240 feet property or lease line, ft. (Also to nearest drig, unit line, if any)	16. No. of acres in le 1840	ise 1	7. Spacing 240	Unit dedicated to this well	
<ol> <li>Distance from proposed location* to nearest well, drilling, completed, 495 feet applied for, on this lease, ft.</li> </ol>	19: Proposed Depth 9280 feet / 16507	feet I	0. BLM/BL FED: NMI	A Bond No. on file 3000860 <sup>/</sup>	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3530 feet	22. Approximate date 02/01/2017	work will start*	1	<ol> <li>Estimated duration</li> <li>30 days</li> </ol>	
	24. Attachments	}		•	
<ol> <li>Well plat certified by a registered surveyor.</li> <li>A Drilling Plan.</li> <li>A Surface Use Plan (if the location is on National Forest SUPO must be filed with the appropriate Forest Service Of</li> </ol>	t System Lands, the fice).	nd to cover the m 20 above). erator certificati ich other site spo LM.	operations ion ecific inform	unless covered by an exi nation and/or plans as ma	isting bond on file ay be required by
25. Signature (Electronic-Submission)	Name (Printed) Mayte Reyes	Typed) / Ph: (575)74	18-6945	Da 1	nte 0/31/2017
Title Regulatory Analyst					
Approved by <i>(Signature)</i> (Electronic Submission)	Name (Printed Cody Layton	(Typed) / Ph: (575)234	4-5959	Di	ate )5/21/2018
Title Supervisor Multiple Resources	Office CARLSBAD				
Application approval does not warrant or certify that the appli conduct operations thereon./ Conditions of approval, if any, are attached.	cant holds legal or equitable title	e to those rights	in the subje	ct lease which would entit	tle the applicant to
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, ma States any false, fictitious or fraudulent statements or represent	ake it a crime for any person kno ations as to any matter within its j	wingly and will urisdiction.	lfully to mal	ke to any department or a	gency of the Uni
(Continued on page 2)	· · · · · · · · · · · · · · · · · · ·		1	*(Instruc	ctions on pag

Must be in compliance with NMOCD Rule 5.9 prior to placing well on production

APPI Approval Date: 05/21/2018

### **INSTRUCTIONS**

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new-reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

The Privacy Act of 1974 and regulation in 43 CFR 2:48(d) provide that you be furnished the following information in connection with information required by this application.

NOTIČES

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts. ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to-civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

•

The BLM collects this information to allow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

(Continued on page 3)

(Form 3160-3, page 2)

Approval Date: 05/21/2018

### **Additional Operator Remarks**

### Location of Well

1. SHL: SWSE / 240 FSL / 2290 FEL / TWSP: 24S / RANGE: 32E / SECTION: 35 / LAT: 32.167492 / LONG: -103.644324 ( TVD: 0 Teet, MD: 0 feet ) PPP: SWSE / 330 FSL / 2310 FEL / TWSP: 24S / RANGE: 32E / SECTION: 35 / LAT: 32.167739 / LONG: -103.644388 (TVD: 8780 feet, MD: 8780 feet ) BHL: NWSE / 2410 FSL / 2310 FEL / TWSP: 24S / RANGE: 32E / SECTION: 26 / LAT: 32.187982 / LONG: -103.644355 ( TVD: 9280 feet, MD: 16507 feet )

### **BLM Point of Contact**

Name: Sipra Dahal Title: Legal Instruments Examiner Phone: 5752345983 Email: sdahal@blm.gov

(Form 3160-3, page 3)

### **Review and Appeal Rights**

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

# **FMSS**

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

# Application Data Report

Title: Regulatory Analyst

05/23/2018

APD ID: 10400023748

**Operator Name: COG PRODUCTION LLC** 

Well Name: EIDER FEDERAL

Well Type: OIL WELL

Submission Date: 10/31/2017

Is the first lease penetrated for production Federal or Indian? FED

**Reservation:** 

**Zip:** 88210

Well Number: 105H Well Work Type: Drill Highlighted data reflects the most recent changes

Show Final Text

Submission Date: 10/31/2017

**APD ID:** 10400023748

BLM Office: CARLSBAD

Federal/Indian APD: FED

Lease number: NMNM120907

Surface access agreement in place?

Agreement in place? NO

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

Operator letter of designation:

APD Operator: COG PRODUCTION LLC

**Tie to previous NOS?** 

User: Mayte Reyes

Lease Acres: 1840

Federal or Indian agreement:

Allotted?

**Operator Info** 

Operator Organization Name: COG PRODUCTION LLC

Operator Address: 2208 West Main Street

**Operator PO Box:** 

Operator City: Artesia State: NM

**Operator Phone:** (575)748-6940

Operator Internet Address: mreyes1@concho.com

### Section 2 - Well Information

Well in Master Development Plan? NO	Mater Development Plan na	ame:
Well in Master SUPO? NO	Master SUPO name:	,
Well in Master Drilling Plan? NO	Master Drilling Plan name:	
Well Name: EIDER FEDERAL	Well Number: 105H	Well API Number:
Field/Pool or Exploratory? Field and Pool	Field Name: WILDCAT	Pool Name: BONE SPRING

Is the proposed well in an area containing other mineral resources? USEABLE WATER

Page 1 of 3

Operator Name: COG PRODUCTION LLC	)
Well Name: FIDER FEDERAL	

Well Number: 105H

												'						
Desc	cribe d	other	miner	als:														
Is th	e prop	osed	well	in a H	elium	prod	uctio	n area?	N Use E	Existing W	ell Pa		Ne	ew :	surface o	distur	bance	?
Туре	e of W	ell Pa	<b>d:</b> MU	ILTIPL	E WE	ELL			Multi	ple Well P	ad Nai	ne: Ell		umt	<b>ber:</b> 105H	H, 205	H, 106	6H,
Well	Class	: HOł	RIZON	ITAL					Numi	Number of Legs: 1								
Well	Work	Туре	: Drill											•,				
Well	Type:		WELL															
Desc	cribe V	Vell T	ype:															
Well	sub-T	ype:	INFILI	L														
Desc	cribe s	ub-ty	vpe:															
Dista	ance t	o tow	n: 22	Miles			Dist	tance to	nearest v	<b>vell:</b> 495 F	T	Dist	ance t	o le	ease line	: 240	FT	
Rese	ervoir	well s	spacir	ng ass	igneo	d acre	s Mea	asurem	ent: 240 A	cres	·							
Well	plat:	СС	DG_Ei	der_1	05H_(	C102_	_2017	102008	5840.pdf									
Well	work	start	Date:	02/01	/2017				Durat	tion: 30 D/	AYS							
F																		
	Sec	tion	3 - V	Vell	Loca	atior	n Tał	ole										
Surv	еу Туן	pe: RI	ECTAI	NGUL	AR													
Desc	ribe S	urvey	у Туре	e:														
Datu	m: NA	D83							Vertic	al Datum:		88						
Surv	ey nu	mber:	:															
	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	ease Type	Lease Number	Elevation	QW	DVT
SHL	240	FSL	229	FEL	24S		35	Aliquot		-	LEA	NEW	NEW	F	NMNM	353.	0	0
Leg #1			0					SWSE	2	103.6443 24		MEXI CO	MEXI CO		120907	0		
KOP Leg #1	240	FSL	229 0	FEL	24S	32E	35	Aliquot SWSE	32.16749 2	- 103.6443 24	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 120907	353 0	0	0
PPP Leg	330	FSL	231 0	FEL	24S	32E	35	Aliquot SWSE	32.16773 9	- 103.6443	LEA	NEW MEXI	NEW MEXI	F	NMNM 120907	- 525	878 0	878 0

co

co

88 .

#1

0

Well Name: EIDER FEDERAL

### Well Number: 105H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	QW	TVD
EXIT	231	FSL	231	FEL	24S	32E	26	Aliquot	32.18770	-	LEA	NEW	NEW	F	NMNM	-	163	928
Leg	0		0					NWSE	7 .	103.6443		MEXI	MEXI		120907	575	00	3
#1										56		со	со			3		
BHL	241	FSL	231	FEL	24S	32E	26	Aliquot	32.18798	-	LEA	NEW	NEW	F	NMNM	-	165	928
Leg	0		0					NWSE	2	103.6443		MEXI	MEXI		120907	575	07	0
#1										55		со	CÒ			0		

-



# **FAFMSS**

U.S. Department of the Interior -BUREAU OF LAND MANAGEMENT Drilling Plan Data Report 05/23/2018

APD ID: 10400023748

**Operator Name: COG PRODUCTION LLC** 

Well Name: EIDER FEDERAL

Well Type: OIL WELL

### Submission Date: 10/31/2017

Highlighted data reflects the most recent changes

Show Final Text

Well Work Type: Drill

Well Number: 105H

# **Section 1 - Geologic Formations**

Formation	the second se	1.1.	True Vertical	Méasured	ſ	· Jan	Producing
ID	Formation Name	Elevation	Depth	Depth	Lithologies	Mineral Resources	Formation
1	QUATERNARY	3530	Ó	Ó		NONE	No
2	RUSTLER	2577	953	953		NONE	No
3	TOP SALT	2244	1286	1286		NONE	No
4.	BASE OF SALT	-1090	4620	4620		NONE	No
5	LAMAR	-1318	4848	4848	· · · · · · · · · · · · · · · · · · ·	NONE	No
6	BELL CANYON	-1359	4889	4889		NONE	No,
7	CHERRY CANYON	-2268	5798	5798		NATURAL GAS,OIL	No
8	BRUSHY CANYON	-3648	7178	7178	SCHIST	NATURAL GAS,OIL	No
9	BONE SPRING LIME	-5290	8820	8820		NATURAL GAS,OIL	No
10	UPPER AVALON SHALE	-5635	9165	9165		NATURAL GAS,OIL	Yes
11		-5815	9345	9345		NATURAL GAS,OIL	No

### **Section 2 - Blowout Prevention**

Pressure Rating (PSI): 2M

Rating Depth: 4875

**Equipment:** Annular, Blind Ram, Pipe Ram. The BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold.

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold.

**Testing Procedure:** BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Well Name: EIDER FEDERAL

Well Number: 105H

### Choke Diagram Attachment:

COG\_Eider\_105H\_2M\_Choke\_20171020091414.pdf

### **BOP Diagram Attachment:**

COG\_Eider\_105H\_2M\_BOP\_20171020091420.pdf

COG\_Eider\_105H\_Flex\_Hose\_20171020091518.pdf

Pressure Rating (PSI): 3M

### Rating Depth: 9280

**Equipment:** Annular. The BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold.

### Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.

**Testing Procedure:** BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

### **Choke Diagram Attachment:**

COG\_Eider\_105H\_3M\_Choke\_20171020091544.pdf

### **BOP Diagram Attachment:**

COG Eider 105H 3M BOP 20171020091550.pdf

COG\_Eider\_105H\_Flex\_Hose\_20171020091558.pdf

S	ec	ti	on	3	-	Ca	sir	ŋg	
---	----	----	----	---	---	----	-----	----	--

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	980	0	980			980	J-55	54.5	STC	2.52	1.27	DRY	9.62	DRY	9.62
2	INTERMED IATE	12.2 5	9.625	NEW	API	Y	0	4875	0	4875			4875	L-80	40	LTC	1.21	1.62	<u></u> DRY	5.73	DRY	5.73
3	PRODUCTI ON	8.75	5.5	NEW	API	N	0	16507	0	16507			16507	Р- 110	17	LTC	1.67	2.99	DRY	2.82	DRY	2.82

### **Casing Attachments**

Well Name: EIDER FEDERAL

Well Number: 105H

c	asi	ina	<b>Attachments</b>	
-	as	шy	Allacinitents	

Casing ID: 1 String Type:SURFACE
Inspection Document:
·
Spec Document:
Tapered String Spec:
Casing Design Assumptions and Worksheet(s):
COG_Eider_105H_Casing_Prog_20171031083046.pdf
Casing ID: 2 String Type: INTERMEDIATE
Inspection Document:
~
Spec Document:
Tapered String Spec:
COG_Eider_105H_Casing_Prog_20171031083259.pdf
Casing Design Assumptions and Worksheet(s):
COG_Eider_105H_Casing_Prog_20171031083514.pdf
Inspection Document:
Spec Document:
Tapered String Spec:
Casing Design Assumptions and Worksheet(s):
ousing boolgn Assumptions and moreaneeds).
COG_Eider_105H_Casing_Prog_20171031083524.pdf

Section 4 - Cement

Operator Name: COG PRODUCTION LLC Well Name: EIDER FEDERAL

Well Number: 105H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	980	400	1.75	13.5	700	50	Class C	4% Gel + 1% CaCl2
SURFACE	Tail			980	250	1.34	14.8	335	50	Class C	2% CaCl2
INTERMEDIATE	Lead	s	980	4875	930	2	12.7	1860	50	Lead: 35:65:6 C Blend	As needed.
INTERMEDIATE	Tail		· ·	4875	250	1.34	14.8	335	50	Tail: Class C	2% CaCl
PRODUCTION	Lead		4875	1650 7	610	2.5	11.9	1525	25	Lead: 50:50:10 H Blend	As needed.
PRODUCTION	Tail			1650 7	1970	1.24	14.4	2442	25	Tail: 50:50:2 Class H Blend	As needed.

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

**Describe what will be on location to control well or mitigate other conditions:** Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirement will be kept on location at all times.

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring.

# **Circulating Medium Table**

Top Depth	Bottom Depth	Mud Type	Min Weight (Ibs/gal)	Max Weight (Ibs/gal)	Density (Ibs/cu ft)	Gel Strength (lbs/100 sqft)	Н	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
980	4875	OTHER : Saturated Brine	10	10.1							Saturated Brine
4875	1650 7	OTHER : Cut Brine	8.6	9.3							Cut Brine
0	980	OTHER : FW Gel	8.6	8.8							FW Gel

Page 4 of 6

Operator Name: COG PRODUCTION LLC Well Name: EIDER FEDERAL

Well Number: 105H

### Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures: None planned.

List of open and cased hole logs run in the well:

OTH

Other log type(s):

CNL/GR

Coring operation description for the well: None planned.

### **Section 7 - Pressure**

Anticipated Bottom Hole Pressure: 4490

Anticipated Surface Pressure: 2447.73

Anticipated Bottom Hole Temperature(F): 150

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

**Contingency Plans geohazards attachment:** 

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

COG\_Eider\_105H\_H2S\_Plan\_20171031084610.pdf COG\_Eider\_105H\_H2S\_Schematic\_20171031084618.pdf

### Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

COG\_Eider\_105H\_Direct\_Plan\_20171031084639.pdf COG\_Eider\_105H\_AC\_Rpt\_20171031084647.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

COG\_Eider\_105H\_Drill\_Prog\_20171031084659.pdf

Other Variance attachment:





# 3,000 psi BOP Schematic



Check Valve

TechnipFMC

TECHNIP Umbilicals Inc. COFLEXIP® Products and Solutions

### **Quality Control Department**

Control Report Dated 6/27/2017

076 60414 05 05

# **COFLEXIP®** Products and Solutions FLEXIBLE PIPE TEST CERTIFICATE

Customer OFS CANADA INC Line Number L16883

Line Serial Number L16883-201

Part Number

Application 3" X 30' 10K CHOKE / KILL LINE

COFLEXIP® Products Division certifies that the results of the test and controls performed on the above mentioned flexible pipe is as follows:

Internal Diameter	3	inches	
Length	30.46	feet	
Working Pressure	10000	psi	QUALITY COA
Test Pressure	15000	psi	Accept
As per attached recorder chart	4	hours	C P 'echnipri
Test Duration			

THIRD PARTY INSPECTION FIRM OR CUSTOMER REPRESENTATIVE

DQAC 1124 Rev 4 17 Apr 17

TU-INC. QUALITY CONTROL

Date Printed: 6/28/2017 8:56:23 AM

Vcts an

### **Test Configuration 12 Zone**

Line S/N	Technician	
116883-201	JUAN	
QC Information Input	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·
QC Imsp	Third Party	
ABEL	BV	
Witness?	Test Proced	ure
Yes	50.0160	· • -
Special Instructions		
÷ ·		

Station Information		Station 05	Calibration	
Pressure Transducer S/N	Temperature S/N	]	Raw Maximum	Eng Minimum
117854	TLEA		0.000000	0,00000
Stable Press	Test Press		Raw Maximum	Eng Maximum anno contro
Calls Day	Pressure Range			
10/18/2017 8-46-42 AM	0 - 30000	1 1		Pressure 1
N Grade		1		TempSite
A THE MILLION	สียนน้ำมากการค	<u></u>	national and	Charling and State
				29
1100 Hitti	addin in Eineachair			
	╫╖╡┷┿┥╋╋┯╴┽┑┿╊┿┥╺╍┥┠╼┥╌			
<b>编</b> 定目10月21	计方法 化动脉			10
ZICO-	- * • • • • • • • • • • • • • • • • • •	* ********		110
We want at a stand a stand	· • • • • • • • • • • • • • • • • • • •	╎┿┶╍╸┥┥╏╘╧┩╎┢┥┨┑┑┠┦┝	<b>┊┼╾┝┵╅╎</b> ╪╎┽╡╼┨╎╿┙╎╅╸┠╌╍┧╸╸	
10.11 10.11	<ul> <li>attractional</li> </ul>			
			╎╎╷┿┯┧┫┯┼╎╎╷┯┥┥┥┙╽	53
			OTTAL CON	N Sec
10000-11-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	<b>┙</b> ┥┽┽┽╴┠╍┽╌╋╸┥╵╻╸┥┝╢╼╷┧╸		1/100	
	المنطالة استراسا المطالح			UNTITUT 258
		stell.	6	-5
		100 10	181	18
<b>400</b>	╔╷╠╪╬╋┿╪╍┥╸╾┽╼┽╡╵╎╖┥╷	16-68-11		<i>§</i>
			Pourts and	11111111111111
			1	
A MA 0006 MA 0008	3000 AM _100000 AM _103000 AM	11:00:00 AM 11:30:00 AM 12	10000 PM 12-3050 PM 140000 PM	A 1-10-00 PM 20000 PM
" (20/20)" " (20/20)" * (	(1)/01) (10)/02) (10)/01/01/01/01/01/01/01/01/01/01/01/01/01/	<ul> <li>(41)/10) * (41)/10) * (4</li> </ul>	מהקנהש למצקניש לנוגיק הא	() (COLUMN ) (COLUMN))

Ŷ,

٩

# 2,000 psi BOP Schematic



**TechnipFMC** 

TECHNIP Umbilicais Inc. COFLEXIP® Products and Solutions **Quality Control Department** 

Control Report Dated 6/27/2017

# **COFLEXIP®** Products and Solutions **FLEXIBLE PIPE TEST CERTIFICATE**

Customer OFS CANADA INC Line Number

Line Serial Number L16883-201

Part Number

076 60414 05 05

L16883

Application 3" X 30

3" X 30' 10K CHOKE / KILL LINE

COFLEXIP® Products Division certifies that the results of the test and controls performed on the above mentioned flexible pipe is as follows:

Internal Diameter	3	inches	
Length	30.46	feet	
Working Pressure	10000	psi	QUALITY COAR
Test Pressure	15000	psi	Accept 7
As per attached recorder chart	4	hours	Contraction of the second
			Poducts and Solution

THIRD PARTY INSPECTION FIRM OR CUSTOMER REPRESENTATIVE

DQAC 1124 Rev 4 17 Apr 17

TU-INC. QUALITY CONTROL

Date Printed: 8/28/2017 8:56:23 AM

# Fest Configuration 12 Zone

1	09 10 225
	Test Procedure
k Lun	AB <sup>1</sup>
	Atria built
·	NVNI
····	Technician
· · · ·	'- - 

20 noitet2

	č.	ų,		0		<b>1</b> 5	T	19	Ē	1 	( <b>M</b>	40 Ti		Ti	1	ti Ti	-		π III		TT	11	FT TT		ĩ			<b>n</b> 11	11		OF	91 77			1	T I	t TT			1		1	N I		ж П			-1		20) (14
e	[!]	ļį	l			1		1				ł		1	1	1	1				1		li	1	1	1		1	:	Į.	1	ll	ij			li	Ľ		1	1		i,	E	Ľ		Ľ				
THE		h			1		1	3		1	4	7	R	>	Ś		r L				1	ŀ	J	İ.	ľ			1	1		;	İt	1		1	1	1			i	1	ŝ	4	.,	J		ł.		.,	
Ċ.	[.]	Г		Ī	1	7	1	]	[]		Þ	í.		N	3	٨	J		Ć	/		P	7	7	2	2		h	Ţ	•	1	1	1	1	Ţ.	þ	1			1	I	I	1	1	1			-	e vi Na p	ŝ
	П	T	1	Ē	[	1	Ţ	TI	Π	1	Ī	Π	h	1	ľ	3	I		1		2	Ż	/	7	۶	Y	7	đ	;		1	5		1	l	;	t t			-	Ĩ	1	1		1	5		-00	4. j	4
6	h	i	ī	T	١	X	ij	1	2	-	-	Ń		ł.	1	h	ŀ	T	1	1	1	1	ī	i.	1	tļ	Γİ	-	÷		T	Ľ.	ί		ľ	Г	•		ļij	- 1	1	il	1	ĥ	1		T,	•	ġ	
Ĉ.	H	ť		T		V	ò	Ś	12	Ņ	z	1) T	Ż	4	/	f	ł		ľ	1	ť	ť	İI	it	ţ	ţ		-i	1		t	ŀ		T	t	t				-1		h	ŀ	ſ	Ť		I	-00		e,
a St		+	1	╫		4	1		2	1	11	5	-	1	1	ţ			1		H	ŧ	11 11	ŧ	t	#	H	+÷	4	T	ť	<u>ب</u>	÷	÷	╀	+-	4	ļ,	1	1	ł		┞	Ľ.	1	H	+-	8	ų,	ŝ
ម្ពុក្ខ័	H	1	ĥ				4	H		t	11	#	ŗ.	ł	1		1		1			1		H		$\frac{1}{1}$	μ	÷	1		11	1	÷	4	╞	Ļ				#	ł	1	ţ	-	4	ŀ	H	28 ×	зÌ	į
IF.		4	Ľ	11	!!		Ľ	Ц		1		ļ	Ц.	1	ļį	Ľ	1	Ш	ļ	1	IJ	4	Ц	<u>   </u>	Ľ	1	2	4				Ц	-	1	ļ	Ļ	U.		4	Ц	ų	ļ	ii.	μ.	Ļ	4	-	×		į,
	H	ł	li		r;	:11	ļ.	#	H	_		ļ	Щ	#	1		1		1	1	+	H	∦			H	Ц	1	Ļ	4		ļÌ		1	ľ	ŀ	1	Ц	-	-	-1		Ļ.	÷		4	+	-00	I.	ie V
Contraction of the second seco		i. tr	1	Ľ		-	Ľ,	4	++	_	1	İ.			ii H	4	4			4	Ц	Ц	ij	H		Ľ		-1 -+-	4		H	ļ.	1	ή.	Ļ	ļ.		Ц		- 1 - 4	+	÷	r.	• -  +-	1. ≁f	-	1	- 00		2
	Ľ	ļį,	Ц					4	+]			ji tr	Ľ	H	1	1	1	1	-	ľ	4	11	Ц	1	1	-	1	-	1.	-	1		•	'   †1	.	Ľ						1	, tr	, i	1	_	4	8	-	1
м ш		1	ľ	li		ļ				1		l	ŀ,		I	l			1		l	1	$\ $			1;		j	1		ļ		1	1		Ľ		1		L	! _!!	1.	, i .1	Ľ.	••		!			
<u>E</u>	li		It			I	1		Í	1	li			I	1				ľ		I	ļĮ	1	i l	ļ		1	ļ	-		1	1	т. 		I	1	t j		;	1		1.	1	ľ	ļ					4
i i i	[]		i'				4	]	[],		Ī	1	1	ļ					İı	Γ,	Π	Ī	I		T	ļ.		;	1	I	li	1	i		ľ	i	Î			•	ï.		ľ,		. •	. 1	1.		È	Á
Circle Gircle	i,		11 11		Ì	-11	Ť	Ì		ľ	l	İ		il		ļ	I			ļ	İ	H	Ħ	ļ	;				1		t	t	1	Ī	ŀ	ľ			÷	+		ii 11	1	ſ,	Ħ		T	B SE		
	1	1.c	ſ			<u></u>	**	*	±	÷	<u>.</u>		-	ينه	*	<u></u>	÷		-	*		¥	<u> </u>								ź	==	-				-		-	÷	-	-	=		<u></u>		**		÷	1. 141
		- 20															•											Γ									2													
			1				_												I																é		1	-		4								1	HC/U	4

0000000

~•

Colline Itaw Manun Colline

```

ALLT

N/S AD

N/5 #

| Hole Size | From | asing 🕠 | Çsg. Sl | ze  | Weight<br>(lbs) | Grade    | Conn.  | SF.<br>Collapse | SF Burst | SF<br>Tension      |
|-----------|------|---------|---------|-----|-----------------|----------|--------|-----------------|----------|--------------------|
| 17.5"     | 0    | 980     | 13.375  | 5"  | 54.5            | J55      | STC    | 2.52            | 1.27     | 9.62               |
| 12.25"    | 0    | 4000    | 9.625   |     | 40              | J55      | LTC    | 1.22            | 1.11     | 3.25               |
| 12.25"    | 4000 | 4875    | 9.625   | ;"  | 40              | L80      | LTC    | 1.21            | 1.62     | 5.73               |
| 8.75"     | ·* 0 | 16,507  | 5.5"    |     | 17              | P110     | LTC    | 1.67            | 2.99     | 2.82               |
|           |      | -       |         | BLM | Minimur         | n Safety | Factor | 1.125           | 1        | 1.6 Dry<br>1.8 Wet |

| Hole Size | C:<br>From | asing<br>Tor | Csg. Si | ze. | Weight<br>(Ibs) | Grade    | Çonn:  | SF<br>Collapse | SF Burst | SF<br>Tension      |
|-----------|------------|--------------|---------|-----|-----------------|----------|--------|----------------|----------|--------------------|
| 17.5"     | 0          | 980          | 13.375  | 5"  | 54.5            | J55      | STC    | 2.52           | 1.27     | 9.62               |
| 12.25"    | 0          | 4000         | 9.625"  | "   | 40              | J55      | LTC    | 1.22           | 1.11     | 3.25               |
| 12.25"    | 4000       | 4875         | 9.625"  | 1   | 40              | L80      | LTC    | 1.21           | 1.62     | 5.73               |
| 8.75"     | 0          | 16,507       | 5.5"    |     | 17              | P110     | LTC    | 1.67           | 2.99     | 2.82               |
|           |            |              |         | BLM | Minimun         | n Safety | Factor | 1.125          | 1        | 1.6 Dry<br>1.8 Wet |

| Hole Size | Erom | asing i 🔗 | Csg. Size | Weight<br>(lbs) | Grade    | Conn     | SF<br>Collapse | SF(Burst) | SF.<br>Tension     |
|-----------|------|-----------|-----------|-----------------|----------|----------|----------------|-----------|--------------------|
| 17.5"     | 0    | 980       | 13.375"   | 54.5            | J55      | STC      | 2.52           | 1.27      | 9.62               |
| 12.25"    | 0    | 4000      | 9.625"    | 40              | J55      | LTC      | 1.22           | 1.11      | 3.25               |
| 12.25"    | 4000 | 4875      | 9.625"    | 40              | L80      | LTC      | 1.21           | 1.62      | 5.73               |
| 8.75"     | 0    | 16,507    | 5.5"      | 17              | P110     | LTC      | ' 1.67         | 2.99      | 2.82               |
|           |      |           | BLM       | 1 Minimur       | n Safety | / Factor | 1.125          | 1         | 1.6 Dry<br>1.8 Wet |

| Hole Size | C.<br>From | asing<br>To | Csg. Si | ze, | Weight<br>(Ibs) | Grade    | Conn.  | SF<br>Collapse | SF Burst | SF<br>Tension      |
|-----------|------------|-------------|---------|-----|-----------------|----------|--------|----------------|----------|--------------------|
| 17.5"     | 0          | 980         | 13.375  | 5"  | 54.5            | J55      | STC    | 2.52           | 1.27     | 9.62               |
| 12.25"    | 0          | 4000        | 9.625   | "   | 40              | J55      | LTC    | 1.22           | 1.11     | 3.25               |
| 12.25"    | 4000       | 4875        | 9.625   | 17  | 40              | L80      | LTC    | 1.21           | 1.62     | 5.73               |
| 8.75"     | 0          | 16,507      | 5.5"    |     | 17              | P110     | LTC    | 1.67           | 2.99     | 2.82               |
|           |            |             |         | BLM | Minimun         | n Safety | Factor | 1.125          | 1        | 1.6 Dry<br>1.8 Wet |

1

### **1. Geologic Formations**

| MD at TD: 16 507' Deepest expected fresh water: 380 | TVI | D of target | 9,280' EOL | Pilot hole depth              | NA   |
|-----------------------------------------------------|-----|-------------|------------|-------------------------------|------|
| The at TD: To,007 Deepeat expected fresh water. 300 | MD  | at TD:      | 16,507'    | Deepest expected fresh water: | 380' |

| Formation            | Depth (TVD)<br>from KB | Water/Mineral Bearing/<br>Target Zone? | ∺ Hazards* |
|----------------------|------------------------|----------------------------------------|------------|
| Quaternary Fill      | Surface                | Water                                  |            |
| Rustler              | 953                    | Water                                  |            |
| Top of Salt          | 1286                   | Salt                                   |            |
| Base of Salt         | 4620                   | Salt                                   |            |
| Lamar                | 4848                   | Salt Water                             |            |
| Bell Canyon          | 4889                   | Salt Water                             |            |
| Cherry Canyon        | 5798                   | Oil/Gas                                |            |
| Brushy Canyon        | 7178                   | Oil/Gas                                |            |
| Bone Spring Lime     | 8820                   | Oil/Gas                                |            |
| U. Avalon Shale      | 9165                   | Oil/Gas                                |            |
| L. Avalon Shale      | 9345                   | Not Penetrated                         |            |
| 1st Bone Spring Sand | Х                      | Not Penetrated                         |            |
| 2nd Bone Spring Sand | Х                      | Not Penetrated                         | -          |
| 3rd Bone Spring Sand | X                      | Not Penetrated                         |            |
| Wolfcamp             | Х                      | Not Penetrated                         |            |

### 2. Casing Program

| Hole Size | C<br>From | asing<br>To | Csg. Size | Weight<br>(Ibs) | Grade    | Conn.  | SF<br>Collapse | SF Burst | SF<br>Tension      |
|-----------|-----------|-------------|-----------|-----------------|----------|--------|----------------|----------|--------------------|
| 17.5"     | 0         | 980         | 13.375"   | 54.5            | J55      | STC    | 2.52           | 1.27     | 9.62               |
| 12.25"    | 0         | 4000        | 9.625"    | 40              | J55      | LTC    | 1.22           | 1.11     | 3.25               |
| 12.25"    | 4000      | 4875        | 9.625"    | 40              | L80      | LTC    | 1.21           | 1.62     | 5.73               |
| 8.75"     | 0         | 16,507      | 5.5"      | 17              | P110     | LTC    | 1.67           | 2.99     | 2.82               |
|           |           |             | BL        | M Minimun       | n Safety | Factor | 1.125          | 1        | 1.6 Dry<br>1.8 Wet |

Intermediate casing will be kept at least 1/3 full while running casing to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface.

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

1

|                                                                                                                                                  | Yor N  |
|--------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Is casing new? If used, attach certification as required in Onshore Order #1                                                                     | Y      |
| Does casing meet API specifications? If no, attach casing specification sheet.                                                                   | Ý      |
| Is premium or uncommon casing planned? If yes attach casing specification sheet.                                                                 | N      |
| Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria). | Y      |
| Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching                                                            |        |
| the collapse pressure rating of the casing?                                                                                                      |        |
|                                                                                                                                                  |        |
| Is well located within Capitan Reef?                                                                                                             | N      |
| If yes, does production casing cement tie back a minimum of 50' above the Reef?                                                                  |        |
| Is well within the designated 4 string boundary?                                                                                                 | ,      |
|                                                                                                                                                  |        |
| Is well located in SOPA but not in R-111-P?                                                                                                      | N      |
| If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?                       |        |
|                                                                                                                                                  | BESKIM |
| Is well located in R-111-P and SOPA?                                                                                                             | N      |
| If yes, are the first three strings cemented to surface?                                                                                         |        |
| Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?                                                                               |        |
|                                                                                                                                                  |        |
| Is well located in high Cave/Karst?                                                                                                              | N      |
| If yes, are there two strings cemented to surface?                                                                                               |        |
| (For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?                                                           |        |
|                                                                                                                                                  |        |
| Is well located in critical Cave/Karst?                                                                                                          | N      |
| If ves, are there three strings cemented to surface?                                                                                             |        |

2

### 3. Cementing Program

| Ćasing)  | #Sks | Wt. Ib/<br>gal | Yld ft3/<br>sack | H <sub>2</sub> 0 gal/sk | 500# Comp<br>Strength<br>(hours) | Slurry Description                |
|----------|------|----------------|------------------|-------------------------|----------------------------------|-----------------------------------|
| Sumf     | 400  | 13.5           | 1.75             | 9                       | 12                               | Lead: Class C + 4% Gel + 1% CaCl2 |
| Surt.    | 250  | 14.8           | 1.34             | 6.34                    | 8                                | Tail: Class C + 2% CaCl2          |
| Inter    | 930  | 12.7           | 2.0              | 9.6                     | 16                               | Lead: 35:65:6 C Blend             |
| muer.    | 250  | 14.8           | 1.34             | 6.34                    | 8                                | Tail: Class C + 2% CaCl           |
|          | 610  | 11.9           | 2.5              | 19                      | 72                               | Lead: 50:50:10 H Blend            |
| 5.5 Prod | 1970 | 14.4           | 1.24             | 5.7                     | 19                               | Tail: 50:50:2 Class H Blend       |

Volumes Subject to Observed Hole Conditions and/or Fluid Caliper Results Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

| Casing String ≥              | TOC    | % Excess                                            |
|------------------------------|--------|-----------------------------------------------------|
| Surface                      | 0'     | 50%                                                 |
| 1 <sup>st</sup> Intermediate | 0'     | 50%                                                 |
| Production                   | 3,500' | 25% OH in Lateral (KOP to EOL) – 40% OH in Vertical |

## 4. Pressure Control Equipment

A variance is requested for the use of a diverter on the surface casing. Ν See attached for schematic.

| BOP installed and<br>tested before<br>drilling which<br>hole? | Size?   | Min.<br>Required<br>WP | ту         | pe   | × | Tested<br>to:              |
|---------------------------------------------------------------|---------|------------------------|------------|------|---|----------------------------|
|                                                               |         |                        | Ann        | ular | х | 2000 psi                   |
|                                                               | :       |                        | Blind      | Ram  |   |                            |
| 12-1/4"                                                       | 13-5/8" | 2M                     | Pipe Ram   |      |   | 2M                         |
|                                                               |         |                        | Double Ram |      |   |                            |
|                                                               |         |                        | Other*     |      |   |                            |
|                                                               |         |                        | Ann        | ular | X | 50%<br>testing<br>pressure |
| 8-3/4"                                                        | 13-5/8" | 3M                     | Blind Ram  |      | х |                            |
|                                                               |         |                        | Pipe Ram   |      | х | 214                        |
|                                                               |         |                        | Double Ram |      |   |                            |
|                                                               |         | · · ·                  | Other*     |      |   |                            |

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

|   | Formation integrity test will be performed per Onshore Order #2.                                                                                                                                                                                                   |
|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Х | On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.                          |
| Y | A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.                                                                                                                    |
|   | N Are anchors required by manufacturer?                                                                                                                                                                                                                            |
| N | A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. |

October 19, 2017

### 5. Mud Program

|                 | Depth 🖉 🙀       | Type            | Weight    | Viscosity | Water Loss |
|-----------------|-----------------|-----------------|-----------|-----------|------------|
| From            | То              |                 | (ppg)     |           |            |
| 0               | Surf. Shoe      | FW Gel          | 8.6 - 8.8 | 28-34     | N/C        |
| Surf csg        | 9-5/8" Int shoe | Saturated Brine | 10 - 10.1 | 28-34     | N/C        |
| 9-5/8" Int shoe | Lateral TD      | Cut Brine       | 8.6 - 9.3 | 28-34     | N/C        |

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

| What will be used to monitor the loss or gain of fluid? | PVT/Pason/Visual Monitoring |
|---------------------------------------------------------|-----------------------------|
|---------------------------------------------------------|-----------------------------|

# 6. Logging and Testing Procedures

| Logging, Coring and Testing. |                                                                    |  |  |
|------------------------------|--------------------------------------------------------------------|--|--|
|                              | Will run <sup>c</sup> GR/CNL from TD to surface (horizontal well – |  |  |
| Y                            | vertical portion of hole). Stated logs run will be in the          |  |  |
|                              | Completion Report and submitted to the BLM.                        |  |  |
| v                            | No Logs are planned based on well control or offset log            |  |  |
|                              | information.                                                       |  |  |
| N .                          | Drill stem test? If yes, explain.                                  |  |  |
| N                            | Coring? If yes, explain.                                           |  |  |

| Additional logs planned |             | Interval                                                   |  |  |  |  |
|-------------------------|-------------|------------------------------------------------------------|--|--|--|--|
| Ν                       | Resistivity | Pilot Hole TD to ICP                                       |  |  |  |  |
| Ν                       | Density     | Pilot Hole TD to ICP                                       |  |  |  |  |
| Y                       | CBL         | Production casing<br>(If cement not circulated to surface) |  |  |  |  |
| Y                       | Mud log     | Intermediate shoe to TD                                    |  |  |  |  |
| Ν                       | PEX         |                                                            |  |  |  |  |

### 7. Drilling Conditions

| <b>Condition</b>           | Specify what type and where? |
|----------------------------|------------------------------|
| BH Pressure at deepest TVD | 4490 psi at 9280' TVD        |
| Abnormal Temperature       | NO 150 Deg. F.               |

No abnormal pressure or temperature conditions are anticipated. Sufficient mud materials to maintain mud properties and weight increase requirements will be kept on location at all times.

Sufficient supplies of Paper/LCM for periodic sweeps to control seepage and losses will be maintained on location.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

N H2S is present

Y H2S Plan attached

### 8. Other Facets of Operation

| Y | Is it a walking operation? |
|---|----------------------------|
| N | Is casing pre-set?         |

| x | H2S Plan.               |
|---|-------------------------|
| × | BOP & Choke Schematics. |
| x | Directional Plan        |

# 7AFMSS

U.S. Department of the Interior **BUREAU OF LAND MANAGEMENT** 

### APD ID: 10400023748

**Operator Name: COG PRODUCTION LLC** 

Well Name: EIDER FEDERAL

Well Type: OIL WELL

# Submission Date: 10/31/2017

Well Number: 105H

Highlighted data reflects the most recent changes

05/23/2018

Show Final Text

Well Work Type: Drill

# Section 1 - Existing Roads

Will existing roads be used? YES

**Existing Road Map:** 

COG\_Eider\_105H\_Existing\_Road\_20171031084714.pdf

Existing Road Purpose: ACCESS, FLUID TRANSPORT

ROW ID(s)

ID: NM132549

Do the existing roads need to be improved? NO

**Existing Road Improvement Description:** 

**Existing Road Improvement Attachment:** 

# Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

COG Eider 105H Maps Plats 20171031084738.pdf

New road type: RESOURCE

Length: 4953.6

Width (ft.): 30

Max slope (%): 33

Max grade (%): 1

Army Corp of Engineers (ACOE) permit required? NO

Feet

ACOE Permit Number(s):

New road travel width: 14

New road access erosion control: Water will be diverted where necessary to avoid ponding, prevent erosion, maintain food drainage, and to be consistent with local drainage patterns. New road access plan or profile prepared? NO

New road access plan attachment:

Access road engineering design? NO

Access road engineering design attachment:

Row(s) Exist? YES

SUPO Data Report



Well Name: EIDER FEDERAL

#### Well Number: 105H

Access surfacing type: OTHER

Access topsoil source: ONSITE

Access surfacing type description: Caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: Blading

Access other construction information: No turnouts are planned. Re-routing access road around proposed well location.

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

### **Drainage Control**

New road drainage crossing: CULVERT, OTHER

Drainage Control comments: None necessary.

Road Drainage Control Structures (DCS) description: None needed.

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

# Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

COG\_Eider\_105H\_1\_Mile\_Data\_20171031084917.pdf

**Existing Wells description:** 

# Section 4 - Location of Existing and/or Proposed Production Facilities

### Submit or defer a Proposed Production Facilities plan? DEFER

**Estimated Production Facilities description:** Production will be sent to the proposed Eider CTB 2, A surface flow line of approximately 1417.9' of 3.5" steel pipe carrying oil, gas and water under a maximum pressure of 125 psi will follow the road to the facility at the Eider CTB 2 location. We plan to install a 4" surface polyethylene pipe transporting Gas Lift Gas from the Eider CTB 2 to the Eider Federal 105H. The surface Gas Lift Gas pipe of approximately 1417.9' under a maximum pressure of 125 psi will be installed no farther than 10 feet from the edge of the road.

Well Name: EIDER FEDERAL

Well Number: 105H

| Water Source Table                                                                                                      |                                       |
|-------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| Water source use type: ICE PAD CONSTRUCTION &<br>MAINTENANCE, STIMULATION, SURFACE CASING<br>Describe type: Fresh Water | Water source type: OTHER              |
| Source latitude:                                                                                                        | Source longitude:                     |
| Source datum:                                                                                                           |                                       |
| Water source permit type: PRIVATE CONTRACT,PRIVATE<br>CONTRACT<br>Source land ownership: PRIVATE                        |                                       |
| Water source transport method: PIPELINE, PIPELINE                                                                       |                                       |
| Source transportation land ownership: PRIVATE                                                                           |                                       |
| Water source volume (barrels): 337500                                                                                   | Source volume (acre-feet): 43.50142   |
| Source volume (gal): 14175000                                                                                           |                                       |
| Water source use type: INTERMEDIATE/PRODUCTION CASING                                                                   | Water source type: OTHER              |
| Describe type: Brine Water                                                                                              |                                       |
| Source latitude:                                                                                                        | Source longitude:                     |
| Source datum:                                                                                                           |                                       |
| Water source permit type: PRIVATE CONTRACT,PRIVATE<br>CONTRACT<br>Source land ownership: COMMERCIAL                     |                                       |
| Water source transport method: TRUCKING,TRUCKING                                                                        |                                       |
| Source transportation land ownership: COMMERCIAL                                                                        |                                       |
| Water source volume (barrels): 22500                                                                                    | Source volume (acre-feet): 2.9000947  |
| Source volume (gal): 945000                                                                                             |                                       |
|                                                                                                                         |                                       |
|                                                                                                                         |                                       |
| C_Eider_105H_Erach_H2O_20171031085117.pdf                                                                               | · · · · · · · · · · · · · · · · · · · |

Water source comments: The fresh water will be obtained from Mark McCloy water well located in Section 33, T24S, R33E, or from Rock House Ranch (575) 885-4195, Brine water will be purchased from Mesquite Services (575) 887-4847. No water well will be drilled on the location. New water well? NO

### New Water Well Info

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

| Operator Name: COG PRODUCTION LLC | 2 |
|-----------------------------------|---|
|-----------------------------------|---|

١.,

Well Name: EIDER FEDERAL

Well Number: 105H

| Est. depth to top of aquifer(ft):   | Est thickness of aquifer:          |
|-------------------------------------|------------------------------------|
| Aquifer comments:                   |                                    |
| Aquifer documentation:              |                                    |
| Well depth (ft):                    | Well casing type:                  |
| Well casing outside diameter (in.): | Well casing inside diameter (in.): |
| New water well casing?              | Used casing source:                |
| Drilling method:                    | Drill material:                    |
| Grout material:                     | Grout depth:                       |
| Casing length (ft.):                | Casing top depth (ft.):            |
| Well Production type:               | Completion Method:                 |
| Water well additional information:  |                                    |
| State appropriation permit:         |                                    |
| Additional information attachment:  |                                    |
|                                     |                                    |

### **Section 6 - Construction Materials**

Construction Materials description: Caliche will be obtained from the actual well site. If caliche does not exist or is not plentiful from the well site, the caliche will be hauled from Mack Chase caliche pit located in Section 20, T24S, R33E. (575) 748-1288.

**Construction Materials source location attachment:** 

### Section 7 - Methods for Handling Waste

Waste type: SEWAGE

Waste content description: Human waste and gray water.

Amount of waste: 1000 gallons

Waste disposal frequency : One Time Only

Safe containment description: Waste will be properly contained and disposed of properly at a state approved disposal facility.

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: PRIVATE

FACILITY

**Disposal type description:** 

Disposal location description: Trucked to an approved disposal facility.

Waste type: DRILLING

Waste content description: Drilling fluids and produced oil land water while drilling and completion operations.

Amount of waste: 6000 barrels

Waste disposal frequency : One Time Only

Safe containment description: All drilling waste will be stored safely and disposed of properly.

Well Name: EIDER FEDERAL

Well Number: 105H

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL FACILITY

Disposal type description:

**Disposal location description:** Trucked to an approved disposal facility.

Waste type: GARBAGE

Waste content description: Garbage and trash produced during drilling and completion operations.

Amount of waste: 500 pounds

Waste disposal frequency : One Time Only

**Safe containment description:** Garbage and trash produced during drilling and completion operations will be collected in a trash container and disposed of properly at a state approved disposal facility. **Safe containmant attachment:** 

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL FACILITY

Disposal type description:

**Disposal location description:** Trucked to an approved disposal facility.

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit?

Reserve pit length (ft.) Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

**Cuttings Area** 

Cuttings Area being used? NO

Are you storing cuttings on location? YES

Description of cuttings location Roll off cutting containers on tracks.

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Well Name: EIDER FEDERAL

Well Number: 105H

### Cuttings area liner specifications and installation description

**Section 8 - Ancillary Facilities** 

Are you requesting any Ancillary Facilities?: YES

### Ancillary Facilities attachment:

COG\_Eider\_105H\_GCP\_20171031085250.pdf

Comments: GCP Attached.

### Section 9 - Well Site Layout

### Well Site Layout Diagram:

COG Eider 105H CTB Flowlines 20171031085312.pdf

COG\_Eider\_105H\_Prod\_Facility\_20171031085322.pdf

COG\_Eider\_CTB\_2\_20171031085346.pdf

**Comments:** Production will be sent to the proposed Eider CTB 2, A surface flow line of approximately 1417.9' of 3.5" steel pipe carrying oil, gas and water under a maximum pressure of 125 psi will follow the road to the facility at the Eider CTB 2 location. We plan to install a 4" surface polyethylene pipe transporting Gas Lift Gas from the Eider CTB 2 to the Eider Federal 105H. The surface Gas Lift Gas pipe of approximately 1417.9' under a maximum pressure of 125 psi will be installed no farther than 10 feet from the edge of the road.

# Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: EIDER FEDERAL

Multiple Well Pad Number: 105H, 205H, 106H, 305H, 306H, 206H

**Recontouring attachment:** 

**Drainage/Erosion control construction:** If needed, immediately following pad construction approximately 400' of straw waddles will be placed on the west side of the location, 400' of straw waddles will be placed on the south side to reduce sediment impacts to fragile/sensitive soils.

Drainage/Erósion control reclamation: N/A

| Well pad proposed disturbance (acres):                                                  | Well pad interim reclamation (acres): 4.54                                                                                           | Well pad long term disturbance<br>(acres): 3.16                                                     |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Road proposed disturbance (acres):                                                      | Road interim reclamation (acres): 1.59                                                                                               | Road long term disturbance (acres):                                                                 |
| Powerline proposed disturbance<br>(acres):<br>Pipeline proposed disturbance<br>(acres): | Powerline interim reclamation (acres):<br>Pipeline interim reclamation (acres):<br>46.153362<br>Other interim reclamation (acres): 0 | Powerline long term disturbance<br>(acres):<br>Pipeline long term disturbance<br>(acres): 46.153362 |
| Total proposed disturbance:                                                             | Total interim reclamation: 52.28336                                                                                                  | Other long term disturbance (acres): 0<br>Total long term disturbance:<br>50.903362                 |

Disturbance Comments:

Well Name: EIDER FEDERAL

#### Well Number: 105H

**Reconstruction method:** Portions of the pad not needed for production operationswill be re-contoured to its original state as much as possible. The caliche that is removed will be reused. The stockpiled topsoil will be spread out over reclaimed area and reseeded with BLM approved seed mixture **Topsoil redistribution:** West 80'. East 60'

Soil treatment: None

Existing Vegetation at the well pad: Shinnery Oak/Mesquite grassland.

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: Shinnery Oak/Mesquite grassland.

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline: Shinnery Oak/Mesquite grassland.

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances: N/A

Existing Vegetation Community at other disturbances attachment:

Non native seed used? NO

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? NO

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? NO

Seed harvest description:

Seed harvest description attachment:

### Seed Management

### Seed Table

Seed type:

Seed name:

Source name:

Source phone:

Seed cultivar:

Seed use location:

Seed source:

Source address:

Well Number: 105H

PLS pounds per acre:

Proposed seeding season:

| Seed Summary |             |  |
|--------------|-------------|--|
| Seed Type    | Pounds/Acre |  |

Seed reclamation attachment:

### **Operator Contact/Responsible Official Contact Info**

First Name: Rand

Phone: (432)254-5556

Last Name: French Email: rfrench@concho.com

**Total pounds/Acre:** 

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? NO

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Weed treatment plan description: N/A

Weed treatment plan attachment:

Monitoring plan description: N/A

Monitoring plan attachment:

Success standards: N/A

Pit closure description: N/A

Pit closure attachment:

COG\_Eider\_105H\_Closed\_Loop\_20171031090055.pdf

### Section 11 - Surface Ownership

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

**BOR Local Office:** 

**COE Local Office:** 

Operator Name: COG PRODUCTION LLC Well Name: EIDER FEDERAL

Well Number: 105H

DOD Local Office: NPS Local Office: State Local Office: Military Local Office: USFWS Local Office: Other Local Office: USFS Region: USFS Forest/Grassland:

**USFS Ranger District:** 

### Section 12 - Other Information

Right of Way needed? NO ROW Type(s):

Use APD as ROW?

**ROW Applications** 

**SUPO Additional Information:** COG respectfully requests approval to build a 1000' x 1000' Gadwall 35 Federal Frac Pond 2 to serve this well and any other well within a two mile radius. The proposed frac pond is to be located in Section 35, T24S, R32E. Plats are attached.

Use a previously conducted onsite? YES

**Previous Onsite information**: Onsite conpleted on 8/22/2017 by Rand French (COG); Gerald Herrera (COG); and Jeff Robertson (BLM).

### **Other SUPO Attachment**

COG\_Gadwall\_Frac\_Pond\_2\_20171017065148.pdf COG\_Eider\_105H\_Certification\_20171031090117.pdf

## **ERATOR CERTIFICATION**

under my direct supervision, have inspected the drill site and I am familiar with the conditions that presently exist; that I nd Federal laws applicable to this operation; that the statements to the best of my knowledge, true and correct; and that the work proposed herein will be performed in conformity with this APD inditions under which it is approved. I also certify that I, or COG ible for the operations conducted under this application. These provisions of 18 U.S.C. 1001 for the filing of false statements.

23~

ÍQ

Artesia, NM 88210

ve signatory): Rand French -mail: rfrench@concho.com



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

# PWD Data Report

### **Section 1 - General**

Would you like to address long-term produced water disposal? NO

## **Section 2 - Lined Pits**

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

**PWD surface owner:** 

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

#### **PWD disturbance (acres):**

### Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

**Unlined Produced Water Pit Estimated percolation:** 

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

**PWD disturbance (acres):** 

PWD disturbance (acres):

Injection well type: Injection well number: Assigned injection well API number? Injection well new surface disturbance (acres): Minerals protection information: Mineral protection attachment: Underground Injection Control (UIC) Permit?

**UIC Permit attachment:** 

# Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location: PWD surface owner: Surface discharge PWD discharge volume (bbl/day): Surface Discharge NPDES Permit? Surface Discharge NPDES Permit attachment: Surface Discharge site facilities information: Surface discharge site facilities map:

### Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location: PWD surface owner: Other PWD discharge volume (bbl/day): Other PWD type description: Other PWD type attachment: Have other regulatory requirements been met?

Other regulatory requirements attachment:

### Injection well name:

#### Injection well API number:

Э

PWD disturbance (acres):

.

.

#### PWD disturbance (acres):

.

.

· .



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

### **Bond Information**

Federal/Indian APD: FED

BLM Bond number: NMB000860

**BIA Bond number:** 

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Bond Info Data Report

05/23/2018

Is the reclamation bond BLM or Forest Service?

**BLM reclamation bond number:** 

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

**Reclamation bond number:** 

**Reclamation bond amount:** 

**Reclamation bond rider amount:** 

Additional reclamation bond information attachment:

# **FAFMSS**

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

# Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Mayte Reyes

Title: Regulatory Analyst

Street Address: 2208 W Main Street

City: Artesia

State: NM

State: NM

Phone: (575)748-6945

Email address: Mreyes1@concho.com

### **Field Representative**

Representative Name: Rand French

Street Address: 2208 West Main Street

City: Artesia

Phone: (575)748-6940

Email address: rfrench@concho.com

Signed on: 10/20/2017

Derator Certification Data Report

05/23/2018

Zip: 88210

Zip: 88210