

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBES
JUL 03 2018
RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PERFORATE TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-26462
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator CROSS TIMBERS ENERGY, LLC		6. State Oil & Gas Lease No. 312471
3. Address of Operator 400 W 7TH ST, FORT WORTH, TX 76102		7. Lease Name or Unit Agreement Name SE MALJAMAR GB-SA
4. Well Location Unit Letter G : 2615 feet from the N line and 2615 feet from the E line Section 29 Township 17S Range 33E NMPM County LEA		8. Well Number 507
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4069 GR		9. OGRID Number 298299
		10. Pool name or Wildcat MALJAMAR;GRAYBURG-SAN ANDRES

12. Check ☐ to indicate Nature of Notice, Report or Other Data
Please provide current Wellbore Schematic.
File frac report w/Frac Focus ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ADD PAY ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.
05/18/2018 - Drilled out CIBP @ 4085'. Set CIPB @ 4150'
05/21/2018 - Perforated 4,088' - 4,091' (2 SPF, 6 shots) & 4096'-4098' (2 SPF, 4 shots). Acidized w/ 1700 gals 15% NEFE HCl & ball sealers.
05/23/2018 - Set CBP @ 4,025'. Perforate as follows:
3961' - 3963' (2 SPF, 4 shots)
3966' - 3970' (2 SPF, 8 shots)
3983' - 3985' (2 SPF, 4 shots)
3988' - 3992' (2 SPF, 8 shots)
3997' - 3999' (2 SPF, 4 shots)
4002' - 4007' (2 SPF, 10 shots)
05/24/2018 - Acidize 3961' - 4007' w/ 1550 gals 15% NEFE HCl & ball sealers.
06/22/2018 - Frac 3961' - 4007' w/ 83,000 gals 9# XL gel, 86,500 lbs 20/40 white sand, and 7,500 lbs Super LC sand.
06/27/2018 - Drill out CBP @ 4025'. Clean out to 4150' (left CIBP @ 4150').
06/28/2018 - RIH w/ tubing and rods. Put well on production.

Spud Date:

12/07/1979

Rig Release Date:

01/20/1980

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Connie Blaylock TITLE REGULATORY TECH DATE 06/29/2018

Type or print name CONNIE BLAYLOCK E-mail address: cblaylock@mspartners.com PHONE: 817-334-7882

For State Use Only

APPROVED BY: Karen Sharp TITLE Staff Mgr DATE 7-5-18

Conditions of Approval (if any):

See above