District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy, Minerals and Natural Resources Department

HOBBS OCD to Appropriate HOBBS OCD

**Submit Original** 

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

JUL 232018

Date: 07/23/2018	GAS CA	PTURE PL	AN	F	RECEIVED
☐ Original ☐ Amended - Reason for Amendme	•			-	S ENERGY, LLC 298299 AN ANDRES
This Gas Capture Plan outlines action new completion (new drill, recomple Note: Form C-129 must be submitted and	te to new zone, re-fra	ac) activity.			
Well(s)/Production Facility – Name  The well(s) that will be located at the	_	ara shown in	tha tabla ba'	low	
Well Name API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
STATE L 4 25-24393	D/21/17S/35E	660 FNL 660 FWL	5	0	CONNECTED TO SALES LINE
Cathoning System and Dinalina No.	kisi - a 4i		<u> </u>		

## Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place.
The gas produced from production facility is dedicated to Gas Transporter and will be connected to Gas Transporter low/high
pressure gathering system located in <u>LEA</u> County, New Mexico. It will require <u>0</u> of pipeline to connect the
facility to low/high pressure gathering system. Operator provides (periodically) to Gas Transporter a drilling, completion and
estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Operator and Gas
Transporter have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be
processed at Gas Transporter Processing Plant located in Sec, Twn, Rng, County, New Mexico. The
actual flow of the gas will be based on compression operating parameters and gathering system pressures.

## Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gas Transporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines