. <b>n</b>	UNITED STATES EPARTMENT OF THE IN	NTERIOR	OMB Expires	M APPROVED NO. 1004-0137 : January 31, 2018
SUNDRY	UREAU OF LAND MANA	RTS ON WERE CO IT	ield Offices Scrial No.	
Do not use th abandoned we	is form for proposals to II. Use form 3160-3 (API	drill or to re-emerand D) for such proposals	lobbs <sup>6.</sup> If Indian, Allotte	e or Tribe Name
SUBMIT IN	TRIPLICATE - Other inst		7: If Unit or CA/Ag	greement, Name and/or No.
1. Typc of Well  S Oil Well Gas Well Ot	her	AUG 1 6 2	018 8. Well Name and N SD EA 29 FED	
2. Name of Operator CHEVRON USA INC	Contact: E-Mail: LBECERR/		9. API Well No. 30-025-43269	9-00-X1
3a. Address 1616 W. BENDER BLVD HOBBS, NM 88240		3b. Phone No. (inchose area code) Ph: 432-687-7665	10. Field and Pool	or Exploratory Arca 263319P-BONE SPRIN
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description)	L	11. County or Paris	h, State
Sec 29 T26S R33E NWNE 136FNL 1657FEL				Y, NM
12 CHECK THE A	PPROPRIATE BOX(ES)	TO INDICATE NATURE O	NOTICE REPORT OR O	THER DATA
TYPE OF SUBMISSION	PPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION			
	Acidize	Deepen	Production (Start/Resume)	U Water Shut-Off
Notice of Intent	Alter Casing	Hydraulic Fracturing	Reclamation	Well Integrity
🛛 Subsequent Report	Casing Repair	New Construction	Recomplete	Other
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abandon	Drilling Operations
	Convert to Injection	Plug Back	Water Disposal	
testing has been completed. Final Al	bandonment Notices must be file	sults in a multiple completion or reco ed only after all requirements, includi	ng reclamation, have been complete	d and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface company surface casing. Bun 1	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5# J-55 casing	od only after all requirements, includi McCormick @ BLM of intent to 843'. Cement in place w cla	ng reclamation, have been complete	160-4 must be filed once and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surface	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.30#, 90 bbls cement to	d only after all requirements, includi McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F	ng reclamation, have been complete to run and ass C, 857 Float shoe @	160-4 must be filed once ad and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surface hole to 11,170'.	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.80#, 90 bbls cement to ace casing 2000PSI for 30	ed only after all requirements, includi McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in	ng reclamation, have been complete to run and ass C, 857 Float shoe @	160-4 must be filed once and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surface	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.50#, 90 bbls coment to ace casing 2000PSI for 30 rs @ BLM of intent to run	d only after all requirements, includi McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi	ng reclamation, have been complete to run and ass C, 857 Float shoe @ Intermediate	160-4 must be filed once and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.80#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, s true and correct. Electronic Submission #4 For CHE	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, Yl	ng reclamation, have been complete to run and ass C, 857 Float shoe @ htermediate ng. Run 9 5/8" d:2.41/sack,	I 60-4 must be filed once and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.30#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, s true and correct. Electronic Submission #4 For CHE nmitted to AFMSS for proce	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, Yl WRON USA INC, sent to the Ho ssing by PRISCILLA PEREZ or	ng reclamation, have been complete to run and ass C, 857 Float shoe @ htermediate ng. Run 9 5/8" d:2.41/sack,	I 60-4 must be filed once and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is Con	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.30#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, s true and correct. Electronic Submission #4 For CHE nmitted to AFMSS for proce	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, Yl WRON USA INC, sent to the Ho ssing by PRISCILLA PEREZ or	ng reclamation, have been complete to run and ass C, 857 Float shoe @ ntermediate ng. Run 9 5/8" d:2.41/sack,	160-4 must be filed once ed and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is Con	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.30#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, s true and correct. Electronic Submission #4 For CHE mmitted to AFMSS for proce	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, Yl WRON USA INC, sent to the Ho ssing by PRISCILLA PEREZ or	ng reclamation, have been complete to run and ass C, 857 Float shoe @ htermediate ng. Run 9 5/8" d:2.41/sack, Information System bbs 08/09/2018 (18PP1629SE) TING SPECIALIST	160-4 must be filed once ed and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is Name (Printed/Typed) LAURA BI	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.80#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, For CHE mitted to AFMSS for proce ECERRA	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, YI WRON USA INC, sent to the Ho essing by PRISCILLA PEREZ or Title PERMIT	ng reclamation, have been complete to run and ass C, 857 Float shoe @ ntermediate ng. Run 9 5/8" d:2.41/sack, Unformation System bbs 08/09/2018 (18PP1629SE) TING SPECIALIST	160-4 must be filed once ad and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is Name (Printed/Typed) LAURA BI	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.80#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, For CHE mitted to AFMSS for proce ECERRA	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, Yi WRON USA INC, sent to the Ho essing by PRISCILLA PEREZ or Title PERMIT Date 08/09/20	ng reclamation, have been complete to run and ass C, 857 Float shoe @ ntermediate ng. Run 9 5/8" d:2.41/sack, Unformation System bbs 08/09/2018 (18PP1629SE) TING SPECIALIST	Datc
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is Com Name (Printed/Typed) LAURA Bl Signature (Electronic S	bandonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 14.30#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, s true and correct. Electronic Submission #4 For CHE mmitted to AFMSS for proce ECERRA Submission) THIS SPACE FO	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, YI WRON USA INC, sent to the Ho essing by PRISCILLA PEREZ or Title PERMIT Date 08/09/20 PR FEDERAL OR STATE ( ACCEPTICED FOI not warrant or	ng reclamation, have been complete to run and ass C, 857 Float shoe @ ntermediate ng. Run 9 5/8" d:2.41/sack, Unformation System bbs 08/09/2018 (18PP1629SE) TING SPECIALIST	ed and the operator has
testing has been completed. Final Al determined that the site is ready for f Spud Dt: 10/20/2017 - Notified 10/20/2017- Drill 17.5" surface cement surface casing. Run 1 sacks, Yld:1.33/sacks, Dens:1 843'. 12/14/17-12/26/17 - Test surfa hole to 11,170'. 12/26/17- Notified Paul Flowe 43.5# HCL-80 LTC casing to 14. I hereby certify that the foregoing is Com Name ( <i>Printed/Typed</i> ) LAURA B Signature (Electronic S Approved By	andonment Notices must be file inal inspection. d Steve Caffey @ BLM e hole to 853'. Notified Jim 3-3/8" 54.5#, J-55 casing 4.30#, 90 bbls cement to ace casing 2000PSI for 30 rs @ BLM of intent to run 11,160'. Cement in place, For CHE mitted to AFMSS for proce ECERRA Submission) THIS SPACE FO d. Approval of this notice does uitable title to those rights in the ict operations thereon. U.S.C. Section 1212, make it a d	McCormick @ BLM of intent to 843'. Cement in place w cla surface. Float collar @ 797', F min, test good. Drill 12-1/4" in and cement intermediate casi Lead w/CL C, 1,591 sacks, Yl WRON USA INC, sent to the Ho essing by PRISCILLA PEREZ or Title PERMIT Date 08/09/20 PR FEDERAL OR STATE O ACCEPTIED FOI not warrant or subject lease OffAct 6 0 9 7 crime for any person knowingly and	ng reclamation, have been complete to run and ass C, 857 Float shoe @ Intermediate ng. Run 9 5/8" d:2.41/sack, Unformation System bbs 08/09/2018 (18PP1629SE) TING SPECIALIST D18 DFFICE USE RECORD 018 /s/ Jonat	Datc

•

## Additional data for EC transaction #430469 that would not fit on the form

## 32. Additional remarks, continued

Dens:11.90#/gal and Tail: CL H, 212 sacks, Yld:1.33/sack, Dens:14.80#/gal, full returns to surface. DV Tool @ 4,941', Float collar @ 11,077', Float shoe @ 11,160'. Test casing to 10,000 PSI for 15 min.

2/21/2018- Full BOPE test to 250PSI low/7500PSI high, good test.

2/22/2018- Test casing to 3740PSI for 30 min, test good. Drill 8-1/2" hole to 12,325'.

2/25/18- Notified BLM of intent to run and cement liner. Run 7 5/8" 29.70# P-110 Wedge 513 liner to 12,318'. Float collar @ 12,230', Float shoe @ 12,318'.

2/28/18-3/2/18- Cement liner in place, squeeze job: CL **C**, 640 sacks, Yld: 1.33/sack, Dens:14.8#/gal, WOC for 6 hrs, csg pressure: 3,500PSI. Drill 6-3/4" hole.

3/18/18- Drill to 19,844' TD.

3/19/18- Notified Patricia Hutchins @ BLM of intent to run and cement prod casing. Run 5-1/2" 20.00# P-110ICY TXP BTC casing to 12,152' & 5" 18# TXP BTC casing to 19,832', float collar @ 19,787', float shoe @ 19,832'.

3/21/18- Cement in place Lead w/CL H 1,002 sacks, Yld:1.20/sack, Dens:15.60#/gal and Tail:CL H 101 sacks, Yld:1.90/sack, Dens:16#/gal, full returns to surface.

3/22/18- Release rig

\*Final directional survey attached.