District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy, Minerals and Natural Resources Line Control of Control of

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

## GAS CAPTURE PLAN

| X Original            | Operator & OGRID No.: Matador Production Company (228937) |     |                |  |  |  |
|-----------------------|---|-----|----------------|--|--|--|
| ☐ Amended             | • •   | •   | Date: 11/28/17 |  |  |  |
| Reason for Amendment: |   | 194 |                |  |  |  |
|                       |   |     |                |  |  |  |

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

#### Well(s)/Production Facility - Name of facility

| The well(s) that will be located at the production facility are shown in the table below. |                          |                          |          |                   |                     |  |  |
|---|--------------------------|--------------------------|----------|-------------------|---------------------|--|--|
| Well Name   | API                      | Well Location<br>(ULSTR) | Footages | Expected<br>MCF/D | Flared or<br>Vented | Comments   |  |
| Dr. Ireland Fed<br>Com No. 121H   | 30-015-****              | UL-? Sec 19 T23S<br>R35E |          | +/- 1,000         | ~21 days            | Flare ~21 days on flowback before turn into TB. Time est. depends on sales connect and well cleanup. |  |
| Dr. Ireland Fed<br>Com No. 122H   | 30-045-****<br>029-46/23 | UL-? Sec 19 T23S<br>R35E |          | +/- 1,000         | ~21 days            | Flare ~21 days on flowback before turn into TB. Time est. depends on sales connect and well cleanup. |  |
| Dr. Ireland Fed<br>Com No. 123H   | 30-015-****              | UL-? Sec 19 T23S<br>R35E |          | +/- 1,000         | ~21 days            | Flare ~21 days on flowback before turn into TB. Time est. depends on sales connect and well cleanup. |  |
| Dr. Ireland Fed<br>Com No. 124H   | 30-015-****              | UL-? Sec 19 T23S<br>R35E |          | +/- 1,000         | ~21 days            | Flare ~21 days on flowback before turn into TB. Time est. depends on sales connect and well cleanup. |  |

## **Gathering System and Pipeline Notification**

The wells will be connected to production facilities after flowback operations are complete so long as the gas transporter system is in place. The gas produced from the production facilities should be connected to an Energy Transfer Partners gathering system. It will require ~750' of pipeline to connect each facility to the Energy Transfer Partners gathering system. Matador Production Company periodically provides a drilling, completion and estimated first production date for

Submit Original to Appropriate District Office wells that are scheduled to be drilled in the foreseeable future to Energy Transfer Limiters. If changes occur that will affect the drilling and completion schedule, Matador Production Company will notify Energy Transfer Partners. Additionally, the gas produced from the well will be processed at a processing plant further downstream and, although unanticipated, any issues with downstream facilities could cause flaring at the wellhead. The actual flow of the gas will be based on compression operating parameters and gathering system pressures measured when the well starts producing.

and a second of the second of

Flowback Strategy

After the fracture treatment/completion operations (flowback), the well will be produced to temporary production tanks and the gas will be flared or vented. During flowback, the fluids and sand content will be monitored. If the produced fluids contain minimal sand, then the well will be turned to production facilities. The gas sales should start as soon as the well starts flowing through the production facilities, unless there are operational issues on the midstream system at that time. Based on current information, it is Matador's belief the system will be able to take the gas upon completion of the well.

Safety requirements during cleanout operations may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

### **Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - o Operating a generator will only utilize a portion of the produced gas and the remainder of gas would still need to be flared
  - o Power Company has to be willing to purchase gas back and if they are willing they require a 5 year commitment to supply the agreed upon amount of power back to them. With gas decline rates and unpredictability of markets it is impossible to agree to such long term demands. If the demands are not met then operator is burdened with penalty for not delivering.
- Compressed Natural Gas On lease
  - o Compressed Natural Gas is likely to be uneconomic to operate when the gas volume declines.
- NGL Removal On lease
  - o NGL Removal requires a plant and is expensive on such a small scale rendering it uneconomic and still requires residue gas to be flared.