District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Date	9-6-18 GAS CAPTURE PLAN						
	Original Operator & OGRID No.: Mewbourne Oil Company - 14744 mended - Reason for Amendment:						
	Gas Capture Plan out completion (new drill,		•	-	reduce we	ll/production	facility flaring/venting for
Note.	Form C-129 must be sul	hmitted and app	roved prior to excee	ding 60 days a	llowed by Rul	e (Subsection A	of 19.15.18.12 NMAC).
Wel	l(s)/Production Facili	tv – Name of	facility				
				na ahaum in i	ha tahla hal	 .	
	well(s) that will be loc Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
	Pronghorn 15 B3CN Fed Com 1H	30-025- 14011	C - 15-23S-34E	185 FNL & 1700 FW	L 0	NA	ONLINE AFTER FRAC
Į						L	
Well place	e. The gas produced low/h	to a production from production pressure	n facility after flo tion facility is de gathering system	edicated to _ n located in	LUCID C	County, New	as transporter system is in and will be connected to Mexico. It will require arne Oil Company provides
be d	odically) to LUCID rilled in the foreseeab	le future. In s changes to Processing P	drilling, completion addition, Mewbood drilling and com Plant located in Se	n and estimate ourne Oil Completion scheme. 25, Two	ed first prod mpany and dules. Gas n. 185, Rng	uction date fo LUCID from these g. 25E , Ed	r wells that are scheduled to have periodic wells will be processed at dy County, New Mexico.
	•	ili be based on	compression open	aung paramei	ers and gaine	ering system p	oressures.
Afte flare sand	d or vented. During flo	owback, the flued to product	uids and sand con ion facilities. Gas	tent will be n	nonitored. V I start as so	When the prodon as the wel	action tanks and gas will be luced fluids contain minimal ls start flowing through the ed on current information, it

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

is Operator's belief the system can take this gas upon completion of the well(s).

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that

- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines