#### **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD Hobbs

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

## 5. Lease Serial No. NMNM7488

SUNDKT N	OTICES AN	D KEPUK 13	ON AAETE2
Do not use this	form for proj	oosals to drill (	or to re-enter an
abandoned well.	Use form 31	60-3 (APD) for	such proposals.

Do not use thi	is torm for proposals to (	ariii or to re-enter an			
abandoned we	6. If Indian, Allottee or	Tribe Name			
SUBMIT IN	7. If Unit or CA/Agreement, Name and/or No. 8910138170				
1. Type of Well  Gas Well Oth	ner	SEP 2	6 2018	8. Well Name and No. MLMU 275	
Name of Operator     OXY USA INCORPORATED	Contact:   E-Mail: david_stew	DAVID STEWARTEC	EIVED	9. API Well No. 30-025-32557-00	D-S1
3a. Address P O BOX 4294 HOUSTON, TX 77210-4294		3b. Phone No. (include area Ph: 432-685-5717	code)	10. Field and Pool or E LANGLIE	xploratory Area
4. Location of Well (Footage, Sec., T	11. County or Parish, State				
Sec 5 T24S R37E NESW 134	LEA COUNTY, NM				
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICATE NATUR	E OF NOTICE	, REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION		ТҮР	E OF ACTION		
Notice of Intent	☐ Acidize	Deepen	☐ Produc	tion (Start/Resume)	■ Water Shut-Off
	☐ Alter Casing	☐ Hydraulic Fractu	ring 🔲 Reclam	ation	■ Well Integrity
☐ Subsequent Report	□ Casing Repair	☐ New Construction			☐ Other
☐ Final Abandonment Notice	☐ Change Plans	and Abando	n ( Tempo:	rarily Abandon	
	☐ Convert to Injection	☐ Plug Back	☐ Water I	Disposal	
following completion of the involved testing has been completed. Final At determined that the site is ready for fit TD-3800' PBTD-3757' Pe 8-5/8" 24# csg @ 411' w/ 260: 5-1/2" 15.5# csg @ 3800' w/ 9  1. RIH & set CIBP @ 3408' w 2. M&P 25sx cmt @ 2920-27' 3. M&P 30sx cmt @ 1305-11' 4. M&P 60sx cmt @ 461' to S 10# MLF between plugs - About the strength of the streng	pandonment Notices must be file inal inspection. erfs-3458-3711' sx, 12-1/4" hole, TOC-Sur 125sx, 7-7/8" hole, TOC-Sur 1/ 40sx cmt to 3115' 70' WOC-Tag 10' WOC-Tag	f-Circ urf-Circ (7R/Ou/F (7a:/1:5) (7a:/1:5)	ncluding reclamation	ATTACHED	nd the operator has
14. I hereby certify that the foregoing is	Electronic Submission #4	31783 verified by the BLN A INCORPORATED, sent		n System	
	itted to AFMSS for process	ing by DEBORAH MCKINN	EY on 08/20/201		
Name (Printed/Typed) DAVID ST	EWARI	Title SR	REGULATOR	ADVISOR	<del></del>
Signature (Electronic S	Submission)	Date 08/	17/2018		
	THIS SPACE FO	R FEDERAL OR STA	TE OFFICE U	SE	
Approved By famos C	a. amos	Title •	Supr. Ac	£T	Date 9-13-18
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conductive th	itable title to those rights in the	subject lease Office	arished	Est Office	2
Title 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it a c	crime for any person knowingl	and willfully to m	ake to any department or a	agency of the United

#### OXY USA WTP LP - Current Myers Langlie Mattix Unit #275 API No. 30-025-32557

Anhy 1161

Salt 1255

Yates 2870

7R 3163

Qu 3522

Penrose 3658

12-1/4" hole @ 411' 8-5/8" csg @ 411' w/ 260sx-TOC-Surf-Circ

Perís @ 3458-3711' | Penírse & Queen

7-7/8" hole @ 3800' 5-1/2" csg @ 3800' w/ 925sx-TOC-Surf-Circ

PB-3757' /

TD-3800'

OXY USA WTP LP - Proposed Myers Langlie Mattix Unit #275 API No. 30-025-32557


60sx @ 461'-Surface

12-1/4" hole @ 411' 8-5/8" csg @ 411' w/ 260sx-TOC-Surf-Circ

30sx @ 1305-1110' WOC-Tag

25sx @ 2920-2770' WOC-Tag

CIBP @ 3408' w/ 40sx to 3115'



Perfs @ 3458-3711'

7-7/8" hole @ 3800' 5-1/2" csg @ 3800' w/ 925sx-TOC-Surf-Circ

PB-3757'

### BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

# Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.