

**HOBBS OCD**

OCT 22 2018  
RECEIVED

### Wellbore Diagram

API No.: 30-025-26344  
Spud Date: 8/30/1979

LG-3175

Hole Size:	17 inches	48#
Surface Casing:	13-3/8" OD	J-55
Set @	702 ft	
Cement Lead:	1,100 sx	CIRC 360 SX
	ppg	cf/sk
Cement Tail:		
TOC:	YES	Circulated
Hole Size:	12-1/4" inches	
Intermediate Casing:	9-5/8" OD	
Set @	5,200 ft	
Cement Lead:	1,450 sx	CIRCULATED 50 SX
	ppg	cf/sk
Cement Tail:		
TOC:	SURFACE	
FLINTCOAT:	--	Casing Tally
Est TOC:	ft	CBL Wire Line
Short Joint:	--	Wire Line
Short Joint:	--	Wire Line

Hole Size:	8-1/2"	inches
Prod. Cag:	7"	OD N-80 & P-110
Set @:	12,710 ft	
Cmt: Lead:	5x	Poz C
Lead Info:	1850.00 ppg	c/sk
Tail:	5x	Poz H
Tail Info:	000	c/sk

Rod Detail (top to bottom)			
Rods	Description	Footage	Depth
1	1-1/2" 26' polish rod		26.00
81	1" grade d/kd sucker rods w/ sh couplings		2,025.00
75	7/8" grade d/kd sucker rods w/ FH couplings		1,875.00
204	3/4" grade d sucker rods w/ ft couplings		5,100.00
1	3/4" grade d x2' pony rod		2.00
1	2-1/2"x1-1/2"x20' RHBC pump		20.00
			0.00
	rod string depth		9,048.00
			0.00
			0.00

Updated:	By:
	Mike Dennis