Submit 1 Copy Office	To Appropriate District	Stat	State of New Mexico		Form C-103 Revised July 18, 2013			
1625 N. French	Dr., Hobbs, NM 88240	5 000			WELL API N			
Submit 1 Copy To Appropriate District Office <u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88410 <u>District III</u> – (505) 334-6178			SERVATION South St. Fran	DIVISION	5. Indicate T		72707 /	
District III - (5 1000 Rio Brazo	05) 334-6178 os Rd., Aztec, NM 87410(7)	2 4 2010 1220 S	South St. Fran	cis Dr.	STATE TEE			
District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 874 10 C7 District IV - (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505					6. State Oil &	& Gas Lease No.		
87505	RE	CEID						
SUNDRY NÖTTCES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A						7. Lease Name or Unit Agreement Name		
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH						DRIVER BVE STATE		
PROPOSALS.)  1. Type of Well: Oil Well  Gas Well  Other					8. Well Number 2H			
2. Name of Operator EOG RESOURCES INC						9. OGRID Number 7377		
3. Address of Operator						10. Pool name or Wildcat		
PO BOX 2267 MIDLAND, TX 79702						BELL LAKE; BONE SPRING, NORTH		
4. Well Location								
Unit Letter E : 2090 feet from the NORTH line and 300 feet from the WEST line								
Section 14 Township 23S Range 33E NMPM County LEA								
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3668' GR								
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data								
NOTICE OF INTENTION TO:								
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING								
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS.☐ P AND A								
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB								
	E COMMINGLE  OOP SYSTEM							
OTHER:	OOP SYSTEM			OTHER:				
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date								
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of								
proposed completion or recompletion.								
EOG propose	es to plug this well usi	na the following	a procedure, p	resent depth 55	•			
	. •		g p. 000aa. 0, p	rooth dopin oo	•			
	, fill hole w/ 4.45 yds o	mt to surface						
2. WOC, top off to surface								
3. After filling w/redi mix, cut off locking device and install ground level dry hole marker								
						- 44-oh	had	
•						See Attach	jeu 	
					Con	ditions of A	Abblossi	
					<b>J</b>			
	04/00/004	_						
Spud Date:	04/30/201	5	Rig Release Dat	e:				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.								
A A A								
	Kan Mich	10	mum p Regu	latory Analyst		DATE 10/23	/2018	
SIGNATURE	The refund	rope	IIILE Regu	natory Analyst	=	_DATE10/23	2010	
Type or print	name Kay Maddox		E-mail address:	kay_maddox@ed	gresources.com	PHONE: 432-6	386-3658	
For State Use		$\bigcap$				•		
APPROVED	BY. Wahl	thitzhu-	TITLE P. E	ΞS.		DATE 10/2	4/2018	
	Approval (if any):		IXIDD .					

 Well Name:
 Driver BVE State #2H

 Location:
 2090' FNL & 300' FWL Sec. 14-23S-33E

 County:
 Lea, NM

 Lat/Long:
 32.306248885,-103.55068816 NAD83

 API #:
 30-025-42464

Spud Date: Compl. Date:

4/30/15

**Current Wellbore Diagram:** 

KB: GL: 3,668'

20" Hole



 Well Name: • Driver BVE State #2H

 Location: 2090' FNL & 300' FWL Sec. 14-23S-33E

Location: County:

Lat/Long:

API#:

Spud Date: Compl. Date:


Lea, NM 32.306248885,-103.55068816 NAD83 30-025-42464 4/30/15

## **Proposed Wellbore Diagram:**

KB: GL: 3,668'

20" Hole





## **GENERAL CONDITIONS OF APPROVAL:**

- 1) Insure all bradenheads have been exposed, identified, and valves are operational prior to rigging up on well.
- 2) Contact the appropriate NMOCD District Office no later than 24 hours prior to moving in and rigging up.
- 3) A copy of the approved C103 intent to P&A should be distributed to the onsite company and plugging representatives. Approved procedures are good for a period of one year from approved date, unless otherwise specified on the C103 intent. Approvals past this date will require the submission and approval of a new C103 intent.
- 4) A company representative is required to be present to witness all operations including setting CIBP's, circulation of mud laden fluids, perforating, squeezing or spotting cement plugs, tags, or any other operations approved on the C103 intent to P&A. Company representative should contact the NMOCD and report all operations.
- 5) Any changes that may be required during plugging operations should be approved by the NMOCD before proceeding.
- 6) A closed loop system is to be used for all plugging operations. Contents of the steel pits to be hauled to a NMOCD permitted disposal facility.
- 7) Mud laden fluids must be placed between all cement plugs mixed at 25 sacks of salt gel per 100 barrels of brine.
- 8) All cement plugs will be 100' or 25 sacks cement, whichever is greater. Class 'C' cement will be used above 7500' and Class 'H' below 7500'.