

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-45288

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

Lease Name or Unit Agreement Name

Lomas Rojas 26 State Com

8. Well Number 504H

9. OGRID Number
7377

10. Pool name or Wildcat
Red Hills/Lower Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
EOG Resources, Inc.

3. Address of Operator
P.O. Box 2267 Midland, TX 79702

4. Well Location
Unit Letter C : 714 feet from the North line and 2518 feet from the West line
Section 26 Township 25S Range 33E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3346 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/01/18 Run 9-5/8", 40#, J55, LTC (0'-3970')
Run 9-5/8", 40#, HCK55, LTC (3970'-4980')
Cmt lead 965 sx, Class C, 12.7 ppg, 2.32 yld
Tail 455 sx Class C, 14.8 ppg, 1.42 yld
Test to 1980 psi/30 min - good
Circ 300 sx to surface
Resume drilling 8-3/4" hole

Spud Date: 10/29/18

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Renee Jarratt TITLE Regulatory Analyst DATE 11/01/18

Type or print name Renee Jarratt E-mail address: PHONE: 432-686-3644

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 11/06/18

Conditions of Approval (if any):