Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
<u>District I</u> - (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	OIL CONSERVATION OF SIGN	3002545132
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87509 V 0 9 20	118 STATE A FEE
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa PC, INVI 67509	6. State Oil & Gas Lease No.
87505	RECEIV	ED
	CES AND REPORTS ON WELLS CALLS TO ALLS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLIC	ATION FOR PERMIT" (FORM C-101) FOR SUCH	COBALT 32 STATE
PROPOSALS.)  1. Type of Well: Oil Well	Gas Well 🔲 Other	8. Well Number 703H
2. Name of Operator		9. OGRID Number
EOG RESO  3. Address of Operator	JURCES	7377 10. Pool name or Wildcat
<u>-</u>	2267 MIDLAND TX 79702	WC025,G09 S2433361 Upper WC
4. Well Location		
	600 feet from the SOUTH line and	1852feet from the EASTline
Section 32	Township 24E Range 34E	NMPM County LEA COUNTY
	11. Elevation (Show whether DR, RKB, RT, GR,	etc.)
	3419' GL	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF IN	FENTION TO: SI	UBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON   REMEDIAL W	
TEMPORARILY ABANDON		DRILLING OPNS.☑ P AND A □
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CEM	IENT JOB
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM		
OTHER:		RILL CSG 🔀
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
SPUD 10/30/18 12-1/4" HOL	.E	
10/31/18		
Surface Casing @ 1,276'		
Ran: 9-5/8" 40# J-55 LTC Lead Cement w/ 410 sx Class C (13.5 ppg. 1.73 vld). Tail w/120 sx Class C (14.8 ppg. 1.33 vld)		
Lead Cement w/ 410 sx Class C (13.5 ppg, 1.73 yld), Tail w/120 sx Class C (14.8 ppg, 1.33 yld)  Test casing to 1,700 psi for 30 min - Good Resume Drilling		
S. ID.	Pic Poloso Potos	
Spud Date: 10/30/18	Rig Release Date:	
I hereby certify that the information a	bove is true and complete to the best of my knowl	ledge and belief.
9.1		
SIGNATURE / W	TITLE Sr. Regulatory Adr	ministrator DATE 11/06/18
Type or print name Emily Follis	E-mail address: emily_follis	@eogresources.coppONE: 432-848-9163
For State Use Only		and the state of t
APPROVED BY:	TITLE petroleum E	ngineer DATE 11/09/18
Conditions of Approval (if any):		